**SKU:** XE-050-3N6X-B

**UPC:** 0783669010916

**Features & Benefits:**

**Description:**Surgency Surge Protection, Commercial & Industrial, Lead Wire Size 10, 3 Phase, Delta System, 50kA Surge Current, 600 V, Indicator LED, Audible Alarm, Dry Relay Contact, UL, CSA

# Specs

## *Additional Class Attributes*

| | |
|---|---|
| **AC Frequency** | 50/60 Hz |
| **Mounting Method** | Mountable or flush mountable with flush mount kit |
| **Type Of Indicators** | Blue indicator LED |
| **Warranty** | 10 Year |

## *Additional Technical Specifications*

| | |
|---|---|
| **Nominal Voltage** | 600 V |

## *Conductor Ranges*

| | |
|---|---|
| **Conduit Hub Size** | 3/4 |
| **Lead Wire Size** | 10 AWG |

## *Dimensions*

| | |
|---|---|
| **Height (IN)** | 10.569 |
| **Height BX (IN)** | 4 |
| **Height (mm)** | 268.4526 |
| **Length (IN)** | 5.245 |
| **Length (mm)** | 133.223 |
| **Weight (LB)** | 0.962450665133076 |
| **Weight BX (LB)** | 3.35 |
| **Width (IN)** | 3.296 |
| **Width BX (IN)** | 6 |
| **Width (mm)** | 83.7184 |

## *Material and Finish*

| | |
|---|---|
| **Insulation** | NA |
| **Material** | Polycarbonate |

## *General*

| | |
|---|---|
| **Bag Quantity** | 1 |
| **Carton Quantity Description** | STD PACK QTY 1 |

| | |
|---|---|
| **NEMA Code** | 0-000-1 |
| **ULCSA Type** | 1 |
| **UPC Code** | 78366901091 |

## *Testing Standards*

| | |
|---|---|
| **CSA File Number** | NA |
| **CSA Standard** | C22.2 No. 269.1-14 |
| **Prop65 Compliance** | WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov |
| **UL Control Number** | E315947 |
| **UL / CULUS Specification** | UL/cUL 1449 Listed |
| **UL File Number** | E484255 |

## *Environment and Temperature*

| | |
|---|---|
| **Environmental Conditions** | Enclosure rated to NEMA/UL Type 1/2/3/3R/3X/4/4X |
| **Operating Temperature** | -40°C to 65°C |

## *Surge Specifications*

| | |
|---|---|
| **Dry relaying contact** | Yes |
| **Electrical Noise Filter** | No |
| **Nominal Discharge Current** | 20 kA |
| **Outlet** | None |
| **Phase** | 3 |
| **Short Circuit Current Rating (SCCR)** | 200 kA |
| **Surge Current Rating** | 50 kA |
| **System** | Delta |
| **UL Voltage Protection Rating L-G** | 3000 |
| **UL Voltage Protection Rating L-L** | 3000 |
| **UL Voltage Protection Rating L-N** | NA |
| **UL Voltage Protection Rating N-G** | NA |