SKU: XE-100-3D1X-B

UPC: 0783669011166

Features & Benefits:

Description: Surgency Surge Protection, Commercial & Industrial, Lead Wire Size 10, 3 Phase, Hi-Leg Delta System, 100kA Surge Current, 240D/120 V, Indicator LED, Audible Alarm, Dry Relay Contact, UL, CSA

Specs

Additional Class Attributes

AC Frequency	50/60 Hz
Mounting Method	Mountable or flush mountable with flush mount kit
Type Of Indicators	Blue indicator LED
Warranty	10 Year

Additional Technical Specifications

Nominal Voltage	240D/120 V

Conductor Ranges

Conduit Hub Size	3/4
Lead Wire Size	10 AWG

Dimensions

Height (IN)	10.569
Height BX (IN)	4
Height (mm)	268.4526
Length (IN)	5.245
Length (mm)	133.223
Weight (LB)	0.962450665133076
Weight BX (LB)	4.35
Width (IN)	3.296
Width BX (IN)	6
Width (mm)	83.7184

Material and Finish

Insulation	NA
Material	Polycarbonate

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1

NEMA Code	0-000-1
ULCSA Type	1
UPC Code	78366901116

Testing Standards

CSA File Number	NA
CSA Standard	C22.2 No. 269.1-14
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	E315947
UL / CULUS Specification	UL/cUL 1449 Listed
UL File Number	E484255

Environment and Temperature

Environmental Conditions	Enclosure rated to NEMA/UL Type 1/2/3/3R/3X/4/4X
Operating Temperature	-40°C to 65°C

Surge Specifications

Dry relaying contact	Yes
Electrical Noise Filter	No
Nominal Discharge Current	20 kA
Outlet	None
Phase	3
Short Circuit Current Rating (SCCR)	200 kA
Surge Current Rating	100 kA
System	Hi-leg delta
UL Voltage Protection Rating L-G	700/1200
UL Voltage Protection Rating L-L	1200/1800
UL Voltage Protection Rating L-N	700/1200
UL Voltage Protection Rating N-G	700