

MUNICIPAL PRODUCT CATALOG



ipexna.com

ISSUE DATE: JUNE 2026

- Pressure Piping Systems
- Water Service Systems
- Sewer Piping Systems
- Specialty Municipal Products



We build tough products for tough environments®



Committed to EXCELLENCE



As a leader in thermoplastic piping systems for over 50 years, IPEX USA LLC. provides proven products that have withstood the rigours of time – from large diameter transmission pipelines to 3/4" house connections.

Our PVC water and sewer systems do not corrode so they maintain the strength and flexibility required to handle soil movement, high traffic loads and deep burial applications. At IPEX, we ensure our systems outperform our competitors with:

- Quality assurance testing that exceeds standards
- Custom-designed PVC compounds
- Third-party certification of pipe and fittings from organizations such as Canadian Standards Association, Factory Mutual, Underwriter's Laboratories and NSF



Bookmark Our Website

ipexna.com



PRODUCT INFO,
TECHNICAL
DOCUMENTS,
ON-SIGHT TRAINING
& MUCH MORE ...



OUR PRESSURE PIPING SYSTEMS & SEWER PIPING SYSTEMS DESIGN MANUALS INCLUDE:

- Standards
- Specifications
- Dimensions
- Pressure Ratings
- Design Calculations
- and much more ...

[available at ipexna.com](http://ipexna.com)



Contents

07

EASY SPECIFICATIONS

PRESSURE PIPING SYSTEMS

Blue Brute Pipe
Blue Brute Fittings
Bionax PVCO Pipe
Bionax SR Pipe
IPEX Centurion
TerraBrute CR
CycleTough

37

WATER SERVICE SYSTEMS

Q-Line
Philmac® 3G™ Compression Fittings

47

SEWER PIPING SYSTEMS

Ring-Tite / Enviro-Tite
Ultra-Rib
Solvent Weld Sewer Fittings
Perforated Pipe
White Bionax PVCO

77

SPECIALTY PRODUCTS

PVC Manholes and Access Chambers
Vortex Flow Inserts
Storm Sewer Inlet Controls



MUNICIPAL EASY SPEC

PRODUCT	PRESSURE RATING			SIZE RANGE		STANDARDS	APPLICATIONS
PRESSURE PIPING SYSTEMS							
Blue Brute® PVC Pipe (CIOD)	DR25	165 psi	(1135 kPa)	4 - 12"	(100 - 300 mm)	CSA B137.3 certified AWWA C900 FM 1612 approved NSF Std. 61 certified BNQ 3624-250*	Water transmission mains Water distribution mains Sewer forcemains Fire lines Industrial process lines Irrigation piping
	DR18	235 psi	(1620 kPa)	4 - 12"	(100 - 300 mm)		
	DR14	305 psi	(2100 kPa)	4 - 12"	(100 - 300 mm)		
Blue Brute® Moulded PVC Fittings (CIOD)		235 psi	(1620 kPa)	4 - 12"	(100 - 300 mm)	CSA B137.2 certified AWWA C900 FM 1612 approved NSF Std. 61 certified BNQ 3624-250*	Water transmission mains Water distribution mains Sewer forcemains Fire lines Industrial process lines Irrigation piping
Bionax® PVCO Pipe (CIOD)	CIOD	235 psi	(1620 kPa)	6 - 24"	(150 - 600 mm)	CSA B137.3.1 certified CIOD Protocol BNQ 3624-500 AWWA C909, FM approved NSF Std. 14 certified NSF Std. 61 certified BNQ NQ 3660-950*	Water transmission mains Water distribution mains Sewer forcemains**
	CIOD	165 psi	(1135 kPa)	14 - 24"	(350 - 600 mm)		
Bionax® SR PVCO Pipe (CIOD)	CIOD	235 psi	(1 620 kPa)	6 - 12"	(150 - 300 mm)	CSA B137.3.1 certified CIOD AWWA C909, FM approved NSF Std. 14 certified NSF Std. 61 certified BNQ 3660-950*	Water transmission, distribution and sewer mains in seismic sensitive areas
IPEX Centurion® PVC Pipe	SDR51	80 psi	(550 kPa)	24 - 60"	(600 - 1500 mm)	CSA B137.3 certified AWWA C900 NSF Std. 61 certified BNQ 3624-250*	Water transmission mains Sewer forcemains Irrigation piping Gravity sewer mains
	SDR41	100 psi	(690 kPa)	14 - 60"	(350 - 1500 mm)		
	SDR32.5	125 psi	(860 kPa)	14 - 42"	(350 - 1050 mm)		
	DR25	165 psi	(1130 kPa)	14 - 36"	(350 - 900 mm)		
	DR18	235 psi	(1620 kPa)	14 - 30"	(350 - 750 mm)		
	DR14	305 psi	(2100 kPa)	14 - 16"	(350 - 400 mm)		
IPEX Centurion Fabricated PVC Fittings (CIOD)		165 psi	(1130 kPa)	14 - 60"	(350 - 1500 mm)	CSA B137.3 certified AWWA C900 NSF Std. 61	Water transmission mains Sewer forcemains Irrigation piping Gravity sewer mains
		235 psi	(1620 kPa)				
Fusible™ Brute Fused-Joint PVC Pipe DR = CIOD SDR = IPSOD	SDR26	160 psi	(1100 kPa)	4 - 24"	(100 - 600 mm) (12.2 m lengths)	CSA B137.3 certified AWWA C900 NSF Std. 61 certified BNQ 3624-250*	Water transmission mains Water distribution mains Sewer forcemains Pipe bursting Storm drains Irrigation piping Trenchless applications
	DR25	165 psi	(1130 kPa)				
	SDR21	200 psi	(1380 kPa)				
	DR18	235 psi	(1620 kPa)				
	DR14	305 psi	(2100 kPa)				
TerraBrute® CR Restrained-Joint PVC Pipe (CIOD)	DR18	235 psi	(1620 kPa)	8 - 24"	(200 - 600 mm)	CSA B137.3 certified AWWA C900 NSF Std. 61 certified Compliant BNQ 3624-250* Compliant BNQ 3660-950*	Horizontal directional drilling Pipe bursting Seismic zone piping Casing installations Steep slope pipelines Bridge crossings
	DR14	305 psi	(2100 kPa)	4 & 6"	(100 & 150 mm)		
CycleTough® PVC Series Pipe (IPSOD)	SDR41	100 psi	(690 kPa)	4 - 24"	(100 - 600 mm)	CSA B137.3 certified ASTM D2241 NSF Std. 61 certified	Potable water piping Sewer forcemains Reclaimed water piping Agriculture/Golf/Turf irrigation Industrial piping
	SDR32.5	125 psi	(860 kPa)	3 - 24"	(75 - 600 mm)		
	SDR26	160 psi	(1100 kPa)	1-1/2 - 24"	(40 - 600 mm)		
	SDR21	200 psi	(1380 kPa)	1-1/2 - 24"	(40 - 600 mm)		
CycleTough® Moulded PVC Fittings (IPSOD)		200 psi	(1380 kPa)	1-1/2 - 8"	(40 - 200 mm)	NSF B137.2 Certified 4000 psi HDB	Potable water systems Sewage force mains Golf course and other irrigation
CycleTough® Fabricated PVC Fittings (IPSOD)		160 psi	(1100 kPa)	10 - 24"	(250 - 600 mm)	NSF B137.3 Certified	Potable water piping Sewer forcemains Reclaimed water piping Golf course irrigation piping Other irrigation piping Industrial piping

* For BNQ Standards, not all sizes, pressure ratings, and manufacturing facilities are included in certifications.

** See White Bionax PVCO Sewer Pressure Pipe (CIOD)

PRODUCT		PRESSURE RATING		SIZE RANGE		STANDARDS	APPLICATIONS
WATER SERVICE SYSTEMS							
Q-Line™ PE-AL-PE Service Tubing	200 psi @ 73.4°F (1380 kPa @ 23°C) 100 psi @ 180°F (690 kPa @ 82°C)		3/4 & 1"	(20 & 25 mm)		CSA B137.9 certified AWWA C903 ASTM F1282 NSF Std. 14 certified NSF Std. 61 certified	Water service Reclaimed water
SEWER PIPING SYSTEMS							
Ring-Tite® PVC Sewer Pipe (PSM)	DR35		4 - 60"	(100 - 1500 mm)		CSA B182.2 certified ASTM D3034 ASTM F679 ASHTO M278 BNQ 3624-130* & 3624-135*	Sanitary sewer Storm sewer Industrial effluent
Enviro-Tite® PVC Sewer Pipe (PSM)	DR35		4 - 15"	(100 - 375 mm)		CSA B182.2 certified ASTM D1760 BNQ 3624-130* & 3624-135*	Sanitary sewer Storm sewer Industrial effluent
Ring-Tite® Heavy Wall PVC Sewer Pipe (PSM)	DR28		4 - 6"	(100 - 150 mm)		Certified to CSA B182.2 BNQ 3624-130* & 3624-135*	Sanitary sewer laterals Storm sewer laterals
Enviro-Tite® PVC Sewer Pipe (PSM)	DR28		4 - 6"	(100 - 150 mm)		Certified to CSA B182.2 BNQ 3624-130* & 3624-135*	Sanitary sewer laterals Storm sewer laterals
Ring-Tite® Gasketed Sewer Fittings (PSM)			4 - 60"	(100 - 1500 mm)		CSA B182.2 certified ASTM D3034 ASTM F679	Sanitary sewer Storm sewer Industrial effluent
IPEX Centurion® PVC Pipe (CIOD)	DR51 DR41		24 - 60"	(600 - 1500 mm)		CSA B137.3 certified AWWA C900	Sanitary sewer Storm sewer Industrial effluent
Ultra-Rib® PVC Sewer Pipe (Open profile OD)			8 - 24"	(200 - 600 mm)		CSA B182.4 certified ASTM F794	Sanitary sewer Storm sewer Highway / culvert
Ultra-Rib® PVC Sewer Fittings (Open profile OD)			8 - 24"	(200 - 600 mm)		CSA B182.4 certified ASTM F794	Sanitary sewer Storm sewer Highway / culvert
Ultra-X2® PVC Sewer Pipe & Fittings (Open profile OD)			30 & 36"	(750 & 900mm)		CSA B182.4 ASTM F794	Storm sewer Highway / culvert
White Bionax® PVCO Sewer Pressure Pipe (CIOD)	CIOD CIOD	235 psi 165 psi (1620 kPa) (1135 kPa)	6 - 18" 16 - 18"	(100 - 450 mm) (400 - 450 mm)		CSA B137.3.1 Protocol BNQ 3624-500 AWWA C909 NSF Std. 14 certified	Sewer forcemains

* For BNQ Standards, not all sizes, pressure ratings, and manufacturing facilities are included in certifications.



BIONAX®
PVC O PRESSURE PIPE

STRENGTH, TOUGHNESS AND FLEXIBILITY

BIONAX is a plastic pipe tougher than any piping material on the market. It requires no delicate internal or external coatings or expensive cathodic protection to resist corrosion.

BIONAX is made of biaxially oriented PVC (PVCO), a material with almost double the hydrostatic strength and three times the impact resistance of conventional PVC. It is engineered to withstand the rigors of today's installations, yet easier to install and to handle than conventional pipes.

BIONAX has the smallest carbon footprint of any commercially available piping material – proven in two independent academic studies.

BIONAX is fully certified to CSA, AWWA and ASTM standards.

The answer is obvious...

✓ REDUCE INSTALLATION COSTS ✓ REDUCE OPERATING COSTS ✓ PROTECT THE ENVIRONMENT

BIONAX PVCO Pressure Pipe...the only CHOICE!

Proven in tough North American climates for more than 50 years, IPEX AWWA municipal pressure pipe & fittings are manufactured from custom engineered PVC compounds to deliver superior strength and corrosion resistance, along with the ability to flex without damage – even under high traffic loads and in deep burial applications. IPEX AWWA PVC pressure pipe offers long-term performance unmatched by any other pipe material.

PRESSURE PIPE & FITTINGS



Blue Brute Pipe	8
Blue Brute Fittings	12
Bionax PVCO Pressure Pipe	6
Bionax SR Pressure Pipe	18
IPEX Centurion	20
TerraBrute CR	26
CycleTough Piping Systems	30

BLUE BRUTE PIPE

4" – 12" (100mm – 300mm)

BLUE BRUTE

Designed for municipal water applications, Blue Brute AWWA C900 pressure pipe delivers superior strength with corrosion resistant performance and the ability to flex without damage. Made with a high-strength, high-impact PVC compound, Blue Brute pipes perform even under high traffic loads and deep burial conditions.

Manufactured with cast-iron outside diameters, Blue Brute is compatible with existing infrastructure of older iron pipes with no special transition fittings required. Blue Brute pressure pipe is hydrostatically proof tested to two times its pressure class/rating ensuring the integrity of every length of pipe that goes into the ground.

APPLICATIONS

- Municipal Water Systems
- Fire Lines
- Industrial Lines
- Forcemains
- Irrigation Lines

STANDARDS



ADVANTAGES

- 1 Corrosion-Proof Performance**
IPEX Blue Brute systems are immune to corrosion from aggressive soils and galvanic action.
- 2 Superior Hydraulics**
The glass-like finish of PVC reduces friction losses and eliminates the tuberculation common in iron pipes. As a result, pumping costs are reduced and water quality is maintained.
- 3 Cast-Iron Outside Diameter (CIOD)**
Blue Brute systems are manufactured with a cast-iron outside diameter (CIOD). This is compatible with waterworks valves, appurtenances and restrainers.
- 4 Bottle-tight Joints, Removable Gaskets**
IPEX's patented gasket system not only withstands many times the rated system pressure, but also withstands full vacuum pressures. The removable gasket system allows special oil-resistant (nitrile) gaskets to be easily installed when working in contaminated soils.
- 5 Third-party Certification**
All IPEX municipal systems are third-party certified as applicable. In addition, IPEX Blue Brute systems have Factory Mutual approval and Underwriter's Laboratories (ULI and ULC) listings



DID YOU KNOW?

Each piece of Blue Brute is hydrostatically tested to two times its pressure class, ensuring excellent performance in the field.



CONSERVATIVE DESIGN

The pressure class/rating is extremely conservative. For example, for DR18 pipe the pressure capacity is 235 psi (1620 kPa), but the minimum burst pressure is 755 psi (5210 kPa).

Dimension Ratio	AWWA Pressure Class	CSA Pressure Rating
14	305	305
18	235	235
25	165	165

SHORT FORM SPECIFICATIONS

GENERAL

Blue Brute pipe shall be certified to CSA B137.3 "Rigid Polyvinyl Chloride PVC Pipe for Pressure Applications" and shall conform to AWWA C900 "Polyvinyl Chloride (PVC) Pressure Pipe, 4" – 12" for Water Transmission and Distribution." Blue Brute DR25 pipe shall have a pressure class/rating of 1120 kPa (165 psi). DR18 pipe shall have a pressure class/rating of 1620 kPa (235 psi). DR14 pipe shall have a pressure class/rating of 2100 kPa (305 psi).

MATERIAL

Blue Brute pipe shall be made from PVC compound conforming to ASTM D1784 cell class 12454.

PRODUCT

Pipe shall be suitable for use at maximum hydrostatic working pressure equal to the pressure class/rating at 73°F (23°C). Laying lengths shall be 10 or 20 feet (3 or 6.1 meters). Pipe shall have cast-iron outside diameters. Each length of pipe must be proof-tested at two times the pressure class.

JOINING



The gasket shall be carefully fitted to the bell groove if not already factory installed. Both bell and spigot shall be clean and free of debris before approved lubricant is applied. The pipe and/or fittings shall be joined by push-fitting bell-and-spigot joint to

the depth line marked on the spigot. When pipe has been cut in the field, the end shall be made square and beveled to a 15° chamfer. All insertion lines should be re-drawn, according to the IPEX Pressure Pipe Installation Guide.

Blue Brute fittings shall conform to AWWA C907 "Polyvinyl Chloride (PVC) Pressure Fittings for Water (4" through 12")" and be certified to CSA B137.2 "PVC Injection Molded Gasketed Fittings for Pressure Applications." They shall also be FM approved.

FABRICATED FITTINGS

Fabricated fittings shall be made from segments of AWWA C900 PVC pipe. Segments are bonded together and may be over-wrapped with fiberglass-reinforced polyester. The pressure class must match the pipe. The fittings must meet the requirements of CSA B137.3.



PRODUCT SELECTION CHART


Length: 20 feet | Color: Blue

		Size		Product Code	Avg. ID		Min. Wall Thickness		Avg. OD	
		in	mm		in	mm	in	mm	in	mm
PVC Pressure Pipe										
Class/Rating 165 CIOD DR 25	4	100	070104	4.42	112	0.192	5	4.80	122	
	6	150	070106	6.35	161	0.276	7	6.90	175	
	8	200	070108	8.33	212	0.362	9	9.05	230	
	10	250	070110	10.21	260	0.444	11	11.10	282	
	12	300	070112	12.15	309	0.527	13	13.20	335	
Class/Rating 235 CIOD DR 18	4	100	070514	4.27	108	0.267	7	4.80	122	
	6	150	070516	6.13	155	0.383	10	6.90	175	
	8	200	070518	8.05	204	0.502	13	9.05	230	
	10	250	070520	9.87	250	0.616	16	11.10	282	
	12	300	070522	11.73	297	0.733	19	13.20	335	
Class/Rating 305 CIOD DR 14	4	100	070414	4.11	104	0.343	9	4.80	122	
	6	150	070416	5.91	149	0.493	13	6.90	175	
	8	200	070418	7.76	198	0.646	16	9.05	230	
	10	250	070420	9.51	242	0.793	20	11.10	282	
	12	300	070422	11.31	287	0.943	24	13.2	335	

IPEX TECHNICAL MANUALS available at ipexna.com



Obtaining the
most up-to-date
technical information
has never been easier
with our innovative
ON-LINE MANUALS



WHAT YOU CAN DO



Zoom to specific paragraph
or chart for easy reading



Download as PDFs



Search document
for key words



Environmentally
Friendly!



Save and email clippings
for ultimate convenience



Visit ipexna.com
& check it out!

BLUE BRUTE FITTINGS

Blue Brute Fittings: 4" – 12" (100mm – 300mm)
IPEX Centurion Fittings: 14" – 60" (350mm – 1500mm)



Blue Brute fittings are injection molded and are even tougher than the pipe. Injection molded Blue Brute fittings have a wall thickness 25% greater than DR18 pipe, and some custom-made fabricated fittings are wrapped with a tough layer of fiberglass for extra protection.

APPLICATIONS

- Municipal Water Systems
- Fire Lines
- Industrial Lines
- Forcemains
- Irrigation Lines

STANDARDS




ADVANTAGES

- 1 Corrosion-Proof Performance**
Blue Brute systems are immune to corrosion from aggressive soils and galvanic action.
- 2 Superior Hydraulics**
The glass-like finish of PVC reduces friction losses and eliminates the tuberculation common in iron pipes. As a result, pumping costs are reduced and water quality is maintained.
- 3 Strength**
A thicker bell results in a more robust fitting.
- 4 Gasket Options**
All Blue Brute fittings are shipped with standard gaskets that accept cast-iron-sized PVC pipe. Non-pressure rated transition gaskets for IPS-sized pipe are an option. For applications where fittings must be buried in soil with hydrocarbon contamination, Nitrile gaskets are available.
- 5 Saves Time & Money**
A consistent O.D. for each size, simplifies the restraint selection. Each fitting is labeled with the O.D. information for easy identification and restraint selection.





PRODUCT SELECTION CHART – PC/PR 235 psi (1620 kPa)



Bell OD for Joint Restraint Selection

Size		Min.	Max.
4"	100 mm	5.44"	5.61"
6"	150 mm	7.84"	8.03"
8"	200 mm	10.29"	10.55"
10"	250 mm	12.69"	12.96"
12"	300 mm	15.07"	15.46"
14"	350 mm	17.28"	17.73"
16"	400 mm	19.64"	20.17"

11-1/4° Elbow B x B



	Dimension		Product Code
	inches	mm	
*	4	100	273104
	6	150	073091
	8	200	073092
*	10	250	273093
*	12	300	273094

22-1/2° Elbow B x B



	4	100	073105
	6	150	073106
	8	200	073107
	10	250	373108
	12	300	373109

45° Elbow B x B



	4	100	073120
	6	150	073121
	8	200	073122
	10	250	373123
	12	300	373124

90° Elbow B x B



	4	100	073150
	6	150	073151
	8	200	073152

DR18, 5° CIOD Bend




	6	150	273076
	8	200	273077
*	10	250	273078
*	12	300	273079

* Denotes Fabricated Fitting



PRODUCT SELECTION CHART - PC/PR 235 PSI (1620 KPA)

Tee B x B x B




Dimension		Product Code
inches	mm	
4 x 4 x 4	100 x 100 x 100	073285
6 x 6 x 4	150 x 150 x 100	073241
6 x 6 x 6	150 x 150 x 150	073286
8 x 8 x 4	200 x 200 x 100	073242
8 x 8 x 6	200 x 200 x 150	073243
8 x 8 x 8	200 x 200 x 200	073287
10 x 10 x 4	250 x 250 x 100	373239
10 x 10 x 6	250 x 250 x 150	373244
10 x 10 x 8	250 x 250 x 200	373250
10 x 10 x 10	250 x 250 x 250	373288
12 x 12 x 4	300 x 300 x 100	373727
12 x 12 x 6	300 x 300 x 150	373245
12 x 12 x 8	300 x 300 x 200	373246
12 x 12 x 10	300 x 300 x 250	373247
12 x 12 x 12	300 x 300 x 300	373289

Hydrant Tee B x B x B



6 x 6 x 6	150 x 150 x 150	373011
8 x 8 x 6	200 x 200 x 150	373010
10 x 10 x 6	250 x 250 x 150	273989
12 x 12 x 6	300 x 300 x 150	273070

Reducing Adapter (Bell x Spigot)



6 x 4	150 x 100	073211
8 x 6	200 x 150	073212
10 x 8	250 x 200	273213
12 x 10	300 x 250	073214

Coupling with Stop B x B




4	100	073030
6	150	073031
8	200	073032
10	250	373028
12	300	373032

Hammer Tee B x B x B



12 x 12 x 6	300 x 300 x 150	373249
-------------	-----------------	--------

Repair Coupling B x B



Dimension		Product Code
inches	mm	
4	100	073404
6	150	073406
8	200	073408
10	250	373027
12	300	373031

Single Tapped Coupling (AWWA Thread)



4 x 4 x 3/4	100 x 100 x 20	073267
4 x 4 x 1	100 x 100 x 25	073268
6 x 6 x 3/4	150 x 150 x 20	073256
6 x 6 x 1	150 x 150 x 25	073257
6 x 6 x 1-1/4	150 x 150 x 32	073144
6 x 6 x 1-1/2	150 x 150 x 40	273300
8 x 8 x 3/4	200 x 200 x 20	073259
8 x 8 x 1	200 x 200 x 25	073260
8 x 8 x 1-1/4	200 x 200 x 32	073147
8 x 8 x 1-1/2	200 x 200 x 40	273265
8 x 8 x 2	200 x 200 x 50	073266
10 x 10 x 3/4	250 x 250 x 20	373535
10 x 10 x 1	250 x 250 x 25	373537
*10 x 10 x 1-1/2	250 x 250 x 40	273044
*10 x 10 x 2	250 x 250 x 50	273045
12 x 12 x 3/4	300 x 300 x 20	373536
12 x 12 x 1	300 x 300 x 25	373538
*12 x 12 x 1-1/2	300 x 300 x 40	273046
*12 x 12 x 2	300 x 300 x 50	273048

* One-piece machined coupling. Note: 3/4" (20mm) Taps to 2" (50mm).
Taps: AWWA Thread


Double Tapped Coupling (AWWA Thread)



6 x 6 x 3/4 x 3/4	150 x 150 x 20 x 20	073305
6 x 6 x 1 x 1	150 x 150 x 25 x 25	073308
8 x 8 x 3/4 x 3/4	200 x 200 x 20 x 20	073290
8 x 8 x 1 x 1	200 x 200 x 25 x 25	073307

Note: 3/4" (20mm) Taps to 1" (25mm).
Taps: AWWA Thread

PRODUCT SELECTION CHART - PC/PR 235 PSI (1620 KPA)

	Dimension		Product Code
	inches	mm	
	6 x 4*	150 x 100	273226
	8 x 6*	200 x 150	273227
	10 x 6*	250 x 150	273228
	10 x 8*	250 x 200	273229
	12 x 8*	300 x 200	273231
	12 x 10*	300 x 250	273232

Plug Plain End




4	100	073180
6	150	073181
8	200	073182
10	250	073183
12	300	073184

Tapped Plug (I.P.S. Threads)



4 x 3/4	100 x 20	273192
4 x 1	100 x 25	073193
4 x 1-1/2	100 x 40	073194
4 x 2	100 x 50	273195
6 x 3/4	150 x 20	273199
6 x 1	150 x 25	273200
6 x 1-1/2	150 x 40	273201
6 x 2	150 x 50	273196
8 x 3/4	200 x 20	073203
8 x 1	200 x 25	073204
8 x 1-1/2	200 x 40	073197
8 x 2	200 x 50	273198

Cast Iron Size x I.P.S. Transition Gasket




4	100	073655
6	150	073611
8	200	073656
12	300	173390

Gasket drawing is for information only. Actual gasket may be different.


Note: 10" (250mm) will be available shortly

C900 Bell x Flange Adapter




4*	100	273015
6*	150	273016
8*	200	273017
10*	250	273018
12*	300	273019

C900 (Spigot) x I.P.S. (Bell) Adapter



4	100	273346
6	150	273347

SBR Gasket



4	100	072344
6	150	072346
8	200	273348
10	250	072350
12	300	072352

Gasket drawing is for information only. Actual gasket may be different.

Nitrile Gasket (Oil Resistant)

4	100	072924
6	150	072926
8	200	072928
10	250	072930
12	300	072932

EPDM Gasket

4	100	272048
6	150	272011
8	200	272039
10	250	272040
12	300	272012

BIONAX PVCO PRESSURE PIPE

6" - 24" (150 - 600mm)

BIONAX®

Imagine a pipe with all the benefits associated with conventional PVC, yet dramatically stronger and more impact resistant.

Bionax pipe is made from molecularly-oriented PVC compound (known as PVCO) and is designed primarily for water mains and sewage forcemains. Made from molecular orientation PVC material, Bionax has almost double the strength of conventional PVC and three times the impact absorption capability. The result is a pipe with enhanced toughness and flexibility.

Bionax is specially engineered to withstand the rigors of today's installations. With less construction inspection and less regular maintenance, the market is calling for a pipe that is more robust, stronger and easier to install. Bionax delivers on all three counts.

Molecularly Oriented PVC Pipe for Municipal Applications

Bionax's molecularly oriented orientation dramatically enhances the pipe properties that are important to pipeline designers:

- Larger internal diameters increase flow rates and reduce pumping costs
- Higher cyclic fatigue resistance for forcemain and irrigation applications
- Tighter bend radius when compared to standard PVC pipe

FEATURES & BENEFITS

- 1 Circumferential Tensile Strength**
Bionax has almost double the tensile strength of conventional PVC (12,100 psi vs. 7,000 psi). This higher strength results in larger inside diameters, improving the hydraulics of the pipe.
- 2 Impact Strength**
Bionax provides more than triple the impact strength of standard PVC pipe. PVCO pipe can withstand extreme jobsite conditions with no damage.
- 3 Crack Resistance**
PVCO's laminar structure prevents crack propagation, preventing damage to the pipe.
- 4 Longitudinal Tensile Strength**
Bionax has higher tensile strength in the axial direction, which allows a tighter bend radius than other materials.
- 5 Certification**
Bionax is third party certified to CSA B137.3.1 and AWWA C909.

APPLICATIONS

- Water Mains
- Sewage Forcemains*
- Industrial Process Piping

STANDARDS



* See White Bionax in "Sewer Piping Systems" section for sewage specific Bionax



SIZES & RATINGS CIOD PIPE

Pressure Class Rating at
73°F / 23°C for 165 psi / 1135 kPa

Pipe Size		OD		Product Code	
in	mm	in	mm		
14	350	15.3	389	120006/120022	*
16	400	17.4	442	120003/120023	*
18	450	19.5	495	120005/120024	*
20	500	21.6	549	120010	
24	600	25.8	655	120011	

* Please validate Product Code before placing an order.

Pressure Class Rating at
73°F / 23°C for 235 psi / 1620 kPa

Pipe Size		OD		Product Code	
in	mm	in	mm		
6	150	6,9	175	118001	
8	200	9,05	230	118002	
10	250	11,1	282	118003	
12	300	13,2	335	118004	
14	350	15,3	389	120001/120019	*
16	400	17,4	442	120002/120020	*
18	450	19,5	495	120004/120021	*
20	500	21,6	549	120007	
24	600	25,8	655	120008	

* Please validate Product Code before placing an order.



DID YOU KNOW?

Every length of CIOD Bionax is hydrotested to AWWA standards before being shipped. In fact, IPEX is the only manufacturer to have third-party certification (by NSF) to meet the stringent AWWA standards and by CSA to meet the CSA Standards.

SHORT FORM SPECIFICATIONS

SCOPE

This specification provides the requirements for molecularly oriented polyvinyl chloride (PVCO) pipe for potable-water systems and other pressure-pipe applications.

MATERIALS

- PVCO pipe shall be manufactured from rigid polyvinyl chloride (PVC) compound meeting the requirements of ASTM D1784 cell class 12454.
- Gaskets shall meet ASTM F477 for high-head applications.

HYDROSTATIC DESIGN BASIS

- Starting-stock PVC pipe shall have a hydrostatic design basis (HDB) of 4000 psi.
- Finished PVCO pipe shall have an HDB of 7100 psi.

PIPE

- Pipe shall be molecularly oriented (molecularly oriented in hoop and axial directions).
- Pipe shall be produced with cast-iron-pipe outside diameters (CIOD) in all sizes.
- Pipe shall be joined by integral-bell gasketed joints conforming to ASTM D3139.
- Pipe spigot ends shall be chamfered by the manufacturer.
- Pipe ends shall be capped at the production facility prior to storage and shipping.
- Pipe shall be colour-coded blue.

CIOD CERTIFICATIONS

- PVC compound shall be CSA-certified to ASTM D1784 cell-class 12454.
- PVCO pipe shall be CSA-certified to CSA Standard B137.3.1 and third-party certified to NSF Standard 14 and AWWA Standard C909.
- PVCO pipe joints shall be third-party certified to ASTM D3139.

STANDARDS

PVCO pipe shall conform to the following standards:

- ANSI/NSF Standard 14: Plastic Piping System Components and Related Materials
- ANSI/NSF Standard 61: Drinking Water System Components – Health Effects
- ASTM D1784: Rigid Polyvinyl Chloride (PVC) Compounds
- ASTM D3139: Joints for Plastic Pressure Pipes Using Flexible Elastomeric Seals
- ASTM F477: Elastomeric Seals (Gaskets) for Joining Plastic Pipe
- AWWA C909-09: Molecularly Oriented Polyvinyl Chloride (PVCO) Pressure Pipe, 4 Inch through 24 inch (100 mm Through 600 mm)
- CSA B137.3.1: Molecularly oriented polyvinyl chloride (PVCO) pipe for pressure applications

BIONAX SR SEISMIC WATER PIPE

6" – 12" (150mm – 300mm)



Bionax SR™ – Seismic Water Pipe – combines the same strength, toughness and flexibility as standard Bionax pipe with the enhanced seismic-resistance benefits of an extended bell. The result is a municipal water transmission and distribution system which performs better than any pipe product available today. Bionax SR can absorb lateral ground strain of seismic events and provides other performance benefits including product consistency, industry standard dimensions and corrosion-resistant attributes for a North American jobsite.

The molecular orientation and the extended bell of Bionax SR pipe provide excellent pipe and joint flexibility—precisely what is required from a water pipe if it is to remain intact after a seismic event.

APPLICATIONS


- Municipal Water Systems
- Fire Lines
- Industrial Lines
- Forcemains

STANDARDS



FEATURES & BENEFITS

- 1 Circumferential Tensile Strength**
Bionax SR has almost double the tensile strength of conventional PVC (12,100 psi vs. 7,000 psi). This higher strength results in larger inside diameters, improving the hydraulics of the pipe.
- 2 Impact Strength**
Bionax SR provides more than triple the impact strength of standard PVC pipe. PVCO pipe can withstand extreme jobsite conditions with no damage.
- 3 Crack Resistance**
PVCO's laminar structure prevents crack propagation, preventing damage to the pipe.
- 4 Longitudinal Tensile Strength**
Bionax SR has higher tensile strength in the axial direction, which allows a tighter bend radius than other materials.
- 5 Light-weight**
e.g. 300mm PC 235 psi pipe = 236 lbs.
- 6 Corrosion-proof & Consistent O.D.**
- 7 Certification**
Bionax SR is third party certified to CSA B137.3.1 and AWWA C909.



SIZES & RATINGS CIOD PIPE

Pressure/Class Rating at 73°F / 23°C for 235 psi / 1620 kPa

Product Code	Size		Average OD		Min. Wall Thickness		Average ID		Insertion Depth			
	inches	mm	inches	mm	inches	mm	inches	mm	Minimum		Maximum	
118101	6	150	6.90	175	0.221	5.62	6.44	163	6.6	167	7.6	192
118102	8	200	9.05	230	0.290	7.36	8.44	214	8.1	207	9.1	232
118103	10	250	11.10	282	0.356	9.03	10.35	263	8.5	217	9.5	242
118104	12	300	13.2	335	0.423	10.74	12.31	313	10.9	277	11.9	302

SHORT FORM SPECIFICATIONS

SCOPE

This specification provides the requirements for Bionax SR molecularly oriented polyvinyl chloride (PVCO) pipe for potable-water systems and other pressure-pipe applications. Bionax SR Gasketed cast-iron-pipe outside diameter (CIOD) Pressure pipe is available in the following pressure classes and nominal sizes:

- PC 235psi 6" through 12" (150mm – 300mm)

MATERIALS

- Bionax SR pipe shall be manufactured from rigid polyvinyl chloride (PVC) compound meeting the requirements of ASTM D1784 cell class 12454.
- Bionax SR gaskets shall meet ASTM F477 for high-head applications

HYDROSTATIC DESIGN BASIS

- Starting-stock for Bionax SR shall have a hydrostatic design basis (HDB) of 4000 psi and finished pipe shall have an HDB of 7100 psi as determined by testing in accordance with ASTM D1598, with data evaluated in accordance with ASTM D2837.

PIPE

- Bionax SR shall be manufactured with cast-iron-pipe outside diameters (CIOD) in all sizes. Pipe walls shall meet minimum thickness requirements for AWWA C909 and CSA B137.3.1. Laying lengths shall be 6.1 meters (20 feet). Pipe shall be joined by means of integral-bell elastomeric-gasket joints conforming to ASTM D3139. Spigot ends shall be chamfered by the manufacturer. Pipe ends shall be capped at the production facility prior to storage and shipping.

STANDARDS

PVCO pipe shall conform to the following standards:

- ANSI/NSF 14 Plastics Piping System Components and Related Materials
- ANSI/NSF Standard 61: Drinking Water System Components – Health Effects
- ASTM F1483 Standard Specification for Oriented Poly(Vinylchloride), PVCO, Pressure Pipe (PR 200psi)
- AWWA C909: Molecularly Oriented Polyvinyl Chloride (PVCO) Pressure Pipe, 4 inch through 24 inch (100 mm through 600 mm) for Water Distribution
- BNQ NQ 3660-950 Safety of Products and Materials in Contact with Drinking Water
- CSA B137.3.1 Molecularly Oriented Polyvinyl Chloride (PVCO) Pipe for Pressure Applications (PR 1620kPa)
- FM 1612 Polyvinyl Chloride (PVC) Pipe and Fittings for Underground Fire Protection Services (PC 150psi, 4" through 12")

FITTINGS

Bionax SR piping systems shall include IPEX Blue Brute molded and fabricated fittings.

LUBRICANT

Pipe must be assembled with IPEX water-soluble lubricant listed to NSF Standard 61.

COLOR CODING

CIOD pipe shall be color coded blue.



DID YOU KNOW?

In cities across North America, aging and corroding water pipe networks suffer pipe bursts daily. In the event of an earthquake the occurrence is multiplied to the extreme. For example, in 1994 when the Northridge Earthquake occurred in the San Fernando Valley, California, 15 seconds of the earth shaking caused 1,100 pipe bursts—more than a typical year's worth and leaving many residents without water for over two weeks.

IPEX CENTURION PRESSURE PIPING SYSTEMS 14" – 60" (350mm – 1500mm)

IPEX CENTURION®

IPEX Centurion extends the corrosion-free benefits of Blue Brute to larger diameters of pipe and new applications. The versatility and ease of installation of IPEX Centurion is unmatched – shop drawings and costly and difficult to install corrosion protection can be eliminated. In addition, unlike HDPE or concrete pressure pipe, every length of IPEX Centurion is tested to double its pressure rating.


ADVANTAGES

- 1 Corrosion-Proof Performance**
IPEX Centurion systems are immune to corrosion from aggressive soils and galvanic action.
- 2 Superior Hydraulics**
The glass-like finish of PVC reduces friction losses and eliminates the tuberculation common in iron pipes. As a result, pumping costs are reduced and water quality is maintained.
- 3 Cast-Iron Outside Diameter (CIOD)**
IPEX Centurion systems are manufactured with a cast-iron outside diameter (CIOD). This is compatible with waterworks valves, appurtenances and restrainers.
- 4 Bottle-tight Joints, Removable Gaskets**
IPEX's patented gasket system not only withstands many times the rated system pressure, but also withstands full vacuum pressures. The removable gasket system allows special oil-resistant (nitrile) gaskets to be easily installed when working in contaminated soils.
- 5 Centurion for Gravity Application**
With its pressure rated joints and non-corroding construction, IPEX Centurion is a natural choice for gravity flow lines.
- 6 Third-party Certification**
All IPEX municipal systems are third-party certified as applicable including Factory Mutual approval.

APPLICATIONS

- Water Transmission Lines
- Force mains
- Gravity Lines
- Irrigation
- Industrial Lines

STANDARDS



Cutout View of
Centurion Pipe

PRESSURE CAPACITY

IPEX Centurion can withstand extremely high short-term pressures in addition to lower levels of long-term pressure. As a result AWWA C900 and CSA B137.3 include both long-term pressure capacity (pressure rating PR or pressure class PC) and short-term capacity (short-term rating STR).

SDR	Short Term Rating STR psi	Long Term Rating PC/PR psi
51	128	80
41	160	100
32.5	200	125
25	264	165
18	376	235
14	488	305

STANDARDS

AWWA C900, CSA B137.3, NSF 61

Factory Mutual FM 1612:

DR18 is FM approved to 500mm diameter (20")

SHORT FORM SPECIFICATIONS

GENERAL



Pipe must conform to AWWA C900 and be certified to CSA B137.3 "Rigid Poly (Vinyl Chloride) (PVC) Pipe for Pressure Applications." DR51, 41, 32.5, 25, 18, and 14 pipe must have the following pressure class rating: 80 psi (550 kPa), 100 psi (690 kPa), 125 psi (860 kPa), 165 psi (1 140 kPa), 235 psi (1 620 kPa) and 305 psi (2 100 kPa). For pressure applications, each length of pipe must be hydro-tested at twice the class/rating and a short-term pressure test must be conducted once per production run. Pipe to be IPEX Centurion or approved equal.

FABRICATED FITTINGS

Fabricated fittings shall be made from segments of AWWA C900 pipe that are butt-fused or bonded together. Some fittings are over-wrapped with fiberglass-reinforced polyester. The fittings must always meet the pressure rating of the pipe system.



COMPATIBILITY

IPEX Centurion is manufactured with a cast-iron outside diameter (CIOD) so it is compatible with much of the existing older infrastructure of iron pipes. In addition, IPEX Centurion can be field-cut, which means unexpected changes in the field can be accommodated quickly, without having to wait for new shop drawings.


While IPEX Centurion is compatible with iron fittings, IPEX recommends the use of IPEX Centurion fittings exclusively with IPEX Centurion pipe.


IPEX CENTURION™ LARGE DIAMETER CIOD PVC PRESSURE PIPE


	Size		Product Code	Avg. ID		Min. Wall Thickness		Avg. OD	
	in	mm		in	mm	in	mm	in	mm
PC/PR 80 (SDR51)	18	450	071004	18.7	475.9	0.38	9.7	19.5	495.3
	20	500	071520	20.8	527.0	0.42	10.8	21.6	548.6
	24	600	071524	24.8	629.6	0.50	12.9	25.8	655.3
	30	750	071526	30.7	780.9	0.63	15.9	32.0	812.8
	36	900	071528	36.8	934.7	0.75	19.1	38.3	972.8
	42	1050	071000	42.6	1082.8	0.87	22.2	44.5	1130.3
	48	1200	071135	48.7	1236.2	1.00	25.3	50.8	1290.3
	54	1350	071043	55.3	1404.6	1.13	28.7	57.6	1462.0
	60	1500	071044	59.2	1503.2	1.21	30.7	61.6	1564.9
PC/PR 100 (SDR41)	14	350	071414	14.6	369.7	0.37	9.5	15.3	388.6
	16	400	071416	16.6	420.4	0.43	10.8	17.4	442.0
	18	450	071418	18.5	471.1	0.48	12.1	19.5	495.3
	20	500	071420	20.5	521.8	0.53	13.4	21.6	548.6
	24	600	071424	24.5	623.3	0.63	16.0	25.8	655.3
	30	750	071426	30.4	773.2	0.78	19.8	32.0	812.8
	36	900	071428	36.4	925.3	0.93	23.7	38.3	972.8
	42	1050	071140	42.2	1071.4	1.09	27.5	44.5	1130.3
	48	1200	071223	48.2	1223.0	1.24	31.5	50.8	1290.3
	54	1350	071045	54.8	1391.9	1.40	35.7	57.6	1462.0
	60	1500	071046	58.6	1488.4	1.50	38.1	61.6	1564.9
PC/PR 125 (SDR32.5)	14	350	—	14.4	364.7	0.47	12.0	15.3	388.6
	16	400	071316	16.3	414.5	0.54	13.6	17.4	442.0
	18	450	071317	18.3	464.8	0.60	15.2	19.5	495.3
	20	500	071320	20.3	514.6	0.67	16.9	21.6	548.6
	24	600	071324	24.2	615.0	0.80	20.2	25.8	655.3
	30	750	071326	30.0	762.8	0.98	25.0	32.0	812.8
	36	900	071328	35.9	912.9	1.18	29.9	38.3	972.8
	42	1050	071219	41.6	1056.6	1.37	34.8	44.5	1130.3
	48	1200	—	47.7*	1211.1*	1.56*	39.6*	50.8*	1290.3*
	54	1350	—	54.1*	1374.1*	1.77*	45.0*	57.6*	1462.0*
PC/PR 165 (DR25)	14	350	071114	14.1	357.5	0.61	15.6	15.3	388.6
	16	400	071116	16.0	406.6	0.70	17.7	17.4	442.0
	18	450	071118	17.9	455.7	0.78	19.8	19.5	495.3
	20	500	071124	19.9	504.7	0.86	22.0	21.6	548.6
	24	600	071136	23.7	602.9	1.03	26.2	25.8	655.3
	30	750	071144	29.4	747.8	1.28	32.5	32.0	812.8
	36	900	071137	35.2	895.0	1.53	38.9	38.3	972.8
	42	1050	—	40.9*	1039.9*	1.78*	45.2*	44.5*	1130.3*
	48	1200	—	46.7*	1187.2*	2.03*	51.6*	50.8*	1290.3*
PC/PR 235 (DR18)	14	350	071214	13.6	345.4	0.85	21.6	15.3	388.6
	16	400	071216	15.5	392.9	0.97	24.6	17.4	442.0
	18	450	071218	17.3	440.3	1.08	27.5	19.5	495.3
	20	500	071220	19.2	487.6	1.20	30.5	21.6	548.6
	24	600	071224	22.9	582.5	1.43	36.4	25.8	655.3
	30	750	071130	28.4	722.4	1.78	45.2	32.0	812.8
	36	900	—	34.0*	863.6*	2.13*	54.1*	38.3*	972.8*
	42	1050	—	39.6*	1004.8*	2.47*	62.8*	44.5*	1130.3*
PC/PR 305 (DR14)	14	350	070424	13.1	333.0	1.09	27.8	15.3	388.6
	16	400	070426	14.9	378.8	1.24	31.6	17.4	442.0


* coming soon!


IPEX CENTURION™ FABRICATED FITTINGS (CIOD), CLASS/PRESSURE RATING 165 PSI

	Dimension		Product Code
	inches	mm	
	14	350	273709
	16	400	273040
	18	450	273710
	20	500	273711
	24	600	273712
	30	750	273713


	14	350	273140
	16	400	273714
	18	450	273715
	20	500	273716
	24	600	273160
	30	750	273038

	14	350	073717*
	16	400	273718
	18	450	273719
	20	500	273720
	24	600	273161
	30	750	273721

	14	350	073722*
	16	400	273723
	18	450	273724
	20	500	273725
	24	600	073162
	30	750	273726

	14	350	273733
	16	400	273427
	18	450	273747
	20	500	273756
	24	600	073766
	30	750	273774

* Obsolete


	Dimension		Product Code
	inches	mm	
	14 x 4	350 x 100	073728*
	14 x 6	350 x 150	073729*
	14 x 8	350 x 200	273730
	14 x 10	350 x 250	073731*
	14 x 12	350 x 300	073732*
	16 x 4	400 x 100	273734
	16 x 6	400 x 150	273735
	16 x 8	400 x 200	273736
	16 x 10	400 x 250	273737
	16 x 12	400 x 300	273738
	16 x 14	400 x 350	073739*
	18 x 4	450 x 100	073740
	18 x 6	450 x 150	273741
	18 x 8	450 x 200	273742
	18 x 10	450 x 250	073743
	18 x 12	450 x 300	073744
	18 x 14	450 x 350	073745*
	18 x 16	450 x 400	073746
	20 x 4	500 x 100	073748
	20 x 6	500 x 150	273749
	20 x 8	500 x 200	273750
	20 x 10	500 x 250	273751
	20 x 12	500 x 300	273752
	20 x 14	500 x 350	073753
	20 x 16	500 x 400	273754
	20 x 18	500 x 450	073755
	24 x 4	600 x 100	273757
	24 x 6	600 x 150	273758
	24 x 8	600 x 200	273759
	24 x 10	600 x 250	073760
	24 x 12	600 x 300	273761
	24 x 14	600 x 350	073762*
	24 x 16	600 x 400	073763
	24 x 18	600 x 450	073764
	24 x 20	600 x 500	073765
	30 x 4	750 x 100	073767*
	30 x 6	750 x 150	073011*
	30 x 8	750 x 200	273013
	30 x 10	750 x 250	073768*
	30 x 12	750 x 300	273769
	30 x 14	750 x 350	073770*
	30 x 16	750 x 400	073039*
	30 x 18	750 x 450	073771*
	30 x 20	750 x 500	073772*
	30 x 24	750 x 600	073773*

* Obsolete

IPEX CENTURION™ FABRICATED FITTINGS (CIOD), CLASS/PRESSURE RATING 165 PSI

Dimension		Product Code
inches	mm	


Reducer Coupling G x G



14 x 4	350 x 100	073776*
14 x 6	350 x 150	273777
14 x 8	350 x 200	073778*
14 x 10	350 x 250	073779*
14 x 12	350 x 300	073780*
16 x 4	400 x 100	073781*
16 x 6	400 x 150	073782*
16 x 8	400 x 200	273783
16 x 10	400 x 250	273784
16 x 12	400 x 300	273785
16 x 14	400 x 350	073786*
18 x 4	450 x 100	073787*
18 x 6	450 x 150	073788*
18 x 8	450 x 200	073789*
18 x 10	450 x 250	073790
18 x 12	450 x 300	073791*
18 x 14	450 x 350	073792*
18 x 16	450 x 400	273793
20 x 4	500 x 100	073794*
20 x 6	500 x 150	273795
20 x 8	500 x 200	073796*
20 x 10	500 x 250	073797*
20 x 12	500 x 300	273798
20 x 14	500 x 350	073799
20 x 16	500 x 400	273800
20 x 18	500 x 450	073801
24 x 4	600 x 100	073802*
24 x 6	600 x 150	073803*
24 x 8	600 x 200	273804
24 x 10	600 x 250	073805*
24 x 12	600 x 300	073806*
24 x 14	600 x 350	073807*
24 x 16	600 x 400	273808
24 x 18	600 x 450	273809
24 x 20	600 x 500	073813
30 x 4	750 x 100	073814*
30 x 6	750 x 150	073815*
30 x 8	750 x 200	073816*
30 x 10	750 x 250	073817*
30 x 12	750 x 300	073818*
30 x 14	750 x 350	073819*
30 x 16	750 x 400	073820*
30 x 18	750 x 450	073821*
30 x 20	750 x 500	073822*
30 x 24	750 x 600	073234


Dimension		Product Code
inches	mm	

Repair Coupling



14	350	273883
16	400	273884
18	450	073885
20	500	273886
24	600	073887
30	750	073425*

Stop Coupling




14	350	073890*
16	400	073891*
18	450	073892*
20	500	073893*
24	600	073163
30	750	073894*

Cap



14	350	273895
16	400	273896
18	450	073897*
20	500	073898
24	600	073899
30	750	073900*

Cross




14	350	073837*
16	400	073844*
18	450	073852*
20	500	073861*
24	600	073871*
30	750	073882*

IPEX CENTURION™ FABRICATED FITTINGS (CIOD), CLASS/PRESSURE RATING 165 PSI

Dimension		Product Code
inches	mm	

Dimension		Product Code
inches	mm	

Reducer Cross G x G x G x G



14 x 4	350 x 100	073832
14 x 6	350 x 150	073833*
14 x 8	350 x 200	073834*
14 x 10	350 x 250	073835*
14 x 12	350 x 300	073836*
16 x 4	400 x 100	073838*
16 x 6	400 x 150	073839*
16 x 8	400 x 200	073840*
16 x 10	400 x 250	073841*
16 x 12	400 x 300	073842*
16 x 14	400 x 350	073843*
18 x 4	450 x 100	073845*
18 x 6	450 x 150	073846*
18 x 8	450 x 200	073847*
18 x 10	450 x 250	073848*
18 x 12	450 x 300	073849*
18 x 14	450 x 350	073850*
18 x 16	450 x 400	073851*
20 x 4	500 x 100	073853*
20 x 6	500 x 150	073854*
20 x 8	500 x 200	073855*
20 x 10	500 x 250	073856*
20 x 12	500 x 300	073857*
20 x 14	500 x 350	073858*
20 x 16	500 x 400	073859*
20 x 18	500 x 450	073860*

24 x 4	600 x 100	073862*
24 x 6	600 x 150	073863*
24 x 8	600 x 200	073864*
24 x 10	600 x 250	073865*
24 x 12	600 x 300	073866*
24 x 14	600 x 350	073867*
24 x 16	600 x 400	073868*
24 x 18	600 x 450	073869*
24 x 20	600 x 500	073870*
30 x 4	750 x 100	073872*
30 x 6	750 x 150	073873*
30 x 8	750 x 200	073874*
30 x 10	750 x 250	073875*
30 x 12	750 x 300	073876*
30 x 14	750 x 350	073877*
30 x 16	750 x 400	073878*
30 x 18	750 x 450	073879*
30 x 20	750 x 500	073880*
30 x 24	750 x 600	073881*

* Obsolete

TerraBrute CR

4" - 24" (100mm - 600mm)

TerraBrute® CR

Engineered for Horizontal Directional Drilling (HDD) and other trenchless applications, TerraBrute® CR is a 100% non-metallic, CSA B137.3 / AWWA C900 PVC pressure pipe system. Non-corroding and installation friendly, TerraBrute CR allows you to standardize on PVC throughout your potable water and sewer infrastructure. Whether you're using open-cut or trenchless methods, there are no more problems matching materials and couplings. No more surprises.

TerraBrute CR's non-metallic "ring-and-pin" gasketed joint design outperforms all other restrained PVC pipe joints on the market, providing more than twice the pull strength of other HDD systems – up to 390,000 lbf. for 24" (600mm) pipe. Unlike competing square-shoulder designs, TerraBrute CR's rounded bell shoulders slide by roots, rocks and other debris that can protrude into the borehole. And unlike HDPE, TerraBrute CR requires no relaxation time before installation of fittings or services.

APPLICATIONS

- Municipal Water Systems
- Fire Lines
- Force mains
- Industrial Lines

STANDARDS



B137.3



C900



Std. 61



3624-250*
3660-950*

* For BNQ Standards, not all sizes, pressure ratings, and manufacturing facilities are included in certifications.

ADVANTAGES

1

Corrosion Resistant

The new, non-metallic, "ring-and-pin" configuration of TerraBrute CR PVC pressure pipe offers complete corrosion resistance. The external "ring" is designed as two half rings for ease of installation and comes complete with the "pins" ready for insertion, creating a strong, locking joint.

2

Proven Performance

Pressure rated in excess of 200 psi, TerraBrute CR delivers the superior strength and corrosion resistance you've come to expect from our Blue Brute pressure pipe, along with the ability to absorb the underground shear and flexure stresses that occur in buried applications.

3

Proven Compatibility

TerraBrute CR trenchless PVC pipe is designed for total compatibility with your municipal system. Connections can be made with standard PVC CIOD fittings, direct tapped couplings or standard service saddles. Repair and handling techniques are the same as for any AWWA PVC pressure pipe.

4

Proven Joining System

Based on our gasketed bell and spigot design, proven through years of service in the field, the TerraBrute CR joint is rated higher than the pressure rating of the pipe. And unlike competing coupling joints, the TerraBrute CR joint has been specially engineered to deliver the highest pull strength safety factors in the industry for HDD applications.

5

Fast and Easy Joint Assembly

Because pipe segments are assembled during pullback operations, pipe stringing can be eliminated. Assembly time for a 12" (300mm) TerraBrute CR joint is typically less than five minutes.

“TerraBrute CR is the result of many years of research into the use of PVC pipes in HDD applications. The new non-corroding, locking joint design enables TerraBrute CR to enter new applications while maintaining the high tensile strength and bending radius of the original TerraBrute.”

*Dr. Erez Allouche,
Louisiana Tech University*

NEW NON-METALLIC GASKETED JOINT DESIGN

Extended Lip Bell

Plastic Ring for Pins


Non-metallic Pins

Grooved and Thickened Spigot

Inner Groove

Insertion Line

1



APPLICATIONS



BRIDGE CROSSINGS

TerraBrute CR's unique "new non-metallic ring-and-pin" joint design provides for easy installation in non-HDD applications where traditional butt fusion techniques would be difficult – such as this span of suspended pressure pipe installed beneath a busy roadway bridge.



ROAD CROSSINGS

TerraBrute CR is ideally suited for short drilling projects where existing structures cannot be disturbed – such as under busy highways, roads and intersections where you connect to PVC pipes.



URBAN CENTERS

Because TerraBrute CR can be assembled segmentally just before entering the borehole, projects take up less space in restricted urban areas, compared to the long strings of pipe typical with conventional PVC and HDPE installations.

SHORT FORM SPECIFICATIONS

GENERAL

PVC pipe used for horizontal directional drilling (HDD) or other trenchless installation methods shall be manufactured with a cast iron outside diameter (CIOD) and shall be made with starting stock certified to CSA B137.3 for 100mm – 600mm (4" – 24") diameters. Pipe will meet the requirements of AWWA C900, must be Factory Mutual approved.

MAXIMUM ALLOWABLE PULLING FORCE

The maximum allowable pulling force shall be the ultimate tensile capacity of the piping system divided by a safety factor of 2, as shown in the table below.

Nominal Size		Maximum Allowable Pulling Force	
mm	in	kN	lbf.
100	4	50	11,200
150	6	110	24,700
200	8	115	25,800
250	10	187	42,100
300	12	275	61,800
350	14	356	80,000
400	16	445	100,000
450	18	578	130,000
500	20	712	160,000
600	24	867	195,000

JOINT DESIGN

PVC pipe must be manufactured with an integral bell, and must have removable gaskets to allow the use of oil-resistant (nitrile) gaskets in contaminated soils.

* For BNQ Standards, not all sizes, pressure ratings, and manufacturing facilities are included in certifications.

PRODUCT SELECTION CHART

TerraBrute CR Pipe & Dimensions

Product Code	Nominal Diameter		Pressure Rating (2:1 safety Factor) psi	Max Outside Diameter (Bell OD)		AVG Internal Diameter		Lay Lengths	
	in	mm		in	mm	in	mm	feet/in	m
070258	4	100	305	6.49	165	4.09	104	19'10"	6.04
070259	6	150	305	9.06	230	5.87	149	19'9"	6.01
070260	8	200	235	11.33	288	8.03	204	19'9"	6.01
070261	10	250	235	14.00	355	9.84	250	19'9"	6.01
070262	12	300	235	16.36	416	11.69	297	19'9"	6.01
070270	14	350	235	19.20	488	13.50	343	19'8"	5.99
070271	16	400	235	21.60	549	15.35	390	19'8"	5.99
070272	18	450	235	24.10	612	16.66	423	19'8"	5.99
070273	20	500	235	26.80	681	18.46	469	19'8"	5.99
070274	24	600	235	31.70	805	22.02	559	19'8"	5.99

TerraBrute CR's larger internal diameters, compared to HDPE pipe, provide the same hydraulic performance usually with one size smaller pipe, saving on material costs.

Due to the extended bell configuration, TerraBrute has slightly shorter laying length than standard Blue Brute pipe.

CYCLETOUGH PIPING SYSTEMS

Pipe: 1-1/2" - 24" (40mm - 600mm)
Injection Molded Fittings: 1-1/2" - 8" (40mm - 200mm)

CycleTough®

CycleTough® IPS piping systems are specifically designed for irrigation systems and sewer forcemains. The constant cyclic surging that is associated with these applications demands a tough pipe, and more importantly, a specially engineered fitting.

CycleTough fittings have been engineered using the latest techniques in Finite Element Analysis (FEA), ensuring problem-free performance for the long haul.

IPEX CycleTough systems are made with the same high-impact, engineered compound as our Blue Brute® systems, and are tested to maintain the same high standards.

APPLICATIONS

- Forcemains
- Irrigation
- Rural Water Supply
- Water Distribution & Transmission

STANDARDS



D2241



NSF 61

ADVANTAGES

- 1 High Pressure Capacity**
CycleTough systems have a 2:1 safety factor for long-term pressures, and over 3.2:1 for temporary surges.
- 2 Toughness Engineered**
CycleTough fittings are engineered for versatility and reliability. Their unique design features extra material added for reinforcement to withstand the stresses imposed by tough irrigation and forcemain applications.
- 3 Iron Pipe Size Outside Diameter (IPSOD)**
CycleTough systems are made with an IPSOD, which is the same outside diameter configuration as schedule piping and most steel process piping.
- 4 Bottle-tight Joints, Removable Gaskets**
IPEX's patented gasket system not only withstands the rated system pressure, but also withstands full vacuum pressures. The removable gasket system allows special oil-resistant (nitrile) gaskets to be easily installed when working in contaminated soils.
- 5 Third-party Certification**
All CycleTough systems are certified to CSA B137.2. Third-party certification verifies a system will perform as expected, meeting all applicable standards.



CYCLETOUGH® REPAIR COUPLING HIGHLIGHT

New Hammer-On Design

Fittings feature square bell ends, which provide additional contact surface area for mallets or hammers to ease installation and adjustments

New Longer Pattern

Repair Couplings now offered in industry-leading lengths to better accommodate installations with large gaps or uneven cuts

High Impact Strength

The resin in CycleTough fittings resists cracking caused by environmental factors, long-term stress, and cyclic stress

Corrosion Proof

Fittings will not rust or corrode in aggressive soils



DID YOU KNOW?

All CycleTough fittings use high molecular weight pipe materials with a minimum HDB of 4,000 psi. Materials with higher molecular weights tend to exhibit better resistance to crack initiation.

SHORT FORM SPECIFICATIONS

PIPES

IPS-OD PVC Pipe shall be manufactured from PVC compound with an ASTM D1784 cell class 12454. PVC Pipe will have a minimum Hydrostatic Design Basis (HDB) of 4000 psi and a short term strength of 6400 psi. Pipe shall be certified to CSA B137.3 and conform to ASTM D2241.

FITTINGS

Injection molded PVC fittings shall be rated at 200 psi and be made from PVC compound with a minimum HDB of 4000 psi.

Fabricated fittings shall be made from sections of pipe certified to CSA B137.3, and fittings shall also be certified to CSA B137.3.

All pipes and fittings shall be listed to NSF Standard 61 and shall be color coded white.



PRODUCT SELECTION CHART CycleTough PIPE

Size		Product Code	Avg. ID		Min. Wall Thickness		Avg. OD	
in	mm		in	mm	in	mm	in	mm

PRESSURE RATINGS

Pressure Ratings and Burst Pressures

Size Range	Dimension Ratio	Burst Pressure (psi)	Long Term Rating (psi)
40 – 600 (1-1/2" – 24")	21	320	200
40 – 600 (1-1/2" – 24")	26	256	160
75 – 600 (3" – 24")	32.5	200	125
100 – 600 (4" – 24")	41	100	100

For more information on how these ratings are calculated, please refer to Volume I: Pressure Piping Systems Design Technical Manual

Series 100 (SDR41)

4	100	061204	4.278	108.41	.109	2.78	4.50	114.3
6	150	061206	6.282	159.57	.162	4.12	6.63	168.3
8	200	061208	8.180	207.77	.209	5.32	8.62	219.1
10	250	061210	10.194	258.93	.262	6.66	10.75	273.1
12	300	061212	12.093	307.15	.311	7.90	12.75	323.9
14	350	060214	13.277	337.24	.341	8.66	14.00	355.6
16	400	060216	15.174	385.41	.390	9.90	16.00	406.4
18	450	060218	17.074	433.67	.437	11.10	18.00	457.2
20	500	060220	18.985	481.71	.488	12.40	20.00	508.0
24	600	060224	22.756	578.01	.587	14.90	24.00	609.6

Series 125 (SDR32.5)

4	100	061104	4.208	106.88	.138	3.50	4.50	114.3
6	150	061106	6.194	157.32	.204	5.18	6.63	168.3
8	200	061108	8.063	204.80	.265	6.72	8.62	219.1
10	250	061110	10.049	255.24	.331	8.40	10.75	273.1
12	300	061112	11.921	302.78	.392	9.96	12.75	323.9
14	350	060114	13.090	332.49	.429	10.90	14.00	355.6
16	400	060116	14.957	379.90	.492	12.50	16.00	406.4
18	450	060118	16.823	427.31	.555	14.10	18.00	457.2
20	500	060120	18.698	474.93	.614	15.60	20.00	508.0
24	600	060124	22.431	569.74	.740	18.80	24.00	609.6

PRODUCT SELECTION CHART CycleTough PIPE

Size		Product Code	Avg. ID		Min. Wall Thickness		Avg.OD	
in	mm		in	mm	in	mm	in	mm

Series 160 (SDR26)

1-1/2	40	061900	1.731	43.97	.080	2.02	1.90	48.3
2	50	061902	2.184	55.47	.091	2.30	2.38	60.4
2-1/2	65	061901	2.642	67.11	.109	2.78	2.87	73.0
3	75	061903	3.215	81.65	.135	3.42	3.50	88.9
4	100	061904	4.134	105.01	.172	4.38	4.50	114.3
6	150	061906	6.085	154.56	.255	6.48	6.63	168.3
8	200	061908	7.921	201.20	.331	8.42	8.62	219.1
10	250	061910	9.874	250.79	.413	10.50	10.75	273.1
12	300	061912	11.717	297.61	.488	12.40	12.75	323.9
14	350	060914	12.857	326.56	.539	13.70	14.00	355.6
16	400	060916	14.698	373.33	.614	15.60	16.00	406.4
18	450	060918	16.531	419.89	.693	17.60	18.00	457.2
20	500	060920	18.364	466.45	.772	19.60	20.00	508.0
24	600	060924	22.039	559.78	.925	23.50	24.00	609.6


Series 200 (SDR21)

1-1/2	40	061300	1.709	43.42	.090	2.28	1.90	48.3
2	50	061301	2.137	54.29	.113	2.86	2.38	60.4
2-1/2	65	061302	2.584	65.62	.137	3.48	2.87	73.0
3	75	061303	3.146	79.91	.167	4.24	3.50	88.9
4	100	061304	4.046	102.77	.214	5.44	4.50	114.3
6	150	061306	5.957	151.30	.316	8.02	6.63	168.3
8	200	061308	7.756	197.00	.409	10.40	8.62	219.1
10	250	061310	9.665	245.49	.512	13.00	10.75	273.1
12	300	061312	11.467	291.25	.606	15.40	12.75	323.9
14	350	061314	12.589	319.77	.665	16.90	14.00	355.6
16	400	061316	14.381	365.27	.764	19.40	16.00	406.4
18	450	061318	16.180	410.98	.858	21.80	18.00	457.2
20	500	061320	17.980	456.70	.953	24.20	20.00	508.0
24	600	061324	21.580	548.12	1.142	29.00	24.00	609.6

CycleTough FITTINGS


Dimension		Product Code
inches	mm	

Stop Coupling G x G




2	50	355036
2-1/2	65	355037
3	75	355038
4	100	355039
6	150	355040
8	200	355041

Repair Coupling G x G




2	50	355217
2-1/2	65	355218
3	75	355219
4	100	355220
6	150	355221
8	200	355222
* 10*	250	055223

22-1/2° Elbow G x G




* 2	50	055053
* 3	75	055054
* 4	100	055055
* 6	150	055056

45° Elbow G x G



* 1-1/2	35	055059
2	50	355060
2-1/2	65	355061
3	75	355062
4	100	355063
6	150	355064
8	200	355065
* 10	250	055066
* 12	300	055067

90° Elbow G x G




* 1-1/2	35	055069
2	50	355070
2-1/2	65	355071
3	75	355072
4	100	355073
6	150	355074
8	200	355075
* 10	250	055076
* 12	300	055280

* Fabricated Non CSA, G = Gasket, Sp = Spigot

PRODUCT SELECTION CHART CycleTough FITTINGS


	Dimension		Product Code
	inches	mm	

Tee G x G x G




*	1-12	35	055227
	2	50	355228
	2-1/2	65	355229
	3	75	355230
	4	100	355231
	6	150	355232
	8	200	355233
*	10	250	055234
*	12	300	055281

Wye G x G x G




*	3	75	055291
*	4	100	055293
*	6	150	055290
*	8 x 6	200 x 150	055294
*	8	200	055298
*	12 x 6	300 x 150	055297
*	12 x 8	300 x 200	055299
*	12	300	055296

Cross G x G x G



*	2	50	055045
*	2-1/2	65	055046
*	3	75	055047
	4	100	355048
	6	150	355049


Increaser Bushing G x Sp



	1-1/2 x 2	35 x 50	355117
	2 x 2-1/2	50 x 65	355118
	2 x 3	50 x 75	355119
	2 x 4	50 x 100	355121
*	2 x 6	50 x 150	049280
	2-1/2 x 3	65 x 75	355320
	2-1/2 x 4	65 x 100	355122
	2-1/2 x 6	65 x 150	355124
	3 x 4	75 x 100	355123
	3 x 6	75 x 150	355125
	4 x 6	100 x 150	355126
	4 x 8	100 x 200	355127
	6 x 8	150 x 200	355128


	Dimension		Product Code
	inches	mm	

Reducing Tee G x G x G




	2 x 1-1/2	50 x 35	355151
	2-1/2 x 2	65 x 50	355153
	3 x 1-1/2	75 x 35	355154
	3 x 2	75 x 50	355155
	3 x 2-1/2	75 x 65	355156
	4 x 2	100 x 50	355157
	4 x 2-1/2	100 x 65	355158
	4 x 3	100 x 75	355159
	6 x 2	150 x 50	355161
	6 x 2-1/2	150 x 65	355162
	6 x 3	150 x 75	355163
	6 x 4	150 x 100	355164
	8 x 2	200 x 50	355165
	8 x 3	200 x 75	355166
	8 x 4	200 x 100	355167
	8 x 6	200 x 150	355168

Male Adapter G x Male Pipe Thread



	1-1/2	35	355099
	2	50	355100
	2-1/2	65	355101
	3	75	355102
*	4	100	055103
*	6	150	055104

Spigot Adapter G x Sp




	1-1/2	35	355028
	2	50	355029
	2-1/2	65	355030
	3	75	355031
*	4	100	055032
*	6	150	055033

* Fabricated Non CSA, G = Gasket, Sp = Spigot

† Reduced using Solvent Welded Threading Reducer Bushings

	Dimension		Product Code
	inches	mm	

Tap Service Tee G x G x NPT



†	2 x 1/2	50 x 15	055187
†	2 x 3/4	50 x 20	055188
†	2 x 1	50 x 25	055189
†	2 x 1-1/4	50 x 30	055190
†	2 x 1-1/2	50 x 35	055191
†	2-1/2 x 1/2	65 x 15	055192
†	2-1/2 x 3/4	65 x 20	055193
†	2-1/2 x 1	65 x 25	055194
†	2-1/2 x 1-1/4	65 x 30	055195
†	2-1/2 x 1-1/2	65 x 35	055196
	2-1/2 x 2	65 x 50	355197
†	3 x 1/2	75 x 15	055198
†	3 x 3/4	75 x 20	055199
	3 x 1	75 x 25	355200
	3 x 1-1/4	75 x 30	355201
	3 x 1-1/2	75 x 35	355202
	3 x 2	75 x 50	355203
†	4 x 1/2	100 x 15	055204
†	4 x 3/4	100 x 20	055205
	4 x 1	100 x 25	355206
	4 x 1-1/4	100 x 30	355207
	4 x 1-1/2	100 x 35	355208
	4 x 2	100 x 50	355209
†	6 x 1/2	150 x 15	055210
†	6 x 3/4	150 x 20	055211
	6 x 1	150 x 25	355212
	6 x 1-1/2	150 x 35	355214
	6 x 2	150 x 50	355215


	Dimension		Product Code
	inches	mm	

Cap



*	2	50	055400
*	3	75	055402
*	4	100	055404
*	6	150	055406
*	8	200	055408


Permanent Plug



*	1-1/2	35	055107
*	2	50	055108
*	2-1/2	65	055109
*	3	75	055110
*	4	100	055111
*	6	150	055112
*	8	200	055113

The spigot plug may be solvent welded.


Adapter Flange x Gasket Bell



*	1-1/2	35	055091
*	2	50	055092
*	2-1/2	65	055093
*	3	75	055094
*	4	100	055095
*	6	150	055096
*	8	200	055268

Flanged fittings have a maximum operating pressure of 150 psi.

Adapter Bell x Female IPT



*	1-1/2	35	055251
*	2	50	055252
*	2-1/2	65	055253
*	3	75	055433
*	4	100	055254
*	6	150	055256

Adapter PE (Plain End) x MIPT



*	3	75	055260
*	4	100	055105
*	6	150	055106

* Fabricated Non CSA, G = Gasket, Sp = Spigot
† Reduced using Solvent Welded Threading Reducer Bushings

notes

As copper prices continue to rise, cities across North America are turning to cost effective alternatives for their water service lines that connect municipal watermains to buildings. From composite tubing for water service lines which are immune to corrosion and mineral buildup, to compression fittings, IPEX offers water service systems that are CSA and NSF certified and backed by the quality and service you've come to expect from IPEX.

WATER SERVICE SYSTEMS




Q-Line Water Service Tubing

38

Philmac® 3G™ Compression Fittings

42



Q-LINE WATER SERVICE TUBING

3/4" & 1" (20mm & 25mm)

Q-Line®

Introducing Q-Line – a unique composite, water service tubing that combines the advantages of both metal and plastic, while eliminating their drawbacks. Now available from IPEX, the world's leading technical innovator in thermoplastic piping systems.

Manufactured by IPEX to AWWA C903-02, Q-Line is the only water service tubing in North America that delivers the strength of metal, the flexibility of soft copper and the durability of thermoplastic. What's more, because it eliminates the shortcomings of traditional piping materials, Q-Line is superior to them all.

APPLICATIONS

- Water Service Tubing
- Municipal Watermains
- Reclaimed Water Applications

STANDARDS



ADVANTAGES

- 1 Engineered Composite Construction**
A composite pipe constructed of flexible aluminum tubing permanently bonded between inner and outer layers of raised temperature polyethylene (PE-RT). Q-Line's unique structure offers optimum strength and toughness in a lightweight, easily handled and installed water service tubing.
- 2 Superior to Traditional Pipe**
Unlike copper, Q-Line's non-corroding thermoplastic layers resist the most aggressive water conditions and hot-soil environments. Q-Line won't leach copper or other metallic ions, so the quality of drinking water is assured and service life is longer.
- 3 Potable Water Certified**
Q-Line carries third-party ASTM F1282 and CSA B137.9 certification, as well as NSF-PW potable water certification, and meets all North American plumbing codes for water supply up to and inside the building.
- 4 High Flow Rates**
With larger inside diameters than CTS polyethylene piping and a super-smooth interior wall that does not permit build-up of calcium or other minerals, Q-Line offers the best flow rates in the industry.
- 5 Handles Like Copper**
Simply roll Q-Line tubing down the trench and it stays where it's laid (unlike plain polyethylene). You can make goosenecks and bends easily just as you would with copper, and Q-Line keeps its shape.

PE-RT
Aluminum
PE-RT



CODES AND STANDARDS

Q-Line water service tubing is manufactured to AWWA C903, ASTM F1282 and CSA B137.9, and meets NSF-PW potable water requirements as well as requirements of the following national codes.

- National Plumbing code of Canada
- Uniform Plumbing Code
- International Plumbing Code
- International Residential Code
- National Standard Plumbing Code
- SBCCI Standard Plumbing Code

MORE ADVANTAGES ...

Built-in Permeation Barrier

Q-Line composite water service tubing has been successfully tested against the most aggressive contaminants, like termiticides.

Zero Scrap Value

Because Q-Line's metallic core is permanently locked between layers of polyethylene, it has zero scrap metal value. So unlike copper and other valuable metals which are continually disappearing due to theft, Q-Line is more likely to stay on the job site where it's needed.

SHORT FORM SPECIFICATIONS

TUBING

Water service tubing shall be composite PE-AL-PE tubing manufactured in accordance with the requirements of AWWA C903 and certified to CSA B137.9 and ASTM F1282. It shall have a long term pressure rating of 1380kPa at 23°C (200 psi at 73°F) and 690kPa at 82°C (100 psi at 180°F). The pipe shall be third-party tested and certified to comply with NSF-PW potable water and NSF CL-TD chlorine resistance requirements. The service tubing shall be colour coded light blue as manufactured by IPEX under the trade name "Q-Line" or approved equal.



FITTINGS

Fittings for composite PE-AL-PE tubing shall be brass water service fittings conforming to AWWA C800.



ONE OF A KIND

Q-Line has unique inside and outside diameters that are different both from copper and conventional PE service tubing. Easily installed adapters that allow Q-line to be used with standard brass fittings are widely available.

PRODUCT SELECTION CHART

Q-Line Pipes

Nominal Size		Product Code	Avg. ID		Min. Wall Thickness		Avg. OD		Min. Bending Radius		Coil Length	
in	mm		in	mm	in	mm	in	mm	in	mm	ft	m
3/4	20	115001	0.79	20	0.10	2.5	0.98	25	5.0	125	150	45.7
3/4	20	115003	0.79	20	0.10	2.5	0.98	25	5.0	125	1000	305.0
1	25	115004	0.98	25	0.14	3.5	1.26	32	6.3	160	150	45.7

Q-Line Pipe to Compression End Municipal Brass are available from the brass fitting manufacturers.

PHILMAC® 3G™ COMPRESSION FITTINGS

1/2" – 2" (12mm – 50mm)



Gone are the days of juggling and assembling loose fitting components on the job site or even having to turn off the water line when connecting a new line. Thanks to Philmac®'s unique Slide & Tighten™ technology, you can get a perfect seal with Philmac® 3G™ fittings in any condition by hand or with a wrench.

Philmac® fittings come pre-assembled and ready to use so there's no need to disassemble the fitting or prepare the pipe. No solvent cementing or special tools are needed. Simply insert the pipe into the fitting until you feel the first point of resistance and then tighten the nut. Visual stops and gradually increasing mechanical resistance as the nut is turned prevents over-tightening.

Philmac®'s compact size makes installation easy in confined spaces, and Philmac® 3G™ fittings are engineered to avoid pipe twist during installation, reducing the risk of untightening previously-installed joints – a constant risk with brass fittings.

ADVANTAGES

- 1 Turn-to-Tighten Design**
Philmac®'s unique design allows you to achieve a perfect seal with the turn of a hand or wrench. Visual stops and gradually increasing mechanical resistance as the nut is tightened reduces the risk of over-tightening.
- 2 Compact Ergonomic Grip**
Small and lightweight, Philmac® 3G™ fittings are specially shaped to your hand for easy turning. Their compact size is perfect for working in confined areas.
- 3 Advanced Material**
Philmac® 3G™ fittings are made from an advanced high-performance polypropylene so they're UV, impact and corrosion-resistant—tough enough for 50+ years of reliable service.
- 4 Dynamic Compression Sealing**
Philmac® 3G™ fittings are highly engineered to provide a robust leak-proof seal with superior pull-out resistance. In addition, the strength of the nut ensures minimal distortion when tightened with a wrench.
- 5 Component Interchangeability**
Because both the CTSOD and ID Series fittings are based on the same core fitting design, components can be easily interchanged in order to transition from one type to another on the same fitting. And with adaptor kits available for other material types, you'll always have the right fitting for the job.

APPLICATIONS

- Water Service Coupling
- Residential Water Service
- Residential Irrigation Systems
- Cottage Country Water Service
- Rural Irrigation

STANDARDS



DID YOU KNOW?

Philmac®'s unique Slide & Tighten™ technology can give you a perfect seal just by hand or with a wrench. Just slide and tighten, and the job's done!



PHILMAC® 3G™: CTSOD AND ID SIZES

Philmac® 3G™ Compression Fittings offer the flexibility to connect to five different types of pipe; three polyethylene pipe types (CTS, ID Series and IPS), Composite and Copper.

There are two dedicated fittings, CTS and ID Series, which come preassembled and ready to use. That leaves three others: IPS, XPA, and copper that require a conversion kit. Converting a Philmac fitting is very simple and can be done in just a few steps.

CTSOD

ID Series



OD Fittings
3/4" – 2"



ID Series
1/2" – 2"



UNIVERSAL TRANSITION COUPLING (UTC™) & FITTINGS

With the Universal Transition Coupling, virtually any type of pipe can be connected to any other type of pipe. Rather than servicing specific materials, the UTC™s service a range of outside pipe diameters, regardless of the piping material. The wide tolerance range allows seven couplings to cover pipe sizes from 1/2" to 2". Versatility coupled with simple slide-and-tighten installation make the Philmac UTC™ the practical choice.



ADVANTAGES

- ✓ Universal transition couplings are the ideal solution for connecting a wide variety of pipes.
- ✓ One coupling connects copper, galvanized iron, PVC, lead and even PE and PEX.
- ✓ Wide tolerance range allows seven couplings to cover pipe sizes from 1/2" to 2".
- ✓ Easy to fit "Slide & Tighten" technology.
- ✓ Couplings are end-load resistant with no restraint needed to prevent pipe pull-out.





Sizing Chart


Pipe Material Standard	A	B	C	D	E	F	G
	0.59" – 0.83" 15 – 21 mm	0.83" – 1.06" 21 – 27 mm	1.06" – 1.34" 27 – 34 mm	1.34" – 1.54" 34 – 39 mm	1.54" – 1.69" 39 – 43 mm	1.85" – 1.93" 47 – 49 mm	2.32" – 2.40" 59 – 61 mm
Nominal Pipe Size (inches)							
PE CTS OD / PEX	1/2	3/4	1	1-1/4	1-1/2	–	–
PE IPS OD	–	1/2	3/4	1	1-1/4	1-1/2	2
PE SIDR 7 Series 100	–	1/2	3/4	1	–	–	–
PE SIDR 9	1/2	3/4	1	–	–	–	–
PE SIDR 11	–	3/4	1	–	1-1/4	1-1/2	–
PE Series 75	1/2	3/4	1	–	1-1/4	–	–
Copper	1/2	3/4	1	1-1/4	1-1/2	–	–
PVC	–	1/2 or 3/4	1	–	1-1/4	–	2
Galvanized Iron	–	1/2 or 3/4	1	–	1-1/4	–	2
Lead - Strong	–	5/8	3/4	1	–	–	–
Lead - Extra Strong	–	1/2	5/8 or 3/4	1	–	–	–
Lead - Double Extra Strong	–	1/2	3/4	–	1	–	–


* If 3/4" XXS Lead Pipe OD is larger than 1.34", the pipe needs to be shaved if using a Size C UTC™ fitting. Otherwise, a size D UTC™ Coupling can be used when OD is larger than 1.34".

PRODUCT SELECTION CHART – CTSOD FITTINGS


	Dimension		Product Code
	inches	mm	
Couplings Compression x Compression			
	3/4	20	258000
	1	20	258001
	1-1/4 x 1-1/4	30 x 30	258002
	1-1/2	35	258003
	2	50	258004


Reducing Couplings Compression x Compression			
	1 x 3/4	25 x 20	258005
	1-1/4 x 1	30 x 25	258131


Male Adapters Compression x MIPT			
	3/4 x 1/2	20 x 15	258006
	3/4	20	258007
	1 x 1/2	25 x 15	258008
	1 x 3/4	25 x 20	258009
	1	25	258010
	1-1/4 x 3/4	30 x 20	258011
	1-1/4 x 1	30 x 25	258012
	1-1/4	30	258013
	1-1/2 x 1	35 x 25	258014
	1-1/2 x 1-1/4	35 x 30	258015
	1-1/2	35	258016
	2 x 1-1/2	50 x 35	258017
	2	50	258018


Female Adapters Compression x FIPT			
	3/4 x 1/2	20 x 15	258019
	3/4	20	258020
	1 x 3/4	25 x 20	258021
	1	25	258022
	1-1/4 x 1	30 x 25	258023
	1-1/4	30	258024
	1-1/2 x 1-1/4	35 x 30	258025
	1-1/2	35	258026
	2 x 1-1/2	50 x 35	258027
	2	50	258028

Elbow Compression x Compression			
	3/4	20	258029
	1	25	258030
	1-1/4	30	258031
	1-1/2	35	258032
	2	50	258033

Elbow Compression x FIPT			
	3/4	20	258034
	1 x 3/4	25 x 20	258035
	1	25	258036
	1-1/4 x 1	30 x 25	258037
	1-1/4	30	258038
	1-1/2 x 1-1/4	35 x 30	258039
	1-1/2	35	258040


End Caps Compression			
	3/4	20	258151
	1	25	258152
	1-1/4	30	258153
	1-1/2	35	258154


Tee Compression			
	3/4	20	258042
	1	25	258043
	1-1/4	30	258044
	1-1/2	35	258045


Tee Compression x Compression x FIPT			
	3/4	20	258047
	1 x 3/4	25 x 20	258048
	1	25	258049
	1-1/4 x 3/4	30 x 20	258050
	1-1/4 x 1	30 x 25	258051
	1-1/4	30	258052
	1-1/2 x 3/4	35 x 20	258053
	1-1/2 x 1-1/4	35 x 30	258054
	1-1/2	35	258055


PRODUCT SELECTION CHART – ID SERIES FITTINGS


	Dimension		Product Code
	inches	mm	
Couplings Compression x Compression			
	1/2	15	258059
	3/4 x 1/2	20 x 15	258065
	3/4	20	258060
	1	25	258061
	1-1/4	30	258062
	1-1/2	35	258063
	2	50	258064


Male Adapters Compression x MIPT			
	1/2	15	258066
	1/2 x 3/4	15 x 20	258067
	3/4 x 1/2	20 x 15	258068
	3/4	20	258069
	3/4 x 1	20 x 25	258070
	1 x 3/4	25 x 20	258071
	1	25	258072
	1 x 1-1/4	25 x 30	258073
	1-1/4 x 1	30 x 25	258074
	1-1/4	30	258075
	1-1/4 x 1-1/2	30 x 35	258076
	1-1/2	35	258077
	1-1/2 x 2	35 x 50	258078
	2	50	258079


Female Adapters Compression x FIPT			
	1/2	15	258080
	1/2 x 3/4	15 x 20	258081
	3/4	20	258082
	3/4 x 1	20 x 25	258083
	1	25	258084
	1 x 1-1/4	25 x 30	258085
	1-1/4	30	258086
	1-1/4 x 1-1/2	30 x 35	258087
	1-1/2	35	258088
	1-1/2 x 2	35 x 50	258089
	2	50	258090

Elbow Compression x Compression			
	1/2	15	258091
	3/4	20	258092
	1	25	258093
	1-1/4	30	258094
	1-1/2	35	258095
	2	50	258096





Elbow Compression x FIPT			
	1/2 x 3/4	15 x 20	258097
	3/4	20	258098
	3/4 x 1	20 x 25	258099
	1	25	258100
	1 x 1-1/4	25 x 30	258101
	1-1/4	30	258130

Tee Compression			
	1/2	15	258102
	3/4	20	258103
	1	25	258104
	1-1/4	30	258105
	1-1/2	35	258106

Tee Compression x Compression x FIPT			
	3/4	20	258107
	1 x 1/2	25 x 15	258108
	1	25	258109
	1-1/4 x 1/2	30 x 15	258110
	1-1/4 x 3/4	30 x 20	258111
	1-1/4 x 1-1/2	30 x 35	258112
	1-1/2 x 2	35 x 50	258113

End Caps Compression			
	1/2	15	258114
	3/4	20	258115
	1	25	258116
	1-1/4	30	258117
	1-1/2	35	258118
	2	50	258183

PRODUCT SELECTION CHART – ADAPTER KITS

			Dimension		Product Code
			inches	mm	
CTS Adapter Kit (Includes Gold Collet, CTS Nut, CTS Seal)					
			3/4	20	258132
			1	25	258133
			1-1/4	30	258134
			1-1/2	35	258135
ID Series Adapter Kit (Includes Red Collet, Red Insert, ID Series Nut, ID Series Seal)					
			1/2	15	258137
			3/4	20	258138
			1	25	258139
			1-1/4	30	258140
			1-1/2	35	258141
			2	50	258142
Q-Line Adapter Kit (Includes Blue Collet, Q-Line Nut, Q-Line Seal)					
			1/2	15	258122
			3/4	20	258123
			1	25	258124
IPS OD Adapter Kit (Includes Green Collet, IPS Nut, IPS Seal)					
			3/4	20	258125
			1	25	258126
			1-1/4	30	258127
			1-1/2	35	258128
			2	50	258129

PRODUCT SELECTION CHART – UNIVERSAL TRANSITION COUPLINGS (UTC™) & FITTINGS


	Dimension mm	Product Code
--	-----------------	-----------------

Coupling UTC x UTC




15 - 21 x 15 - 21	255208
21 - 27 x 21 - 27	255209
27 - 34 x 27 - 34	255210
34 - 39 x 34 - 39	255946
39 - 43 x 39 - 43	255211
47 - 49 x 47 - 49	255947
59 - 61 x 59 - 61	255948

Reducing Coupling UTC x UTC




21 - 27 x 15 - 21	255212
27 - 34 x 15 - 21	255214
27 - 34 x 21 - 27	255213
34 - 39 x 27 - 34	255197
39 - 43 x 27 - 34	255215

Elbow UTC x UTC



15 - 21 x 15 - 21	255156
21 - 27 x 21 - 27	255157

Tee UTC x UTC x UTC




15 - 21 x 15 - 21 x 15 - 21	255158
-----------------------------	--------

Tee UTC x UTC x FIPT



15 - 21 x 3/4 FIPT	255159
21 - 27 x 3/4 FIPT	255167

Adapter UTC x MIPT



15 - 21 x 3/4 MIPT	255169
21 - 27 x 3/4 MIPT	255344
27 - 34 x 3/4 MIPT	255345
27 - 34 x 1 MIPT	255196

With a long-proven track record for reliable, watertight performance underground, IPEX offers the widest range of industrial and domestic, sanitary and storm water sewage conveyance systems available on the market today. Third-party certified to applicable industry standards, all of our state-of-the-art PVC gravity sewer systems are engineered and manufactured to virtually eliminate the leakage and infiltration common with traditional materials like concrete.

SEWER PIPING SYSTEMS



Ring-Tite / Enviro-Tite	48
Ultra-Rib	58
Solvent Weld Sewer Fittings	66
Perforated Pipe (New England)	74
White Bionax PVCO	76

RING-TITE/ENVIRO-TITE PIPING SYSTEMS

Ring-Tite
4" - 60" (100mm - 1500mm)
Enviro-Tite
4" - 15" (100mm - 375mm)

Ring-Tite® Enviro-Tite®

Ring-Tite and Enviro-Tite piping systems are DR35 and DR28 sewer pipes manufactured to demanding ASTM and CSA standards. The two products are identical except for Enviro-Tite having a minimum recycled material content of 50%. Both products have tight joints that can withstand well in excess of both the ASTM and CSA requirements.

ADVANTAGES

- 1 Corrosion-proof Performance**
IPEX Ring-Tite and Enviro-Tite systems are immune to corrosion from aggressive soils and galvanic action. In addition, H₂S and other aggressive chemicals common in sanitary sewage have no effect.
- 2 Tight Joints & Lower Treatment Costs**
Eliminate infiltration and exfiltration. Ring-Tite and Enviro-Tite joints easily outperform concrete and corrugated PE joints.
- 3 Third-Party Certification**
IPEX Ring-Tite and Enviro-Tite systems are certified to CSA B182.2. Third party certification is your verification that the product will perform as stated.
- 4 High Flow Capacity**
IPEX's PVC pipe and fittings are manufactured with smooth inner walls and provide systems with a Manning coefficient of 0.009, allowing for use of smaller diameters of pipe when compared to rough walled pipe.

APPLICATIONS

- Gravity Flow Sanitary Sewers
- Storm Sewers
- Sewer Laterals
- Industrial Effluent Lines

STANDARDS

RING-TITE



B182.2



3624-130/135



D3034 & F679

ENVIRO-TITE




B182.4



3624-130/135



F1760



Enviro-Tite®

SHORT FORM SPECIFICATIONS

GENERAL

Main line sewers will be PVC DR35 sewer pipe and shall be in compliance with ASTM D3034 or ASTM F1760 and third-party certified to CSA B182.2. Sewer laterals will be PVC DR28 sewer pipe and shall be third-party certified by CSA as above.

JOINTS

Sealing gaskets must meet the requirements of ASTM D3034 or ASTM F1760 or CSA B182.2. In addition, the pipe joints must be able to withstand a minimum hydrostatic pressure of 50 psi (345 kPa) without leakage.

PIPE STIFFNESS

The minimum ring stiffness shall be 46 psi (320 kPa) for DR35 pipe and 90 psi (625 kPa) for DR 28. This stiffness will be determined using the test methods prescribed by ASTM D3034 and ASTM F1760.

FITTINGS

Injection-moulded gasketed PVC fittings shall meet the requirements of ASTM D3034 and ASTM F1336 and shall be certified to CSA B182.1 or CSA B182.2. Fabricated fittings must conform to ASTM F1336 and CSA B182.2.



DIMENSIONS

DR35

Nominal Size		Average I.D.		Min Wall Thickness		Average O.D.	
in	mm	in	mm	in	mm	in	mm
4	100	3.97	100.94	0.12	3.06	4.21	107.06
5	135	5.32	135.08	0.16	4.09	5.64	143.26
6	150	5.92	150.29	0.18	4.55	6.28	159.39
8	200	7.92	201.16	0.24	6.10	8.40	213.36
10	250	9.90	251.46	0.30	7.62	10.50	266.70
12	300	11.79	299.36	0.36	9.07	12.50	317.50
15	375	14.43	366.42	0.44	11.10	15.30	388.62
18	450	17.63	447.87	0.53	13.57	18.70	475.01
21	525	20.79	527.99	0.63	16.00	22.05	559.99
24	600	23.39	594.00	0.71	18.00	24.80	630.00
27	675	26.36	669.42	0.80	20.29	27.95	710.00
30	750	30.17	766.36	0.91	23.22	32.00	812.80
36	900	36.11	917.22	1.09	27.79	38.30	972.80
42	1050	41.95	1065.72	1.27	32.29	44.50	1130.30
48	1200	47.89	1216.56	1.45	36.87	50.79	1290.30
54	1350	54.27	1378.49	1.64	41.77	57.55	1462.00
60	1500	58.08	1475.48	1.76	44.71	61.61	1564.90

DR28

4	100	3.91	99.42	0.15	3.82	4.21	107.06
5	135	5.24	133.02	0.20	5.12	5.64	143.26
6	150	5.83	148.01	0.22	5.69	6.28	159.39



PRODUCTION SELECTION CHART

		Dimension		Product Code
		inches	mm	
Ring-Tite PVC Gravity Sewer Pipe DR28				
	Green	4	100	042074
		5	135	042075
		6	150	042076
	White	4	100	042164
		5	135	042078
		6	150	042166

Ring-Tite PVC Gravity Sewer Pipe DR35				
		4	100	039204
		5	135	039150
		6	150	039206
		8	200	041148
		10	250	041149
		12	300	041412
		15	375	041152
		18	450	041448
	Green	21	525	041449
		24	600	041450
		27	675	041451
		30	750	041459
		36	900	041453
		42	1050	041481
		48	1200	041038
	54	1350	041040	
	60	1500	041039	
White		8	200	041008
		10	250	041016
		12	300	041021
		15	375	041027


Enviro-Tite PVC Sewer Pipe DR28

	Green	4	100	042036
		5	135	042037
		6	150	042038
	White	4	100	042114
		5	135	042115
		6	150	042116

Enviro-Tite PVC Sewer Pipe DR35


Green

4	100	039207
5	135	039208
6	150	039209
8	200	041850
10	250	041851
12	300	041852
15	375	041855

	Dimension		Product Code
	inches	mm	
Tee G x G x G			
	4	100	043104
	5	135	043443
	6 x 4	150 x 100	043105
	6	150	043106
	8 x 4	200 x 100	043094
	8 x 5	200 x 135	043095
	8 x 6	200 x 150	043096
	8	200	043098
	10 x 4	250 x 100	043102
	10 x 5	250 x 135	043085
	10 x 6	250 x 150	043099
	10 x 8	250 x 200	043108
	10	250	043089
	12 x 4	300 x 100	043091
	12 x 5	300 x 135	043109
	12 x 6	300 x 150	043103
	12 x 8	300 x 200	043100
	12 x 10	300 x 250	043078
	12	300	043101
	15 x 4	375 x 100	043092
	15 x 5	375 x 135	043246
	15 x 6	375 x 150	043110
	15 x 8	375 x 200	043111
	15 x 10	375 x 250	043112
	15 x 12	375 x 300	043113
	15	375	043107
	18 x 4	450 x 100	043912
	18 x 6	450 x 150	043114
	18 x 8	450 x 200	043891
	18 x 10	450 x 250	043911
	18 x 12	450 x 300	043910
	18 x 15	450 x 375	043347
	18	450	043444
	21 x 4	525 x 100	043004
	21 x 6	525 x 150	043115
	21 x 8	525 x 200	043908
	21 x 10	525 x 250	043907
	21 x 12	525 x 300	043889
	21 x 15	525 x 375	*
	21 x 18	525 x 450	043349
	21	525	043906
	24 x 4	600 x 100	043809
	24 x 6	600 x 150	043351
	24 x 8	600 x 200	043905
	24 x 10	600 x 250	043353
24 x 12	600 x 300	043359	
24 x 15	600 x 375	043037	
24 x 18	600 x 450	043045	
24 x 21	600 x 525	043354	
24	600	043044	
27 x 4	675 x 100	*	
27 x 6	675 x 150	043888	
27 x 8	675 x 200	*	
27 x 10	675 x 250	043360	
27 x 12	675 x 300	*	
27 x 15	675 x 375	*	
27 x 18	675 x 450	*	
27 x 21	675 x 525	*	
27 x 24	675 x 600	*	
27	675	*	

Dimension		Product Code
inches	mm	


Tee Wye G x G x G



4	100	043156
6 x 4	150 x 100	043158
6	150	043449
8 x 4	200 x 100	043159
8 x 6	200 x 150	043160
8	200	043450
10 x 4	250 x 100	043693
10 x 6	250 x 150	043451
10 x 8	250 x 200	043452
12 x 4	300 x 100	043453
12 x 6	300 x 150	043454
12 x 8	300 x 200	043455
15 x 4	375 x 100	043456
15 x 6	375 x 150	043457
15 x 8	375 x 200	043458
18 x 4	450 x 100	043999
18 x 6	450 x 150	043459
18 x 8	450 x 200	043460
21 x 4	525 x 100	*
21 x 6	525 x 150	043116
21 x 8	525 x 200	*
24 x 4	600 x 100	043046
24 x 6	600 x 150	*
24 x 8	600 x 200	*
27 x 4	675 x 100	*
27 x 6	675 x 150	*


Dimension		Product Code
inches	mm	


45° Wye G x G x G





4	100	043304
5 x 4	135 x 100	043303
5	135	043305
6 x 4	150 x 100	043307
6	150	043306
8 x 4	200 x 100	043294
8 x 6	200 x 150	043296
8	200	043298
10 x 4	250 x 100	043311
10 x 6	250 x 150	043312
10 x 8	250 x 200	043313
10	250	043308
12 x 4	300 x 100	043319
12 x 6	300 x 150	043276
12 x 8	300 x 200	043314
12 x 10	300 x 250	043315
12	300	043309
15 x 4	375 x 100	043320
15 x 6	375 x 150	043153
15 x 8	375 x 200	043316
15 x 10	375 x 250	043317
15 x 12	375 x 300	043318
15	375	043310
18 x 4	450 x 100	043904
18 x 6	450 x 150	043903
18 x 8	450 x 200	043902
18 x 10	450 x 250	043362
18 x 12	450 x 300	043363
18 x 15	450 x 375	043901
18	450	043900
21 x 4	525 x 100	043899
21 x 6	525 x 150	043898
21 x 8	525 x 200	043897
21 x 10	525 x 250	043896
21 x 12	525 x 300	043895
21 x 15	525 x 375	043894
21 x 18	525 x 450	043893
21	525	043467
24 x 4	600 x 100	043488
24 x 6	600 x 150	043364
24 x 8	600 x 200	043799
24 x 10	600 x 250	043892
24 x 12	600 x 300	043042
24 x 15	600 x 375	043554
24 x 18	600 x 450	043041
24 x 21	600 x 525	*
24	600	043040
27 x 4	675 x 100	043551
27 x 6	675 x 150	043787
27 x 8	675 x 200	043549
27 x 10	675 x 250	043890
27 x 12	675 x 300	*
27 x 15	675 x 375	*
27 x 18	675 x 450	*
27 x 21	675 x 525	*
27 x 24	675 x 600	*
27	675	*

PRODUCTION SELECTION CHART


	Dimension		Product Code
	inches	mm	
Double 45° Wye G x G x G x G			
	6 x 4	150 x 100	043254
	6	150	043255
	8 x 4	200 x 100	043258
	8 x 6	200 x 150	043469
	8	200	043260
	10 x 4	250 x 100	*
	10 x 6	250 x 150	043251
	12 x 4	300 x 100	*
	12 x 6	300 x 150	043259
	12 x 8	300 x 200	043248
	15 x 4	375 x 100	*
	15 x 6	375 x 150	*
	15 x 8	375 x 200	*
	15 x 10	375 x 250	*
	15 x 12	375 x 300	*
	18 x 4	450 x 100	*
	18 x 6	450 x 150	*
	18 x 8	450 x 200	*
	18 x 10	450 x 250	*
	18 x 12	450 x 300	*
	18 x 15	450 x 375	*


	Dimension		Product Code
	inches	mm	
45° Elbow G x G			
	4	100	043504
	5	135	043505
	6	150	043506
	8	200	043507
	10	250	043508
	12	300	043509
	15	375	043515
	18	450	043971
	21	525	043957
	24	600	043953
	27	675	043516

	Dimension		Product Code
	inches	mm	
45° Elbow Sp x G			
	4	100	043404
	5	135	043405
	6	150	043406
	8	200	043407
	10	250	043411
	12	300	043412
	15	375	043951
	18	450	043203
	21	525	043946
	24	600	043943
	27	675	*

	Dimension		Product Code
	inches	mm	
90° Elbow G x G			
	4	100	043214
	6	150	043216
	8	200	043217
	10	250	043218
	12	300	043219
	15	375	043220
	18	450	043239
	21	525	043955
	24	600	043989
	27	675	043204


	Dimension		Product Code
	inches	mm	
22-1/2° Elbow G x G			
	4	100	043964
	5	135	043968
	6	150	043969
	8	200	043963
	10	250	043966
	12	300	043965
	15	375	043967
	18	450	043174
	21	525	043958
	24	600	043954
	27	675	043808

	Dimension		Product Code
	inches	mm	
90° Elbow Sp x G			
	4	100	043234
	6	150	043236
	8	200	043238
	10	250	043205
	12	300	043206
	15	375	043221
	18	450	043948
	21	525	043945
	24	600	043942
	27	675	*

	Dimension		Product Code
	inches	mm	
22-1/2° Elbow Sp x G			
	4	100	043977
	5	135	043976
	6	150	043975
	8	200	043972
	10	250	043973
	12	300	043974
	15	375	043952
	18	450	043949
	21	525	043947
	24	600	043944
	27	675	043199


Dimension		Product Code
inches	mm	

45° Long Radius Bend Sp x G




4	100	043143
5	135	043365
6	150	043166
8	200	043144
10	250	043151
12	300	043152

22-1/2° Long Radius Bend Sp x G




4	100	043172
5	135	043366
6	150	043922
8	200	043139
10	250	043140
12	300	043141

Repair Coupling G x G (w/o pipe stop)



4	100	043624
5	135	043625
6	150	043626
8	200	043627
10	250	043630
12	300	043631
15	375	043637
18	450	043941
21	525	043938
24	600	043937
27	675	043670


Coupling G x G (with stop)



4	100	043640
5	135	043641
6	150	043643
8	200	043644
10	250	043645
12	300	043632
15	375	043638
18	450	043935
21	525	043934
24	600	043933
27	675	043940


Dimension		Product Code
inches	mm	

Saddle Wye (c/w 2 straps)



6 x 4	150 x 100	043594
8 x 4	200 x 100	043595
8 x 6	200 x 150	043598
10 x 4	250 x 100	043599
10 x 6	250 x 150	043596
12 x 4	300 x 100	043600
12 x 6	300 x 150	043597
15 x 4	375 x 100	043603
15 x 6	375 x 150	043602
18 x 4	450 x 100	043440
18 x 6	450 x 150	043441
21 x 4	525 x 100	043442
21 x 6	525 x 150	*
24 x 4	600 x 100	*
24 x 6	600 x 150	043584
27 x 4	675 x 100	*
27 x 6	675 x 150	*

Saddle Tee (c/w 2 straps)



6 x 4	150 x 100	043125
8 x 4	200 x 100	043124
8 x 6	200 x 150	043126
10 x 4	250 x 100	043127
10 x 6	250 x 150	043129
12 x 4	300 x 100	043130
12 x 6	300 x 150	043132
15 x 4	375 x 100	043133
15 x 6	375 x 150	043135
18 x 4	450 x 100	043429
18 x 6	450 x 150	043431
21 x 4	525 x 100	043432
21 x 6	525 x 150	043433
24 x 4	600 x 100	043434
24 x 6	600 x 150	043585
27 x 4	675 x 100	043703
27 x 6	675 x 150	043477

Spigot Plug




4	100	043734
5	135	043735
6	150	043736
8	200	043738
10	250	043740
12	300	043741
15	375	043742
18	450	043743
21	525	043744
24	600	043745
27	675	043751

PRODUCTION SELECTION CHART

	Dimension		Product Code
	inches	mm	


Increaser SP x G



5 x 4	135 x 100	043729
6 x 4	150 x 100	043939
8 x 4	200 x 100	043621
8 x 6	200 x 150	043620
10 x 4	250 x 100	043368
10 x 6	250 x 150	043618
10 x 8	250 x 200	043622
12 x 6	300 x 150	043617
12 x 8	300 x 200	043616
12 x 10	300 x 250	043623
15 x 4	375 x 100	043369
15 x 6	375 x 150	043300
15 x 8	375 x 200	043370
15 x 10	375 x 250	043371
15 x 12	375 x 300	043615
18 x 8	450 x 200	043538
18 x 10	450 x 250	043678
18 x 12	450 x 300	043629
18 x 15	450 x 375	043539
21 x 12	525 x 300	*
21 x 15	525 x 375	043288
21 x 18	525 x 450	043673
24 x 12	600 x 300	043047
24 x 15	600 x 375	043048
24 x 18	600 x 450	043674
24 x 21	600 x 525	043675
27 x 12	675 x 300	043679
27 x 15	675 x 375	*
27 x 18	675 x 450	043289
27 x 21	675 x 525	043676
27 x 24	675 x 600	043677


	Dimension		Product Code
	inches	mm	

Increaser Coupling G x G



6 x 4	150 x 100	043882
8 x 4	200 x 100	043536
8 x 6	200 x 150	043535
10 x 6	250 x 150	043528
10 x 8	250 x 200	043531
12 x 6	300 x 150	043530
12 x 8	300 x 200	043532
12 x 10	300 x 250	043520
15 x 6	375 x 150	043931
15 x 8	375 x 200	043930
15 x 10	375 x 250	043533
15 x 12	375 x 300	043534
18 x 8	450 x 200	043690
18 x 10	450 x 250	043929
18 x 12	450 x 300	043293
18 x 15	450 x 375	043928
21 x 4	525 x 100	043927
21 x 8	525 x 200	043926
21 x 10	525 x 250	043925
21 x 12	525 x 300	043924
21 x 15	525 x 375	043923
21 x 18	525 x 450	043921
24 x 4	600 x 100	043920
24 x 6	600 x 150	043919
24 x 8	600 x 200	043918
24 x 10	600 x 250	043917
24 x 12	600 x 300	043916
24 x 15	600 x 375	043915
24 x 18	600 x 450	043914
24 x 21	600 x 525	043913
27 x 12	675 x 300	*
27 x 15	675 x 375	*
27 x 18	675 x 450	*
27 x 21	675 x 525	*
27 x 24	675 x 600	*

Eccentric Increaser SP x G



6 x 4	150 x 100	043237
10 x 4	250 x 100	043268
10 x 5	250 x 135	043655
10 x 6	250 x 150	043269
10 x 8	250 x 200	043270
12 x 4	300 x 100	043271
12 x 5	300 x 135	043656
12 x 6	300 x 150	043272
12 x 8	300 x 200	043273
12 x 10	300 x 250	043274
15 x 4	375 x 100	043275
15 x 6	375 x 150	043277
15 x 8	375 x 200	043278
15 x 10	375 x 250	043279
15 x 12	375 x 300	043280

18 x 4	450 x 100	043281
18 x 6	450 x 150	043282
18 x 8	450 x 200	043230
18 x 10	450 x 250	043512
18 x 12	450 x 300	043283
18 x 15	450 x 375	043284
21 x 15	525 x 375	043285
21 x 18	525 x 450	*
24 x 18	600 x 450	*
24 x 21	600 x 525	*
27 x 21	675 x 525	*
27 x 24	675 x 600	*

	Dimension		Product Code
	inches	mm	
Cap			
	4	100	043959
	5	135	043960
	6	150	043988
	8	200	043961
	10	250	043886
	12	300	043987
	15	375	043962
	18	450	043746
	21	525	043747
	24	600	043168
27	675	043749	


Bell Cleanout Adapter

	6	150	043760
---	---	-----	--------


Spigot Cleanout Adapter

	6	150	043750
---	---	-----	--------


Adapter Coupling G x G (PVC Sp to ABS)

	4	100	043712
	5 x 4	135 x 100	043711
	6 x 4	150 x 100	043713

Adapter Coupling G x G (PVC Sp to AC Sp)

	4	100	043720
	5 x 4	135 x 100	043642

Clay Tile Adapter Sp x Sp (Clay G to PVC G)

	4	100	043169
	6	150	043170
	8	200	043171

M Adapter Sp x G

	6	150	081319
---	---	-----	--------

Bushing Adapter AC Bell x PVC Sp (Sp x G)

	4 x 4	100 x 100	043724
	8 x 8	200 x 200	043727

Bushing Adapter PVC Bell x AC Sp (Sp x G)

	6 x 5	150 x 135	043619
---	-------	-----------	--------

Adapter PVC Bell (off concrete main)

	4	100	043770
	6	150	043771
	8	200	043772


Sanded Manhole Bell (w/o stop)

	4	100	043060
	5	135	043334
	6	150	043061
	8	200	043063
	10	250	043064
	12	300	043065
	15	375	043062
	18	450	043066
	21	525	043067
	24	600	043068
	27	675	043591


PRODUCTION SELECTION CHART

	Dimension		Product Code
	inches	mm	


Manhole Adapter G x SP (24"/600mm long)

	4	100	043297
	5	135	043299
	6	150	043301
	8	200	043302
	10	250	043328
	12	300	043329
	15	375	043330
	18	450	043331
	21	525	043548
	24	600	043332
	27	675	*


Wing Adapter (mortar-on)

	4	100	043190
	5	135	043192
	6	150	043191
	8	200	043193
	10	250	043194
	12	300	043195
	15	375	043196
	18	450	*
	21	525	*
	24	600	*
	27	675	*

Universal Storm Sewer Saddle (c/w Bell & Seating Gasket)

	4	100	082244
	5	135	082245
	6	150	082246
	8	200	082248

Hand Tight Expansion End Plug


	4	100	043200
	5	135	043201
	6	150	043202
	8	200	043212

Stainless Steel Strap


	6	150	043346
	8	200	043348
	10	250	043350
	12	300	043352

	Dimension		Product Code
	inches	mm	


Boot Jack - Sanitary

	5x4x4 (P)	135x100x100x100 (P)	043705
	6x5x5 (P)	150x135x135x100 (P)	043706
	6x4x4 (P)	150x100x100x100 (P)	043707


Boot Jack - Storm

	5x4x4 (P)	135x100x100x100 (P)	043715
	6x5x5 (P)	150x135x135x100 (P)	043716
	6x4x4 (P)	150x100x100x100 (P)	043717

Test Tee - Sanitary

	4x4x4 (C)	100x100x100 (C)	043646
	5x4x4 (C)	135x100x100 (C)	043647
	5x5x4 (C)	135x135x100 (C)	043648
	6x6x4 (C)	150x150x100 (C)	043649

Test Tee - Storm

	4x4x4 (C)	100x100x100 (C)	043666
	5x4x4 (C)	135x100x100 (C)	043667
	5x5x4 (C)	135x135x100 (C)	043668
	6x6x4 (C)	150x150x100 (C)	043669

(P): Plug (C): Cap

Description	Product Code
Metric	

Lubricant

1 kg container	074811
4 kg container	074812

Dimension		Product Code
inches	mm	

Lubricant

1 kg container	074811
4 kg container	074812

InsertaTees (for DR35 PVC Sewer Pipe)



8 x 4	200 x 100	072434
10 x 4	250 x 100	072440
10 x 6	250 x 150	072441
12 x 4	300 x 100	072436
12 x 6	300 x 150	072437
12 x 8	300 x 200	072442
15 x 4	375 x 100	072438
15 x 6	375 x 150	072443
15 x 8	375 x 200	072444
18 x 4	450 x 100	072439
18 x 6	450 x 150	072445
18 x 8	450 x 200	072446
18 x 10	450 x 250	072447
18 x 12	450 x 300	072448
21 x 4	525 x 100	072449
21 x 6	525 x 150	072450
21 x 8	525 x 200	072451
21 x 10	525 x 250	072452
21 x 12	525 x 300	072453
21 x 15	525 x 375	-
24 x 4	600 x 100	072583
24 x 6	600 x 150	072584
24 x 8	600 x 200	072585
24 x 10	600 x 250	072586
24 x 12	600 x 300	072587
27 x 4	675 x 100	072588
27 x 6	675 x 150	072589
27 x 8	675 x 200	072590
27 x 10	675 x 250	072591
27 x 12	675 x 300	072592
* 30 x 4	750 x 100	072593
* 30 x 6	750 x 150	072594
* 30 x 8	750 x 200	072595
* 30 x 10	750 x 250	072596
* 30 x 12	750 x 300	072597
** 36 x 4	900 x 100	072598
** 36 x 6	900 x 150	072599
** 36 x 8	900 x 200	072600
** 36 x 10	900 x 250	072601
** 36 x 12	900 x 300	072602

* 30" DR35 32.000" O.D. Pipe w .915 WT Pipe
 ** 36" DR35 38.300" O.D. Pipe w 1.100 WT Pipe



IPEX OFFERS A 4" x 3" SDR 35 ADAPTER BUSHING

IPEX offers a new adapter bushing to create a transition between a SDR35 Drain Line solvent weld system and a Ring-Tite® gasket system.

Deflection stress on buried piping systems is a common occurrence in construction and can inadvertently place unwanted stress on joints. The new adapter bushing is designed with a 4" long spigot to reduce any chance of the joint pulling apart as a result of deflection stress.

Dimension	Product Code
inches	Code

SDR35 Adapter Bushing (for transition between Solvent Weld & Ring-Tite)

4 x 3 Extended Sp x H	243040
-----------------------	--------

ULTRA-RIB PIPING SYSTEMS

8" – 24" (200mm – 600mm)

Ultra-Rib®

IPEX Ultra-Rib® is a gravity flow PVC sewer pipe with concentric reinforcing ribs that encircle the pipe to provide superior ring stiffness and performance. It is an extruded, seamless pipe made from high grade PVC compound.

Ultra-Rib is available in standard sewer sizes from 200mm to 600mm (8" – 24"). Its optimized profile design offers strength and reliability, as well as economy and superior flow rates.

APPLICATIONS

- Sanitary and Storm Sewers
- Industrial Lines
- Highway & Culvert

STANDARDS



ADVANTAGES

- 1 Tight Joints and Lower Treatment Costs**
Eliminate infiltration and exfiltration. Ultra-Rib's 50 psi capable joints easily outperform concrete and corrugated PE joints.
- 2 Superior Flow Characteristics**
Because of the smooth inside wall of Ultra-Rib, a Manning's number of 0.009 can be used when designing systems using Ultra-Rib pipe. This compares with Manning's numbers of up to 0.023 for other materials like clay or concrete.
- 3 Abrasion Resistance**
Ultra-Rib has been proven to be more abrasion resistant than other profile pipes, and has out-performed concrete pipe in testing at California State University.
- 4 Chemical Resistance**
PVC is virtually immune to chemical attack from any type of sewage. Hydrogen sulphide attack, which causes millions of dollars of damage to concrete and metal infrastructure, will not affect Ultra-Rib.
- 5 Stress Crack Resistance**
While some HDPE pipes have been found to crack prematurely under load, Ultra-Rib's tough PVC construction and superior formulation has been proven to be immune to these problems.


DID YOU KNOW?

Ultra-Rib seamless 'Open Profile' wall has the same stiffness as DR35, but with a more efficient use of structural material.



DIMENSIONS

Pipe Size		Average I.D.		Average Diameter Over Ribs		O.D. at Bell		Waterway Wall t	
in	mm	in	mm	in	mm	in	mm	in	mm
8	200	7.89	200	8.80	224	9.78	248	0.087	2.20
10	250	9.86	251	11.00	280	12.22	311	0.091	2.30
12	300	11.74	298	13.10	333	14.59	371	0.102	2.60
15	375	14.37	365	16.04	408	17.82	453	0.110	2.80
18	450	17.65	448	19.57	497	21.77	553	0.130	3.30
21	525	20.75	527	22.80	579	25.14	638	0.160	4.06
24	600	23.50	597	25.61	650	28.24	717	0.180	4.58



SHORT FORM SPECIFICATIONS

GENERAL

IPEX Ultra-Rib PVC Pipe is available in sizes 8, 10, 12, 15, 18, 21 and 24 inch (200mm - 600mm)

MATERIAL

Ultra-Rib PVC Pipe shall be made of PVC compound having a cell classification of 12454 as defined in ASTM D1784B.

PRODUCT

The pipe shall be extruded with a smooth interior and with solid reinforcing ribs on the exterior at right angles to the pipe. The space between any two ribs serves as a gasket race.

Ultra-Rib PVC pipe and fittings shall be certified to CSA B182.4 "Profile (Ribbed) PVC Sewer Pipe and Fittings", and shall meet the requirements of ASTM F794 "Standard Specification for Poly (Vinyl Chloride) (PVC) Ribbed Gravity Sanitary Pipe and Fittings Based on Controlled Inside Diameter".

PIPE STIFFNESS

Pipe stiffness must be 46 lbs/in of sample length/ inch of deflection at 5% vertical deflection when tested according to ASTM D2412.

JOINTS

Gaskets for use with Ultra-Rib pipe are manufactured from EPDM and are designed specifically for use with Ultra-Rib pipe. This unique design is also available in Nitrile.

Sealing gaskets shall meet the requirements of CSA B182.4 and ASTM F477, with the additional requirement that joints shall be able to withstand 345 kPa (50 psi) hydrostatic pressure.

The joint will not leak at 10.8 psi or 25' of head with 22" Hg vacuum with spigot under 5% ring deflection and joint at full axial deflection.

MOLDED FITTINGS

Injection-molded gasketed PVC fittings of ribbed construction shall be certified to CSA B182.1 or CSA B182.2 and used for direct connection to Ultra-Rib pipes in available sizes.

FABRICATED FITTINGS

Fittings fabricated for use with Ultra-Rib pipe shall be certified to CSA B182.4 or ASTM F794 and may include legs of PVC pipe meeting CSA B182.1, B182.2 or ASTM D3034 or F679.

LUBRICANT

Assembly of Ultra-Rib pipe and fittings shall be done in accordance with the manufacturer's directions using only IPEX PVC pipe lubricant. Substitute lubricants shall not be used. IPEX lubricant shall be applied to the inside of the bell to be joined, to a uniform thickness for a distance inside the bell equivalent to three ribs from outside edge.

COLOR CODING

Pipe shall be color coded green.



PRODUCT SELECTION CHART



Dimension		Product Code
inches	mm	

Ultra-Rib Pipe



8	200	086008
10	250	086010
12	300	086012
15	375	086015
18	450	086018
21	525	086021
24	600	086024



Tee B x B x B (Ultra-Rib x Ultra-Rib x Ultra-Rib)



8	200	087100
10 x 8	250 x 200	087101
10	250	087102
12 x 8	300 x 200	087103
12 x 10	300 x 250	087104
12	300	087105
15 x 8	375 x 200	087106
15 x 10	375 x 250	087107
15 x 12	375 x 300	087108
15	375	087109
18 x 8	450 x 200	087110
18 x 10	450 x 250	087111
18 x 12	450 x 300	087112
18 x 15	450 x 375	087113
18	450	087114
21 x 8	525 x 200	087115
21 x 10	525 x 250	087116
21 x 12	525 x 300	087117
21 x 15	525 x 375	087118
21 x 18	525 x 450	087119
21	525	087120
24 x 8	600 x 200	087121
24 x 10	600 x 250	087122
24 x 12	600 x 300	087123
24 x 15	600 x 375	087124
24 x 18	600 x 450	087125
24 x 21	600 x 525	087126
24	600	087127

Dimension		Product Code
inches	mm	

Tee B x B x G (Ultra-Rib x Ultra-Rib x DR35 or 28)



8 x 4	200 x 100	087150
8 x 5	200 x 135	087151
8 x 6	200 x 150	087152
8	200	087153
10 x 4	250 x 100	087154
10 x 5	250 x 135	087155
10 x 6	250 x 150	087156
10 x 8	250 x 200	087157
12 x 4	300 x 100	087159
12 x 5	300 x 135	087160
12 x 6	300 x 150	087161
12 x 8	300 x 200	087162
12 x 10	300 x 250	087163
12	300	087164
15 x 4	375 x 100	087165
15 x 5	375 x 135	087166
15 x 6	375 x 150	087167
15 x 8	375 x 200	087168
15 x 10	375 x 250	087169
15 x 12	375 x 300	087170
18 x 4	450 x 100	087172
18 x 5	450 x 135	087173
18 x 6	450 x 150	087174
18 x 8	450 x 200	087175
18 x 10	450 x 250	087176
18 x 12	450 x 300	087177
18 x 15	450 x 375	087178
18	450	087179
21 x 4	525 x 100	087180
21 x 5	525 x 135	087181
21 x 6	525 x 150	087182
21 x 8	525 x 200	087183
21 x 10	525 x 250	087184
21 x 12	525 x 300	087185
21 x 15	525 x 375	087186
21 x 18	525 x 450	087187
21	525	087188
24 x 4	600 x 100	087190
24 x 5	600 x 135	087199
24 x 6	600 x 150	087191
24 x 8	600 x 200	087192
24 x 10	600 x 250	087193
24 x 12	600 x 300	087194
24 x 18	600 x 450	087196
24 x 21	600 x 525	087197
24	600	087198

Dimension		Product Code
inches	mm	

Wye B x B x G (Ultra-Rib x Ultra-Rib x DR35 or 28)

	8 x 4	200 x 100	087250
	8 x 5	200 x 135	087251
	8 x 6	200 x 150	087252
	8	200	087253
	10 x 4	250 x 100	087254
	10 x 5	250 x 135	087255
	10 x 6	250 x 150	087256
	10 x 8	250 x 200	087257
	10	250	087258
	12 x 4	300 x 100	087259
	12 x 5	300 x 135	087260
	12 x 6	300 x 150	087261
	12 x 8	300 x 200	087262
	12 x 10	300 x 250	087263
	12	300	087264
	15 x 4	375 x 100	087265
	15 x 5	375 x 135	087266
	15 x 6	375 x 150	087267
	15 x 8	375 x 200	087268
	15 x 10	375 x 250	087269
	15 x 12	375 x 300	087270
	15	375	087271
	18 x 4	450 x 100	087272
	18 x 5	450 x 135	087273
	18 x 6	450 x 150	087274
	18 x 8	450 x 200	087275
	18 x 10	450 x 250	087276
	18 x 12	450 x 300	087277
	18 x 15	450 x 375	087278
	18	450	087279
	21 x 4	525 x 100	087235
	21 x 5	525 x 135	087236
	21 x 6	525 x 150	087237
	21 x 8	525 x 200	087238
	21 x 10	525 x 250	087239
	21 x 12	525 x 300	087240
	21 x 15	525 x 375	087241
	21 x 18	525 x 450	087242
	21	525	087243
	24 x 4	600 x 100	087360
	24 x 5	600 x 135	087359
	24 x 6	600 x 150	087361
	24 x 8	600 x 200	087362
	24 x 10	600 x 250	087363
	24 x 12	600 x 300	087364
	24 x 15	600 x 375	087365
	24 x 18	600 x 450	087366
	24 x 21	600 x 525	087367
	24	600	087368

Dimension		Product Code
inches	mm	


Wye B x B x B (Ultra-Rib x Ultra-Rib x Ultra-Rib)

	8	200	087280
	10 x 8	250 x 200	087281
	10	250	087282
	12 x 8	300 x 200	087283
	12 x 10	300 x 250	087284
	12	300	087285
	15 x 8	375 x 200	087286
	15 x 10	375 x 250	087287
	15 x 12	375 x 300	087288
	15	375	087289
	18 x 8	450 x 200	087290
	18 x 10	450 x 250	087291
	18 x 12	450 x 300	087292
	18 x 15	450 x 375	087293
	18	450	087294
	21 x 8	525 x 200	087295
	21 x 10	525 x 250	087296
	21 x 12	525 x 300	087297
	21 x 15	525 x 375	087298
	21 x 18	525 x 450	087299
	21	525	087316
	24 x 8	600 x 200	087317
	24 x 10	600 x 250	087318
	24 x 12	600 x 300	087319
	24 x 15	600 x 375	087320
	24 x 18	600 x 450	087321
	24 x 21	600 x 525	087322
	24	600	087323

PRODUCT SELECTION CHART


	Dimension		Product Code
	inches	mm	

90° Elbow B x B (Ultra-Rib x Ultra-Rib)




8	200	087300
10	250	087301
12	300	087302
15	375	087303
18	450	087304
21	525	087305
24	600	087306

45° Elbow B x B (Ultra-Rib x Ultra-Rib)



8	200	087325
10	250	087326
12	300	087327
15	375	087328
18	450	087329
21	525	087330
24	600	087331


22-1/2° Elbow B x B (Ultra-Rib x Ultra-Rib)



8	200	087375
10	250	087376
12	300	087377
15	375	087378
18	450	087379
21	525	087380
24	600	087381

	Dimension		Product Code
	inches	mm	



Increaser B x G (Ultra-Rib x DR35 or 28)



8 x 4	200 x 100	087400
8 x 5	200 x 135	087401
8 x 6	200 x 150	087402
10 x 4	250 x 100	087403
10 x 5	250 x 135	087404
10 x 6	250 x 150	087405
10 x 8	250 x 200	087406
12 x 4	300 x 100	087407
12 x 5	300 x 135	087408
12 x 6	300 x 150	087409
12 x 8	300 x 200	087410
12 x 10	300 x 250	087411
15 x 4	375 x 100	087412
15 x 5	375 x 135	087413
15 x 6	375 x 150	087414
15 x 8	375 x 200	087415
15 x 10	375 x 250	087416
15 x 12	375 x 300	087417
18 x 4	450 x 100	087418
18 x 5	450 x 135	087419
18 x 6	450 x 150	087420
18 x 8	450 x 200	087421
18 x 10	450 x 250	087422
18 x 12	450 x 300	087423
18 x 15	450 x 375	087424
21 x 4	525 x 100	087482
21 x 6	525 x 150	087483
21 x 8	525 x 200	087484
21 x 10	525 x 250	087485
21 x 12	525 x 300	087486
21 x 18	525 x 450	087488
24 x 4	600 x 100	087489
24 x 6	600 x 150	087490
24 x 8	600 x 200	087491
24 x 10	600 x 250	087492
24 x 12	600 x 300	087493
24 x 15	600 x 375	087494
24 x 18	600 x 450	087495
24 x 21	600 x 525	087496


	Dimension		Product Code
	inches	mm	

Stop Coupling B x B



	8	200	087450
	10	250	087451
	12	300	087452
	15	375	087453
	21	525	087455
			

	Dimension		Product Code
	inches	mm	


Plug SP

	8	200	087525
	10	250	087526
	12	300	087527
	15	375	087528
	18	450	087529
	21	525	087530
	24	600	087531

Repair Coupling B x B

	8	200	087475
	10	250	087476
	12	300	087477
	15	375	087478
	18	450	087479
	21	525	087480
	24	600	087481


Manhole Adapter (for grout)

	8	200	087550
	10	250	087551
	12	300	087552
	15	375	087553
	18	450	087554
	21	525	087555
	24	600	087556


Gaskets

	8	200	087808
	10	250	087810
	12	300	087812
	15	375	087915
	18	450	087818
	21	525	087821
	24	600	087824

Ultra-Rib to DR 35 Adapter

	8	200	087575
	10	250	087576
	12	300	087577
	15	375	087578
	18	450	087579
	21	525	087580
	24	600	087581


Cap B

	8	200	087500
	10	250	087501
	12	300	087502
	15	375	087503
	18	450	087504
	21	525	087505
	24	600	087506

PRODUCT SELECTION CHART


	Dimension		Product Code
	inches	mm	

Wing Adapter (Adapts Ultra-Rib to AC, VCT or concrete Mains)



8	200	087625
10	250	087626
12	300	087627
15	375	087628
18	450	087629
21	525	087630
24	600	087631

Inserta-Tees



8 x 4	200 x 100	087650
10 x 4	250 x 100	087651
10 x 6	250 x 150	087652
10 x 8	250 x 200	087649
12 x 4	300 x 100	087653
12 x 6	300 x 150	087654
12 x 8	300 x 200	087655
12 x 10	300 x 250	**
15 x 4	375 x 100	087656
15 x 6	375 x 150	087657
15 x 8	375 x 200	087658
15 x 12	375 x 300	087648
18 x 4	450 x 100	087660
18 x 6	450 x 150	087661
18 x 8	450 x 200	087662
18 x 10	450 x 250	087663
18 x 12	450 x 300	087664
18 x 15	450 x 375	Available on Request
21 x 4	525 x 100	087665
21 x 6	525 x 150	087666
21 x 8	525 x 200	087667
21 x 10	525 x 250	087668
21 x 12	525 x 300	087674
21 x 15	525 x 375	Available on Request
24 x 4	600 x 100	087669
24 x 6	600 x 150	087670
24 x 8	600 x 200	087671
24 x 10	600 x 250	087672
24 x 12	600 x 300	087685



Vortex Flow™
ODOR & CORROSION CONTROL

Looking for a cost-effective **solution** to sewer odor & corrosion?



Product Information & Benefits



CORROSION CONTROL

By oxidizing dissolved H_2S , a Vortex Flow Insert in a municipal sewer drop can significantly reduce concrete and metal corrosion, extending sewer life and saving the municipality money.

CHEMICAL FREE ODOR CONTROL

By increasing dissolved oxygen levels in wastewater and oxidizing sulfides and other odorous compounds, the Vortex Flow Insert eliminates the need for costly chemical injection, high-maintenance biofilters and air scrubbers.

LOW MAINTENANCE

With no moving parts, the Vortex Flow Insert operates virtually maintenance free dramatically reducing maintenance costs of manholes and sewers.

BUILT-TO-SPEC FOR ANY SIZE

Manholes, chambers and pumping stations are built in a variety of sizes. Each Vortex Flow Insert is custom designed based on the peak flow that the unit is required to handle.

Vortex Flow Inserts from IPEX are a proven method for dealing with odor and corrosion in sewer drops. Simple, cost-effective and reliable, Vortex Flow Inserts have been proven to deliver significant cost savings across North America.

Using the wastewater's own flow energy to suppress turbulence, aerate the sewage and oxidize dissolved hydrogen sulfides (H_2S), the Vortex Flow's patented spiral design sucks odorous gases downward towards the bottom of the structure where they are entrained back into the sewage flow.



1.800.463.9572

Product manufactured by IPEX Inc and distributed in the United States by IPEX USA LLC.
Vortex Flow™ is a trademark of IPEX Branding Inc.

SOLVENT WELD SEWER FITTINGS

3" - 8" (75mm - 200mm)
8" - 24" (200mm - 600mm)

IPEX offers a wide variety of moulded sewer fittings 3" in diameter and larger. Solvent welded fittings are typically installed in sanitary and drainage systems. Injection-moulded fittings are available in 3" to 8" sizes. Fabricated DR35 solvent weld sewer fittings are available in 8" to 24" sizes.

SOLVENT WELD VS. GASKETED JOINTS

Solvent welding is a process by which a joint is made by chemically fusing together a pipe and a fitting. A solvent is applied to the surface of a PVC pipe spigot and the inside of a matching bell. In some cases a primer may be used to prepare the surfaces. The solvent dissolves some of the chemical bonds in the PVC material, effectively "melting" the material. Once the two surfaces are pushed together the material from the two surfaces begin to fuse together. As the joint cures, the solvent evaporates and the joint becomes stronger, until it essentially becomes a continuous pipe.

Solvent welded joints are able to resist large tensile loads and will not pull apart. In fact, it can be shown that the pipe itself will fail before the joint will.

APPLICATIONS

- Gravity Flow Sanitary Sewers
- Storm Sewers
- Sewer Laterals

STANDARDS



D3034



B182.1
B182.2




File 2431
(4", 6" & 8")


ADVANTAGES


- 1 Leak-Proof Joints**
Properly installed DR35 solvent weld sewer fittings provide leak-proof joints. This eliminates underground water infiltration and exfiltration. The results: substantial savings in sewage treatment costs for municipalities.
- 2 Superior Chemical Resistance**
The chemical resistance of SDR35 sewer fittings is exceptional. Acids, alkalis and normally diluted hydrocarbons have little or no effect. Aggressive soil conditions due to sulfates, carbonates, industrial effluents and acid rain are easily handled by DR35 solvent weld sewer fittings.
- 3 Super Abrasion Resistance**
SDR35 solvent weld sewer fittings are highly resistant to abrasion, making them ideal for transporting abrasive effluent, even in high velocity storm sewer systems.





PRODUCT SELECTION CHART


	Dimension		Product Code
	inches	mm	
Tee H x H x H			
	3	76	040102
	4	100	040104
	4 x 3	100 x 75	040109
	6	150	040106
	6 x 4	150 x 100	040105
	8	200	040108
	8 x 4	200 x 100	040117
	8 x 6	200 x 150	040118
	* 10	250	040111
	* 10 x 4	250 x 100	040119
	* 10 x 6	250 x 150	040120
	* 10 x 8	250 x 200	040121
	* 12	300	040112
	* 12 x 4	300 x 100	040122
	* 12 x 6	300 x 150	040123
	* 12 x 8	300 x 200	040124
	* 12 x 10	300 x 250	040125
	* 15	375	040113
	* 15 x 6	375 x 150	040128
	* 15 x 8	375 x 200	040126
	* 15 x 10	375 x 250	040083
	* 15 x 12	375 x 300	040127
	* 18	450	040115
	* 18 x 6	450 x 150	040091
	* 18 x 8	450 x 200	040092
	* 18 x 15	450 x 375	040919
	* Fabricated Fitting		


Cleanout Tee H x H x FPT			
	4	100	040922

2-Way Cleanout			
	4	100	040350

	Dimension		Product Code
	inches	mm	
Cross Tee H x H x H x H			
	3	75	040975
	4	100	040976
	* 6	150	040915
	* 8	200	040828
	* 12	300	040010
	* Fabricated Fitting		

Tee Wye H x H x H			
	3	75	040155
	4	100	040156
	6	150	040159
	6 x 4	150 x 100	040158
	* 8	200	040801
	* 8 x 4	200 x 100	040129
	* 8 x 6	200 x 150	040110
	* Fabricated Fitting		


Tee Wye S x H x H			
	4	100	040157

Saddle Tee (solvent skirt and branch)			
	4 on 6	100 on 150	040775
	4 on 8	100 on 200	040776
	4 on 12	100 on 300	040804
	6 on 8	150 on 200	040779
	6 on 10	150 on 250	040081
	6 on 12	150 on 300	040841
	6 on 15	150 on 375	040914
	8 on 12	200 on 300	040840
	10 on 12	250 on 300	040097

PRODUCTION SELECTION CHART

Dimension		Product Code
inches	mm	

45° Wye H x H x H



3	75	040302
3 x 2	75 x 50	040303
4	100	040304
4 x 2	100 x 50	040308
4 x 3	100 x 75	040309
6	150	040306
6 x 4	150 x 100	040307
8	200	040311
8 x 4	200 x 100	040310
8 x 6	200 x 150	040312
* 10	250	040313
* 10 x 4	250 x 100	040315
* 10 x 6	250 x 150	040316
* 10 x 8	250 x 200	040317
* 12	300	040314
* 12 x 4	300 x 100	040305
* 12 x 6	300 x 150	040319
* 12 x 8	300 x 200	040320
* 12 x 10	300 x 250	040321
* 15	375	040325
* 15 x 4	375 x 100	040040
* 15 x 6	375 x 150	040323
* 15 x 8	375 x 200	040326
* 15 x 10	375 x 250	040327
* 15 x 12	375 x 300	040324


* Fabricated Fitting

45° Wye S x H x H



3	75	040332
4	100	040334
6	150	040338

45° Double Wye



6 x 4	150 x 100	040172
6	150	040331
* 8 x 4	200 x 100	040170
* 8 x 6	200 x 150	040030
* 8	200	040050
* 10 x 8	250 x 200	040031
* 10	250	040018
* 12 x 10	300 x 250	040328
* 12	300	040329

* Fabricated Fitting


Dimension		Product Code
inches	mm	

Saddle Wye (solvent skirt and branch)




4 on 6	100 on 150	040785
4 on 8	100 on 200	040786
4 on 10	100 on 250	040777
4 on 12	100 on 300	040787
6 on 8	150 on 200	040788
6 on 15	150 on 375	040675
8 on 24	200 on 600	040087

90° Elbow H x H (long turn)




3	75	040255
4	100	040214
6	150	040280
8	200	040036

90° Elbow S x H (long turn)



3	75	040272
4	100	040234
6	150	040282
8	200	040283


90° Elbow H x H



3	75	040037
4	100	040256
6	150	040206
8	200	040208
10	250	040260
* 12	300	040261
* 15	375	040262
* 18	450	040263
* 24	600	040075

* Fabricated Fitting

90° Elbow S x H




4	100	040274
6	150	040236
8	200	040237
* 12	300	040258
* 15	375	040103

* Fabricated Fitting

Dimension		Product Code
inches	mm	

45° Elbow H x H



3	75	040502
4	100	040504
6	150	040506
8	200	040508
* 10	250	040407
* 12	300	040409
* 15	375	040410
* 18	450	040411
* 24	600	040399

* Fabricated Fitting


45° Elbow S x H



3	75	040402
4	100	040404
6	150	040406
8	200	040408
* 10	250	040412
* 12	300	040413
* 15	375	040414
* 18	450	040405

* Fabricated Fitting

22-1/2° Elbow H x H



3	75	040963
4	100	040964
6	150	040969
8	200	040970
* 10	250	040971
* 12	300	040973
* 15	375	040974
* 18	450	040042

* Fabricated Fitting

22-1/2° Elbow S x H




4	100	040864
6	150	040866
* 18	450	040977

* Fabricated Fitting

Dimension		Product Code
inches	mm	


Increaser Coupling H x H



4 x 2	100 x 50	040656
4 x 3	100 x 75	040654
6 x 4	150 x 100	040661
* 8 x 4	200 x 100	040610
8 x 6	200 x 150	040611
* 10 x 4	250 x 100	040613
* 10 x 6	250 x 150	040614
* 10 x 8	250 x 200	040615
* 12 x 4	300 x 100	040616
* 12 x 6	300 x 150	040617
* 12 x 8	300 x 200	040618
* 12 x 10	300 x 250	040619
* 15 x 4	375 x 100	040620
* 15 x 6	375 x 150	040621
* 15 x 8	375 x 200	040622
* 15 x 10	375 x 250	040623
* 15 x 12	375 x 300	040627
* 18 x 10	450 x 250	040101
* 18 x 15	450 x 375	040630
* 21 x 18	600 x 450	040086

* Fabricated Fitting


Coupling w Stop H x H



2	50	040600
3	75	040602
4	100	040604
6	150	040606
8	200	040631
* 10	250	040608
* 12	300	040612
* 15	375	040609
* 18	450	040603
* 24	600	040078

* Fabricated Fitting

Repair Coupling H x H




4	100	040624
6	150	040626

PRODUCTION SELECTION CHART

	Dimension		Product Code
	inches	mm	

Extended Bushing S x H



6 x 4	150 x 100	040939
8 x 4	200 x 100	040897
8 x 6	200 x 150	040940
* 10 x 4	250 x 100	040898
10 x 6	250 x 150	040899
* 10 x 8	250 x 200	040900
* 12 x 6	300 x 150	040902
* 12 x 8	300 x 200	040903
* 12 x 10	300 x 250	040904
* 15 x 10	375 x 250	040905
* 15 x 12	375 x 300	040906
* 18 x 12	450 x 300	040913
* 18 x 15	450 x 375	040908


* Fabricated Fitting

Reducer Bushing S x H




4 x 3	100 x 75	040933
6 x 4	150 x 100	040896

Reducer Bushing S x FPT



4 x 1-1/2	100 x 40	040416
-----------	----------	--------


Adapter (Sewer Spigot x DWV Hub)



4	100	040728
4 long	100 long	040808
6	150	040729
* 18	450	040340

* Fabricated Fitting


Adapter Bushing (Sewer Spigot x DWV Hub)



3 x 1-1/2	76 x 40	040932
3 x 2	76 x 50	040341
4 x 1-1/2	100 x 40	040011
4 x 2	100 x 50	040935


	Dimension		Product Code
	inches	mm	

Extended Adapter Bushing (Sewer Spigot x DWV Hub)



4 x 3	100 x 75	040934
6 x 4	150 x 100	040941

Adapter Sleeve (Sewer Hub x DWV Spigot)



4	100	040342
12	300	040207

Cast Iron Spigot Adapter H x H



4 x 4	100 x 100	040704
-------	-----------	--------

Adapter Coupling (Sewer Hub x DWV Hub)



4 x 3	100 x 75	040655
4 x 4	100 x 100	040725
6 x 4	150 x 100	040727
6 x 6	150 x 150	040756

Male Adapter Hub x MPT



4	100	040723
---	-----	--------

Female Adapter Hub x FPT



3	75	040948
4	100	040949
6	150	040952
8	200	040945
* 10	250	040946
* 12	300	040947

* Fabricated Fitting

Dimension		Product Code
inches	mm	

Cleanout Adapter (Spigot x FPT)



3	75	040953
4	100	040954
6	150	040956
* 8	200	040955
* 10	250	040931
* 12	300	040173

* Fabricated Fitting

Dimension		Product Code
inches	mm	


Threaded Plug (Countersunk)



4	100	040492
6	150	040958
* 8	200	040044
* 10	250	040928
* 12	300	040929


* Fabricated Fitting

Cleanout (Spigot x cap)




6	150	063750
---	-----	--------

Closet Flange (Countersunk)



4	100	040965
---	-----	--------

Cleanout (Hub x cap)



6	150	063760
---	-----	--------

Offset Downspout Adapter



2 x 3 x 4	50 x 75 x 100	040765
3 x 4 x 4	75 x 100 x 100	040767
4 x 6 x 6	100 x 150 x 150	040766

Solvent Cap



3	75	040986
4	100	040959
6	150	040988
8	200	040990
10	250	040995
12	300	040996
15	375	040997
* 18	450	040998
* 21	525	040985
* 24	600	040917

* Fabricated Fitting


Downspout Adapter



H2 x 3 x 3	50 x 75 x 75	040013
H2 x 3 x 4	50 x 75 x 100	040961
H3 x 4 x 4	75 x 100 x 100	040962
* H4 x 4 x 4	100 x 100 x 100	040972
H4 x 6 x 6	100 x 150 x 150	040943
H6 x 6 x 6	150 x 150 x 150	040944

* Fabricated Fitting

MPT Plug



3	75	040423
4	100	040424
6	150	040926
8	200	040927

Drain Grate



3	75	040811
4	100	040911
6	150	040912

PERFORATED SEWER PIPE (NEW ENGLAND)

4" - 6" (100mm - 150mm)

Designed for use in septic fields and for foundation drainage, our New England perforation pattern PVC sewer pipe comes with two rows of holes, and is engineered to provide even distribution of effluent from the supply header. The solvent weld assembly method offers tight joints, eliminating infiltration, exfiltration and root infestation.

ADVANTAGES

① Costs Less to Operate

A plastic sewer system costs less to operate and maintain because it has greater flow capacity per given size and fewer joints. The pipe is flexible enough to conform to shifts and settling caused by unstable soil conditions or traffic without cracking, breaking or opening of the joints.

② Greater Hydraulic Efficiency

The greater hydraulic efficiency of BDS pipe and Manning's number of $n = 0.009$ results from its smooth inner wall, long lengths, and tight joints. It is not affected by sewer gases or sulfuric acid created as products of the hydrogen sulfide cycle or from aggressive soil conditions.

The preceding virtues eliminate build up of slime, slime bulk and sand which improves efficiency flow and discharge over traditional materials of equivalent size for the life of the sewer system.

③ Life Cycle

The economic life cycle of a PVC sewer system is projected at more than 50 years.

APPLICATIONS

- Building Sanitary Drain and Building Storm Drain
- Building Sewer and Building Storm Sewer
- Sewer Lateral or Stub Line

STANDARDS

PVC Sewer Pipe



D2729



B182.1
B182.2



3624-130

PVC Sewer Fitting



D3034




B182.1
B182.2



SHORT FORM SPECIFICATIONS

4" and 6" perforated PVC pipe shall be DR35 in 10 foot laying lengths with solvent bell ends. Pipe shall conform to requirements of ASTM D3034 and be certified to CSA B 182.1 and B 182.2.

Perforations shall consist of 2 rows of 1/2" (12.7mm) holes positioned at 120° radially on the pipe. Spacing between holes shall be 5" (125mm).




Hole Size: 1/2" (12.7mm)
Spacing: 5" O.C. (125mm)



DID YOU KNOW?

No other pipe approaches plastic pipe in terms of low weight per foot ratio to strength. The light-weight section reduces manpower needs, reduces equipment handling cost, and freight cost.



PERFORATED SEWER PIPE SELECTION CHART
& PRODUCT DIMENSIONS (BELLED GASKETED)

Nominal Pipe Size		Product Code	DR	Avg Outside Diameter (O.D.)		Min. Wall Thick (t)		d		D1		D2		D3		Bell Depth B		Weight	
in	mm			in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb./100 ft.	kg/m
4	100	039143	35	4.22	107.1	0.13	3.3	3.95	100.4	4.21	106.9	4.24	107.6	4.50	114.2	1.73	43.9	107	1.6
6	150	039163	35	6.28	159.4	0.19	4.9	5.89	149.7	6.27	159.3	6.30	160.0	6.68	169.7	2.95	74.9	232	3.0

PERFORATED SEWER PIPE SELECTION CHART
& PRODUCT DIMENSIONS (BELLED SOLVENT WELD)

Nominal Pipe Size		Product Code	DR	Avg Outside Diameter (O.D.)		Min. Wall Thick (t)		d		D1		D2		D3		Bell Depth B		Weight	
in	mm			in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lb./100 ft.	kg/m
4	100	003649	35	4.22	107.1	0.13	3.3	3.95	100.4	4.21	106.9	4.24	107.6	4.50	114.2	1.73	43.9	107	1.6
6	150	003660	35	6.28	159.4	0.19	4.9	5.89	149.7	6.27	159.3	6.30	160.0	6.68	169.7	2.95	74.9	232	3.0

Perforated pipe is also available from 8" (200mm) to 36" (900mm).

White Bionax PVCO

6" - 18" (150mm - 450mm)

BIONAX®

White Bionax® sewer pressure pipe is designed for sewer applications and sized to Cast Iron Outside Diameter (CIOD) Pipe. Bionax sewer pressure pipe is fully compatible with existing PVC pipe inventories and available in sizes 150mm through 450mm with a pressure rating of 235 psi for all sizes or 165 psi for sizes 400mm and 450mm only.

Bionax sewer pressure pipe is the same Bionax pipe we use in water applications with a different colour and print line to easily differentiate between applications. The pipe is made in 6.1m (20ft.) lay lengths and is intended for sewer force main applications or for when pressure rated pipe and joint is required for sewer installation. It offers all the same performance benefits of Bionax water pipe including corrosion resistance, fatigue strength and longevity.

Molecularly Oriented PVC Pipe for Municipal Applications

Bionax's molecular orientation dramatically enhances the pipe properties that are important to pipeline designers:

- Larger internal diameters increase flow rates and reduce pumping costs
- Higher cyclic fatigue resistance for forcemain and irrigation applications
- Tighter bend radius when compared to standard PVC pipe

FEATURES & BENEFITS

- AWWA C909 165 or 235 PSI rated pipe
- Cast iron outside diameter for ease of use with regular accessories

Improvements compared to PVC pipe:

- White colour and SEWER PRESSURE/NON-POTABLE print line for easy differentiation from a water pipe
- Higher impact strength
- Reduced friction losses and pumping costs
- Lower surge pressures for the same flow conditions
- Increased cyclic strength
- Increased resistance to point loading
- Lighter weight for easier handling

- Sewer Pressure

STANDARDS



SIZES & PRESSURE CLASSES OF BIONAX

Pressure Class at
73°F / 23°C for 165 psi / 1,135 kPa

Pipe Size		OD		Product Code
in	mm	in	mm	
16	400	17.4	442	120103
18	450	19.5	495	120105

Pressure Class at
73°F / 23°C for 235 psi / 1,620 kPa

Pipe Size		OD		Product Code
in	mm	in	mm	
6	150	6.9	175	1182001
8	200	9.05	230	118202
10	250	11.1	282	118203
12	300	13.2	335	118204
14	350	15.3	389	120101
16	400	17.4	442	120102
18	450	19.5	495	120104



DID YOU KNOW?

Every length of CIOD Bionax is hydrotested to AWWA standards before being shipped. In fact, IPEX is the only manufacturer to have third-party certification (by NSF) to meet the stringent AWWA standards and by CSA to meet the CSA Standards.

SHORT FORM SPECIFICATIONS

SCOPE

This specification provides the requirements for Molecularly Oriented Polyvinyl Chloride (PVCO) pipe for sewer pressure-pipe applications.

MATERIALS

- PVCO pipe shall be manufactured from rigid Polyvinyl Chloride (PVC) compound meeting the requirements of ASTM D1784 cell class 12454.
- Gaskets shall meet ASTM F477 for high-head applications.

HYDROSTATIC DESIGN BASIS

- Starting-stock PVC pipe shall have a Hydrostatic Design Basis (HDB) of 4,000 psi.
- Finished PVCO pipe shall have an HDB of 7,100 psi.

PIPE

- Pipe shall be molecularly oriented.
- Pipe shall be produced with cast-iron-pipe outside diameters (CIOD) in all sizes.
- Pipe shall be joined by integral-bell gasketed joints conforming to ASTM D3139.
- Pipe spigot ends shall be chamfered by the manufacturer.
- Pipe shall be color-coded white.

CERTIFICATIONS

- PVCO pipe shall conform to AWWA C909 and is certified by CSA and BNQ to CSA B137.3.1.

STANDARDS

PVCO pipe shall conform to the following standards:

- ANSI/NSF Standard 14: Plastic Piping System Components and Related Materials
- ASTM D1784: Rigid Polyvinyl Chloride (PVC) compounds
- ASTM D3139: Joints for Plastic Pressure Pipes Using Flexible Elastomeric Seals
- ASTM F1483: Molecularly Oriented Polyvinyl Chloride (PVCO) Pressure Pipe
- ASTM F477: Elastomeric Seals (Gaskets) for Joining Plastic Pipe
- AWWA C909: Molecularly Oriented Polyvinyl Chloride (PVCO) Pressure Pipe, 4 inch and Larger
- CSA B137.3.1: Molecularly Oriented Polyvinyl Chloride (PVCO) Pipe for Pressure Applications



TEMPEST™
INLET CONTROL DEVICES

NEXT GENERATION STORMWATER FLOW CONTROL



CONTROL BACK-UPS & CSO'S DURING PEAK FLOW EVENTS WITH TEMPEST™ INLET CONTROL DEVICES



TEMPEST LMF

The Tempest LMF system features a vortex inlet design that allows a low flow rate to be set and eliminates the passage of odors and floatables and allows for debris and sediment to collect in the structure.



TEMPEST HF

The standard Tempest HF system allows a near constant discharge rate to be set and eliminates the passage of odors and floatables and allows for debris and sediment to collect in the structure.



TEMPEST MHF

The Tempest MHF is a standard orifice plate device designed to allow a specified flow volume through the outlet pipe at a specified head.



TEMPEST HF SUMP

The Tempest HF SUMP system is designed for catch basins &

manholes in which there is no sump or the outlet pipe is too low to install a standard Tempest device.

Request your
FREE
Conceptual
Design
today!

For unique municipal applications, IPEX has developed equally unique solutions. From advanced odor control and improved wastewater quality products such as our Vortex Flow™ Inserts to the EnviroStream™ Stormwater Treatment System, IPEX has your engineered solution.

SPECIALTY PRODUCTS



PVC Manholes and Access Chambers

78

Vortex Flow Inserts

80

Storm Sewer Inlet Controls

82



PVC MANHOLES & ACCESS CHAMBERS

PVC Manholes:
42" – 48" (1050mm & 1200mm)
Access Chambers:
24" (600mm)

IPEX manholes and access chambers are non-corroding, non-infiltrating manholes and chambers designed to maximize system access while minimizing maintenance requirements. The factory made benching is made of chemical resistant FRP or Polypropylene material, while the barrel and chimney are manufactured from IPEX Centurion™ pipe. The 1050mm and 1200mm (42" and 48") manholes can be equipped with special stainless steel steps, while the 600mm (24") access chamber is designed to allow inspection equipment or flushing equipment easy access to the sewer system. In all cases, the pre-cast concrete base acts as an anchor to prevent flotation and to stabilize the structure. Since the concrete is never in contact with the effluent or the sewer atmosphere, corrosion is eliminated

APPLICATIONS

- Industrial Sewer Systems
- High Water Table Areas
- Aggressive Effluents
- Vacuum Sewer Systems

ACCESS CHAMBERS VS. MANHOLES

With today's emphasis on occupational health and safety, most municipalities are focused on minimizing the degree of confined space work occurring in their underground systems. This is where access chambers come in.

An access chamber differs from a manhole in that it is too small to allow man entry into a sewer. It is typically from 450mm (18") to 600mm (24") in diameter and is large enough to allow the insertion of cameras or flushing equipment into the system. The major advantage is that they allow improved access to the system while minimizing the maintenance concerns associated with concrete manholes. In addition, they are cost efficient to install.

The best choice for a given system depends on a number of factors, including:

- Degree of man access required
- Size of piping system
- Number of direction changes

Ultimately, a combination of manholes and access chambers can be used for a system, with access chambers used for straight connections and full size manholes for any changes of direction



Introducing BIONAX[®] SR[™]

Water Pipe Designed for Seismic Regions



Exceeds the
Japanese Seismic
Design Standard by

70%

Compatible with
NORTH AMERICAN
Manufactured Pipe
and Fittings
(CIOD)

**CORROSION
RESISTANCE**

6" to 12"
DIAMETERS
(150 to 300 mm)

Bionax SR – Seismic Water Pipe – combines the same strength, toughness and flexibility as standard Bionax PVCO pipe with the enhanced seismic-resistance benefits of an extended bell. The result is a municipal water transmission and distribution system which performs better than any pipe product available today. Bionax SR can improve absorption of lateral ground strain of seismic events and provides other performance benefits including product consistency, industry standard dimensions and corrosion-resistant attributes for North American jobsites.



BIONAX[®] SR[™]
SEISMIC WATER PIPE

VORTEX FLOW INSERT FOR ODOUR & CORROSION CONTROL

Vortex Flow™

Hydrogen sulfide (H₂S) gas and other odorous gases are a fact of life with sanitary sewer drop structures. When these gases become airborne, they not only generate complaints from the neighbourhood, but also impact air quality and cause corrosion within the sewer system.

The IPEX Vortex Flow Insert (VFI) offers a revolutionary new technology to eliminate odorous emissions and minimize corrosion in vertical sewer drops. With no moving parts and requiring virtually no maintenance, VFIs have delivered significant cost savings in installations across North America.

The patented spiral flow design eliminates odorous and corrosive gases in a unique way by using the wastewater's own flow energy to suppress the turbulence which releases noxious gases. The spiral flow creates a downdraft to trap airborne gases and force air into the sewage flow, oxidizing the odorous gases. By installing a Vortex drop structure, municipalities can save thousands of dollars in monthly chemical feed, air-phase treatment and maintenance costs.

APPLICATIONS

- Manholes, Chambers and Forcemains
- Pumping Station Wet Wells
- Steep Grade Sewers
- Turbine discharges



DID YOU KNOW?

Dr. Eugene Natarius, creator of the Vortex Drop Structure, received a Technical Innovation Award from the American Public Works Association for this revolutionary design.

ADVANTAGES

① Reduced Corrosion Extends Sewer Life

Hydrogen sulfide (H₂S) emissions from forcemain discharges can literally eat through a concrete drop manhole. By oxidizing dissolved H₂S, a Vortex Flow Insert can significantly reduce concrete and metal corrosion, extending sewer life and saving the municipality money.

② Eliminates Odour Treatment Costs

By increasing dissolved oxygen levels in wastewater and oxidizing sulfides and other odorous compounds, the use of a Vortex Flow Insert in a drop structure eliminates the need for costly chemical injection, high-maintenance biofilters and air scrubbers.

③ Improves Waste Water Quality

Because a Vortex drop structure reduces the odorous and corrosive elements in the flow, a Vortex Flow Insert, installed upstream of a treatment plant, can actually improve wastewater quality prior to treatment, reducing treatment costs at sewage plants.

④ Reduced Maintenance Costs

The use of a Vortex drop structure eliminates the corrosion of concrete and metal sewer components, dramatically reducing municipal maintenance costs of manholes and sewers.

⑤ Built-to-Spec for Any Size

Manholes, chambers and pumping stations are built in a variety of sizes. For that reason, IPEX custom designs and builds every Vortex Flow Insert based on the peak flow that the unit is required to handle.




SHORT FORM SPECIFICATIONS

All sanitary sewer drops of five feet or more in manholes or pumping stations shall be equipped with Vortex Flow Drop structures as manufactured by IPEX Inc.


Vortex units must be fabricated using AWWA C900 pipe, as well as PVC sheet conforming to ASTM D1248.

Vortex drop structures must be supplied with shop drawings approved by the Project Engineer, as well as installation instructions. The hydraulic capacity of the unit (both minimum and maximum flows) must be clearly indicated in the submission.



HOW IT WORKS

1. Vortex Top Form



Wastewater flows into the Vortex Top Form directing the flow around a channel of decreasing radius. At the same time, the Vortex channel slopes downward to accelerate the wastewater to a supercritical velocity.

2. Vortex Drop Shaft



Once in the smaller Drop Shaft, the velocity and centrifugal forces generated cause the flow to hug the inside walls of the Drop Shaft. This spiraling flow creates a negative air core, drawing airborne gases down to the Energy Dissipation Pool.

3. Energy Dissipation Pool



The flow exit is submerged in the Energy Dissipation Pool at the bottom of the Vortex. Air and gases drawn down the air core are forced back through the wastewater and re-entrained into the flow. This significantly increases the dissolved oxygen concentration, and the odorous compounds are quickly oxidized.

To receive a conceptual design for a Vortex Flow Insert, go to ipexna.com & complete the design information form

STORM SEWER INLET CONTROLS



PROBLEM: SURCHARGED SEWER SYSTEMS

During heavy rain events, storm sewers can become overloaded causing sewer backups into residential basements and onto urban environments and streets. These events cause significant environmental and property damage and are all too common in older sections of municipalities where combined, undersized sewer systems often end up discharging a mixture of storm water runoff and sanitary wastewater into homes, streets and lakes when sewer capacities exceed historical norms. Traditional approaches to overcoming these challenges have been expensive, disruptive and time consuming for municipalities and the private sector.

SOLUTION: TEMPEST INLET CONTROL SYSTEMS

- Provides control by restricting flow into the sewer system
- Provides temporary ponding in catch basins, parking lots & roadways
- Helps preserve sewer capacity, slows down the inlet flow
- Reduces residential flooding and flash flooding
- Water surcharge is controlled & directed as per engineer design
- Can accommodate outlet pipes 6" and larger

APPLICATIONS

- Parking Lots
- Roads
- Areas where main line storm sewer capacity must be managed



DID YOU KNOW?

Tempest ICDs have a quick release mechanism that's accessed with a reach bar. The units can then be simply lifted out for easy maintenance. (Excluding Tempest HF Sump)

ADVANTAGES

1 Reduces Sewer Overflows and Basement Backups

Tempest is a family of cost-effective inlet control devices that work together across a series of catch basins to limit the amount of storm water runoff that can enter a combined sewer system during a storm event. Basement backups and sewer overflows are avoided because storm water surcharges are controlled at the sewer inlet and are allowed to remain in catch basins or temporarily above ground.

2 Integrated Odour and Floatable Control

In addition to flow control, Tempest systems can also alleviate sewer system odour emissions as well as prevent floating debris from entering the sewer system.

3 Wide Range of Models & Pre-set Flow Rates

Available in a wide range of patent pending models and pre-set flow rates, Tempest systems can accommodate most storm water flow control requirements from 2 lps to 17 lps and beyond. Application specific solutions can also be engineered to meet your unique needs in both wet and dry catch basin environments.

4 Easy to Install and Maintain

Constructed from durable PVC, Tempest units are corrosion free and built to last. The Tempest's light weight design accommodates both square and round catch basins and features a universal back plate and interchangeable components with no moving parts that makes the units quick and easy to install over a catch basin outlet pipe. These devices also include a quick release mechanism to allow easy access for service without the need to drain the installation.



THE TEMPEST FAMILY OF SYSTEMS

TEMPEST LMF

Restricts:

- ✓ Flow
- ✓ Odours
- ✓ Floatables



LOW to MODERATE FLOW RATES
2 L/s (32 GPM) – 17 L/s (270 GPM)

14 pre-set flow rates

The Tempest LMF system features a vortex inlet design that allows a low flow rate to be set and eliminates the passage of odours and floatables and allows for debris and sediment to collect in the structure.

TEMPEST HF & HF SUMP

Restricts:

- ✓ Flow
- ✓ Odours
- ✓ Floatables



HIGH FLOW RATES
15 L/s (240 GPM) or greater

5 pre-set flow rates

The standard Tempest HF system allows a near constant discharge rate to be set and eliminates the passage of odours and floatables and allows for debris and sediment to collect in the structure.

The Tempest HF SUMP system is designed for catch basins & manholes in which there is no sump or the outlet pipe is too low to install a standard Tempest device.

TEMPEST MHF

Restricts:

- ✓ Flow



MEDIUM TO HIGH FLOW RATES
9 L/s (143 GPM) or greater

Specified pre-set flow rates

The Tempest MHF is a standard orifice plate device designed to allow a specified flow volume through the outlet pipe at a specified head.

UNIVERSAL BACK PLATES

AVAILABLE FOR BOTH SQUARE AND
ROUND CATCH BASINS
(excluding Tempest HF Sump)




For square
catch basins



For round
catch basins



PRODUCTION SELECTION CHART

Description		
LMF ICD		
	Square Catch Basin Adapter	Low to medium flow Restricts flow to 2 Lps - 17 Lps 14 preset flow rates
	Round Catch Basin Adapter	Floatable and odour control Supplied with neoprene gasket

HF ICD and Odour Traps ICD

	HF Square Catch Basin Adapter	Hi flow
	HF Round Catch Basin Adapter	Restricts flow to 15 Lps & > 5 preset flow rates Floatable and odour control
	Odour Trap Square Catch Basin Adapter	Supplied with neoprene gasket
	Odour Trap Round Catch Basin Adapter	Option for odour trap only, no flow restriction


MHF Plate ICD

	Square Catch Basin Adapter	Medium to high flow Restricts flow to 9 Lps and > 5 preset flow rates
	Round Catch Basin Adapter	Supplied with neoprene gasket

MHF Plug ICD

	8"	Medium to high flow
	10"	Restricts flow to 9 Lps and >
	12"	5 preset flow rates

HF Sump ICD

	Square Catch Basin Adapter	High flow Creates a sump Restricts flow to 15 Lps and >
	Round Catch Basin Adapter	5 preset flow rates Floatable and odour control

Description		
TEMPEST Devices		
	Universal Mounting Plate Hub Adapter	If a universal mounting plate already exists in the structure:
	LMF Device	Choose an ICD device only for a square structure
	HF Device	Choose the universal mounting plate hub adapter and ICD device for a round structure
	8" Odour Trap	
	MHF Plate Device	

Please contact your local IPEX representative for sizing of a TEMPEST ICD and a quotation

NOTES: In order to assist in choosing the proper TEMPEST ICD and for proper sizing and a quotation, the following information will be required when contacting IPEX for a TEMPEST ICD:

1. Feature(s) requirement: flow, floatable control, odour control
2. Flow requirement
3. Water height (Head / m)
4. Depth of sump / height of outlet pipe
5. Host pipe material
6. Inside diameter of host pipe
7. Catch basin configuration
8. Catch basin structure dimensions



"Our Commitment Starts here"

Thermoplastics play a vital role in making our water supply and sewer systems safe for the environment – and for our health

Reducing water main corrosion and breakage is key to addressing the current water quality crisis in North America.

Unlike alternative materials, PVC does not serve as a nutrient for bacteria growth and its smooth interior surface is less prone to build-up of encrustants. And, because thermoplastics do not react chemically with drinking water, vinyl doesn't corrode.

Plastics consume just 2% of our oil and natural gas resources and thermoplastic resins require less energy to produce than most alternative materials.

At IPEX, we use a substantial amount of recycled plastic in many of our products. Our commitment to a safe and healthy environment starts here.

SALES AND CUSTOMER SERVICE

IPEX USA LLC.

Toll Free: (800) 463-9572

ipexna.com

About IPEX by Aliaxis

As leading suppliers of thermoplastic piping systems, IPEX by Aliaxis provides our customers with some of the world's largest and most comprehensive product lines. All IPEX by Aliaxis products are backed by more than 50 years of experience. With state-of-the-art manufacturing facilities and distribution centers across North America, we have earned a reputation for product innovation, quality, end-user focus and performance.

Markets served by IPEX by Aliaxis products are:

- Electrical systems
- Telecommunications and utility piping systems
- Industrial process piping systems
- Municipal pressure and gravity piping systems
- Plumbing and mechanical piping systems
- Electrofusion systems for gas and water
- Industrial, plumbing and electrical cements
- Irrigation systems
- PVC, CPVC, ABS, PE, PVCO, PP and PVDF pipe and fittings (1/2" to 60")

Products are manufactured by IPEX USA LLC.

BIONAX®, BIONAX®SR™, IPEX Centurion®, IPEX Fusible™, Fusible Brute™, Fusible Series™, TerraBrute CR®, Cycle Tough®, Blue 904®, Q-Line®, Philmac® 3G™, Gold Stripe®, and Ring-Tite®, Enviro-Tite®, Ultra-Rib®, Ultra-X2®, Vortex Flow™, and Tempest™ are trademarks of IPEX Branding Inc.

This literature is published in good faith and is believed to be reliable. However, it does not represent and/or warrant in any manner the information and suggestions contained in this brochure. Data presented is the result of laboratory tests and field experience.

A policy of ongoing product improvement is maintained. This may result in modifications of features and/or specifications without notice.



IPEX
by aliaxis

CTMNNAI210101R13U
© 2026 IPEX