



ECFUF-124 - 1/2" Flexible Coupling with 24" Bend Length, Bronze

By Killark
Catalog # [ECFUF-124](#)

1/2" Flexible Coupling with 24" Bend Length, Bronze



Features

- Bronze flexible metal construction
- An inner liner of asphaltum impregnated jute fibre tubing to protect conductors
- Provided with one zinc plated steel nipple and one zinc plated steel female union
- Special lengths available – consult factory

Application

For use in hazardous areas where movement or vibration requires a flexible connection or a difficult bend is required in a conduit system.

Specifications

UL File Number	E10514
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11716
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G

EU RoHS Indicator

- Class III, Divisions 1 & 2
Contact Manufacturer

Dimensions

Height	1.5 in
Width	1.5 in
Hub Size	1/2"
Length	30.125 in
Gross Weight with Packaging	3.5
Dimensions	30.125 in x 1.5 in x 1.5 in

General

Color	Bronze
UPC	783936105680
Type	Flexible Coupling With Female Union
Material	Bronze
Finish Type	Natural
Series	ECFUF Series

Product Assets

- [Catalog \[English\]](#)
[Installation Manual \[English\]](#)