KILLARK®

EKJ-219SS-EX - 3/4″ x 19″ Flexible Coupling, Stainless Steel, Quad Listed

By Killark
Catalog # EKJ-219SS-EX

3/4″ x 19″ Flexible Coupling, Stainless Steel, Quad Listed

Features

- Stainless Steel flexible metal construction
- NPT male fitting (316SS) welded to each end
- Outer Braid (304SS) with inner flex hose of 321SS
- Inner liner of silicone coated fabric
- Certified QUAD listed

Application

For use in hazardous areas where movement or vibration requires a flexible connection or a difficult bend is required in a conduit system.

Specifications

Buy America(n) Qualified	Contact Manufacturer
ATEX File Number	10ATEX11068U
IECEx File Number	10.0057U
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Dimensions

Height	1.69 in
Width	1.69 in
Hub Size	3/4″
Length	23.5 in
Gross Weight with Packaging	4.79
Dimensions	23.5 in x 1.69 in x 1.69 in

General

Color	Silver
UPC	783936073453
Type	Flexible Coupling
Material	Stainless Steel
Finish Type	Natural
Series	EKJ Series

Product Assets

Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved