KILLARK®

EKJ-315SS-EX - 1″ x 15″ Flexible Coupling, Stainless Steel, Quad Listed

By Killark
Catalog # EKJ-315SS-EX

1″ x 15″ Flexible Coupling, Stainless Steel, Quad Listed

Features

- Stainless Steel flexible metal construction
- NPT male fitting (316SS) welded to each end
- Outer Braid (304SS) with inner flex hose of 321SS
- Inner liner of silicone coated fabric
- Certified QUAD listed

Application

For use in hazardous areas where movement or vibration requires a flexible connection or a difficult bend is required in a conduit system.

Specifications

Buy America(n) Qualified	Contact Manufacturer
ATEX File Number	10ATEX11068U
IECEx File Number	10.0057U
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Dimensions

Hub Size	1″
Gross Weight with Packaging	6.82

General

Color	Silver
UPC	783936073521
Type	Flexible Coupling
Material	Stainless Steel
Finish Type	Natural
Series	EKJ Series

Product Assets

Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved