KILLARK®

EY-50 - 1/2″ EY Vertical Seal Fitting Aluminum, Female/Female

By Killark
Catalog # EY-50

1/2″ EY Vertical Seal Fitting Aluminum, Female/Female

Features

- Large opening for easy packing of fiber dam and pouring of compound.
- Integral bushings in conduit hubs to protect conductor insulation from damage.
- NPT tapped hubs to ensure ground continuity.
- Design provides minimum turning radius.
- 25% conductor fill.

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

EU RoHS Indicator	Contact Manufacturer
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Dimensions

Hub Size	1/2″
Length	5 in
Height	0.1 in
Width	10 in
Gross Weight with Packaging	0.34
Dimensions	5 in x 10 in x 0.1 in

General

Color	Gray
Series	EY Series
UPC	783936089959
Type	Sealing Fitting
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	10

Product Assets

Catalog [English]
Installation Manual [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved