KILLARK®

# EY-50TM - 1/2″ EY Vertical Seal Fitting Iron, w/nipple Male/Female

By Killark
Catalog # EY-50TM

1/2″ EY Vertical Seal Fitting Iron, w/nipple Male/Female

## Features

- Large opening for easy packing of fiber dam and pouring of compound.
- Integral bushings in conduit hubs to protect conductor insulation from damage.
- NPT tapped hubs to ensure ground continuity.
- Design provides minimum turning radius.
- 25% conductor fill.
- Supplied with removeable close nipples.

## Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

## Specifications

| | |
|---|---|
| EU RoHS Indicator | Contact Manufacturer |
| Buy America(n) Qualified | Contact Manufacturer |
| Hazardous Rating(s) | • Class I, Divisions 1 & 2, Groups B, C, D<br>• Class I, Zones 1 & 2, Groups IIB, IIA<br>• Class II, Divisions 1 & 2, Groups E, F, G<br>• Class III, Divisions 1 & 2 |

## Dimensions

| | |
|---|---|
| Hub Size | 1/2″ |
| Length | 5 in |
| Height | 0.1 in |
| Width | 10 in |
| Gross Weight with Packaging | 1.06 |
| Dimensions | 5 in x 10 in x 0.1 in |

## General

| | |
|---|---|
| Color | Gray |
| Series | EY Series |
| UPC | 783936090924 |
| Type | Sealing Fitting With Nipple |
| Material | Iron |
| Finish Type | Powder Epoxy Paint |

## Logistics

| | |
|---|---|
| Carton Quantity | 5 |

## Product Assets

Catalog [English]
Installation Manual [English]
Installation Manual [English]



© 2026 Hubbell Incorporated. All rights reserved