



EY-6 - 2" EY Seal Fitting Aluminum, Female/Female

By Killark
Catalog # [EY-6](#)

2" EY Seal Fitting Aluminum, Female/Female



Features

- Large opening for easy packing of fiber and pouring of compound
- Integral bushings in conduit hubs to protect conductor insulation from damage
- NPT tapped hubs to ensure ground continuity
- 25% conductor fill
- EY-T style supplied with removable close nipples

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G

- Class III, Divisions 1 & 2

Dimensions

Hub Size	2"
Length	10.31 in
Height	4.13 in
Width	8.38 in
Gross Weight with Packaging	1.72
Dimensions	10.31 in x 8.38 in x 4.13 in

General

Color	Gray
Series	EY Series
UPC	783936110066
Type	Sealing Fitting
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	5
-----------------	---

Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[English\]](#)