



EY-8 - 3" EY Seal Fitting Aluminum, Female/Female

By Killark

Catalog # [EY-8](#)

3" EY Seal Fitting Aluminum, Female/Female



Features

- Large opening for easy packing of fiber and pouring of compound
- Integral bushings in conduit hubs to protect conductor insulation from damage
- NPT tapped hubs to ensure ground continuity
- 25% conductor fill
- EY-T style supplied with removable close nipples

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

UL File Number

E10514

CSA File Number

LR11716

Hazardous Rating(s)

- Class I, Divisions 1 & 2, Groups C, D
- Class I, Zones 1 & 2, Groups IIB, IIA
- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2

EU RoHS Indicator

Contact Manufacturer

Dimensions

Height

10.5 in

Width

6.25 in

Hub Size

3"

Length

5.875 in

Gross Weight with Packaging

3.83

Dimensions

5.875 in x 6.25 in x 10.5 in

General

Color

Gray

UPC

783936110080

Type

Sealing Fitting

Material

Aluminum, Copper Free (less than 4/10 of 1%)

Finish Type

Powder Epoxy Paint

Series

EY Series

Product Assets

[Catalog \[English\]](#)

[Installation Manual \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand
© 2026 Hubbell Incorporated. All rights reserved
KILL_CA-EY8-SPEC-EN | REV 5/2026