



EY-8TM - 3" EY Seal Fitting Iron, w/nipple Male/Female

By Killark
Catalog # [EY-8TM](#)

3" EY Seal Fitting Iron, w/nipple Male/Female

Features

- Large opening for easy packing of fiber and pouring of compound
- Integral bushings in conduit hubs to protect conductor insulation from damage
- NPT tapped hubs to ensure ground continuity
- 25% conductor fill
- EY-T style supplied with removable close nipples

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

UL File Number	E10514
CSA File Number	LR11716
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D



- Class I, Zones 1 & 2, Groups IIB, IIA
 - Class II, Divisions 1 & 2, Groups E, F, G
 - Class III, Divisions 1 & 2
- EU RoHS Indicator
- Contact Manufacturer

Dimensions

Hub Size	3"
Gross Weight with Packaging	12.8

General

Color	Gray
UPC	783936111605
Type	Sealing Fitting With Nipple
Material	Iron
Finish Type	Powder Epoxy Paint
Series	EY Series

Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[English\]](#)