KILLARK®

EYD-0TM - 4″ EYD Seal Fitting Iron, w/nipple Male/Female

By Killark
Catalog # EYD-0TM

EYD Seal Fitting Iron, Male/Female

Features

- Threaded for Rigid Conduit or IMC
- Tapered threads (NPT)
- Simplified installation
- Internal drainage path provides a visual means to ensure that the compound chamber is properly filled
- Temporary plastic sleeve protects thread for drain/breather from contamination when pouring compound
- Unique design enables installation of drain/breather right after compound is poured – no waiting
- Provides continuous water drain path while allowing conduit run to breathe, in compliance with the NEC
- Includes Drain Breather Fitting KDB-1

Application

To minimize the passage of gases and vapors from one electrical installation to another through the conduit system while offering a degree of ventilation and draining of condensation. To confine any explosions from sealed enclosures and prevent pressure pilling between conduit systems.

Specifications

Ratings	3R
CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Dimensions

Hub Size	4″
Weight	17.27 lb.
Height	9.78 in
Width	5.125 in
Turning Radius	4.125
Gross Weight with Packaging	20

General

Color	Gray
Series	EYD Series
UPC	783936111827
Type	Sealing Fitting
Material	Zinc Plated Iron
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	1

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved