KILLARK®

EYD-5TM - 1-1/2″ EYD Seal Fitting Iron, w/nipple Male/Female

By Killark
Catalog # EYD-5TM

1-1/2″ EYD Seal Fitting Iron, w/nipple Male/Female

Features

- Large opening for easy packing of fiber and pouring of compound
- Integral bushings in conduit hubs to protect conductor insulation from damage
- NPT tapped hubs to ensure ground continuity
- 25% conductor fill
- EYD-T style supplied with removable close nipples
- Simple to install internal drain to allow condensation to weep and conduit system to breathe

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

UL File Number	E10514
CSA File Number	LR11716
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Dimensions

Height	5.125 in
Width	2.203 in
Hub Size	1-1/2″
Length	4.625 in
Gross Weight with Packaging	3.8
Dimensions	4.625 in x 2.203 in x 5.125 in

General

Color	Gray
UPC	783936111773
Type	Sealing Fitting With Nipple
Material	Iron
Finish Type	Powder Epoxy Paint
Series	EYD Series

Product Assets

Catalog [English]
Installation Manual [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved