



EYD-6-T - 2" EYD Seal Fitting Aluminum, w/nipple Male/Female

By Killark
Catalog # [EYD-6-T](#)

2" EYD Seal Fitting Aluminum, w/nipple Male/Female



Features

- Large opening for easy packing of fiber and pouring of compound
- Integral bushings in conduit hubs to protect conductor insulation from damage
- NPT tapped hubs to ensure ground continuity
- 25% conductor fill
- EYD-T style supplied with removable close nipples
- Simple to install internal drain to allow condensation to weep and conduit system to breathe

Application

Class I, Divisions 1 and 2: The purpose of seals in a Class I hazardous location is to minimize the passage of gases and vapors and prevent the passage of flames from one electrical installation to another through the conduit system. Seals are required to

Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA

- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2

Dimensions

Hub Size	2"
Gross Weight with Packaging	2.14

General

Color	Gray
Series	EYD Series
UPC	783936110844
Type	Sealing Fitting With Nipple
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	5
-----------------	---

Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[English\]](#)