KILLARK®

FXCS-1B4-M - FXCS Series, Seal-XM, AL Dead-End Momentary Contact Double Push Button Ctrl Stn, Red/Green Buttons, Hub Size 1/2", 2NO/2NC Contact Rating

By Killark
Catalog # FXCS-1B4-M

FXCS Series - Seal-XM - Aluminum Dead-End Momentary Contact Double Push Button Control Station - Factory Sealed - Red And Green Buttons - Hub Size 1/2 Inch - 2NO/2NC Contact Rating

Features

- Incorporates Factory Sealed Universal contact blocks and GOB3 LED pilot light devices.
- External sealing fittings typically not required, reducing installation time and cost.
- No seal plate between the electrical device and back box allows direct wiring to contact terminals.
- NEMA 3 weatherproof.
- Grounding boss supplied in the splice box.
- Sold as a complete unit.
- Standard finish is a gray epoxy powder baked on for ultimate corrosion resistance.
- More wiring room in back box.

Application

SEAL-XM Series is used to prevent the igniting of external hazardous atmospheres by the enclosed arcing devices in such areas as: hazardous locations due to the presence of flammable gases or vapors, combustible dusts or easily ignitable fibers or flyings

Specifications

Nema Rating	3
CSA File Number	LR11714, 2493125
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Configuration

Back Box Type	FXB
Hub Pattern	Dead-End

Current

Frequency Rating	50/60 Hz
Amperage Rating	10 A

Dimensions

Hub Size	1/2"
Depth	4.28 in

General

Color	Green-Red
UPC	783936105321
Type	Factory Sealed
Series	FXCS Seal-XM Series

Logistics

Factory Sealed	Factory Sealed

Operational

Actuator	Double Pushbutton
Action	Momentary

Product Assets

Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved