



FXCS-2B4-M - FXCS Series, Seal-XM, AL
Dead-End Momentary Contact Double
Push Button Ctrl Stn, Red/Green Buttons
w/ Start Nameplates, Hub 3/4", 2NO/2NC

By Killark
Catalog # FXCS-2B4-M

FXCS Series - Seal-XM - Aluminum Dead-End Momentary
Contact Double Push Button Control Station - Factory Sealed -
Red And Green Buttons With "Start"Nameplates - Hub Size 3/4"
- 2NO/2NC Contact Rating

Features

- Incorporates Factory Sealed Universal contact blocks and GOB3 LED pilot light devices.
- External sealing fittings typically not required, reducing installation time and cost.
- No seal plate between the electrical device and back box allows direct wiring to contact terminals.
- NEMA 3 weatherproof.
- Grounding boss supplied in the splice box.
- Sold as a complete unit.
- Standard finish is a gray epoxy powder baked on for ultimate corrosion resistance.
- More wiring room in back box.

Application

SEAL-XM Series is used to prevent the igniting of external hazardous atmospheres by the enclosed arcing devices in such areas as: hazardous locations due to the presence of flammable gases or vapors, combustible dusts or easily ignitable fibers or flyings

Specifications

Nema Rating	3
CSA File Number	LR11714, 2493125
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2



EU RoHS IndicatorContact Manufacturer

Configuration

Back Box Type	FXB
Hub Pattern	Dead-End

Current

Frequency Rating	50/60 Hz
Amperage Rating	10 A

Dimensions

Hub Size	3/4"
Depth	4.28 in

General

Color	Green-Red
UPC	783936002057
Type	Factory Sealed
Series	FXCS Seal-XM Series

Logistics

Factory Sealed	Factory Sealed
----------------	----------------

Operational

Actuator	Double Pushbutton
Action	Momentary

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)