KILLARK®

FXCS-2S2A1 - FXCS Series, AL Dead-End Maintained Contact 2-Position Selector Switch Ctr Stn, Off-On/Blank Nameplate, Hub Size 3/4", 1NO/1NC Contact

By Killark
Catalog # FXCS-2S2A1

FXCS Series - Aluminum Dead-End Maintained Contact 2-Position Selector Switch Control Station - Factory Sealed - "Off - On"/Blank Nameplate -Hub Size 3/4 Inch - 1NO/1NC Contact Rating

Features

- Eliminates external sealing requirements.
- Lower installation cost.
- NEMA 3 weatherproof.
- Color coded wiring with more wiring space for easier field installation.
- Stainless steel captive screws for cover assembly.
- Lockout accessory available must be factory installed.
- Ground boss for grounding in the splice box.
- Device bodies and covers are copper-free cast aluminum alloy.
- Push button, selector switches and pilot light bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

SEAL-X Series is used to prevent the igniting of external hazardous atmospheres by the enclosed arcing devices in such areas as: hazardous locations due to the presence of flammable gases or vapors, combustible dusts or easily ignitable fibers or flyings

Specifications

CSA File Number	LR11714, LR11712
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3
UL File Number	E53360, E12379
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Conductor

Number Of Poles	1

Configuration

Back Box Type	FXB
Hub Pattern	Dead-End

Current

Frequency Rating	50/60 Hz
Amperage Rating	10 A
Contact Rating	• 60A INRUSH @ 120 VAC • 30A INRUSH @ 240 VAC • 15A INRUSH @ 480 VAC • 12A INRUSH @ 600 VAC • 6A BREAKING @ 120 VAC • 3A BREAKING @ 240 VAC • 1.5A BREAKING @ 480 VAC • 1.2A BREAKING @ 600 VAC • 10A CARRYING @ 120 VAC • 10A CARRYING @ 240 VAC • 10A CARRYING @ 480 VAC

Dimensions

Hub Size	3/4"
Length	6.63 in
Depth	5.62 in
Height	4.38 in
Width	6 in
Gross Weight with Packaging	4.4
Dimensions	6.63 in x 6 in x 4.38 in

General

Color	Black
Series	FXCS Series
UPC	783936201399
Type	Factory Sealed

Logistics

Factory Sealed	Factory Sealed

Operational

Actuator	2 Position Selector Switch
Action	Maintained

Product Assets

Catalog [English]
Installation Manual [English]
Installation Manual [French]

A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved