



FXS Series - Dead-End SPDT (Center Off) Tumbler Switch Unit -Factory Sealed - Hub Size 1/2 Inch - 20A

By Killark
Catalog # [FXS-15C](#)

FXS Series - Aluminum Dead-End SPDT (Center Off) Tumbler
Switch Unit -Factory Sealed - Hub Size 1/2 Inch - 20A

Features

- Eliminates external sealing requirements.
- Lower installation cost.
- NEMA 3 weatherproof.
- Color coded wiring with more wiring space for easier field installation.
- Stainless steel captive screws for cover assembly.
- Lockout accessory available must be factory installed.
- Ground boss for grounding in the splice box.
- Device bodies and covers are copper-free cast aluminum alloy.
- Push button, selector switches and pilot light bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

FXS tumbler switches are suitable for applications where making, breaking, or changing connections in an electrical circuit is required and where conditions of load do not exceed the switch ratings.

Specifications

Nema Rating	3
UL File Number	E53360, E10501
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11712
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2



EU RoHS IndicatorContact Manufacturer

Conductor

Number Of Poles1

Configuration

Back Box TypeFXB

Current

Frequency Rating50/60 Hz
Amperage Rating20 A

Dimensions

Height4.38 in
Width6 in
Length6.63 in
Gross Weight with Packaging4.4
Depth3.15 in
Dimensions6.63 in x 6 in x 4.38 in

General

ColorGray
UPC783936195018
TypeFactory Sealed
SeriesFXS Series

Operational

ActuatorLever
ActionSPDT (CNTR OFF)

Product Assets

[Catalog \[English\]](#)