KILLARK®

FXS Series - Dead-End 2-Pole Tumbler Switch Unit - Factory Sealed - Hub Size 3/4 Inch - 30A

By Killark
Catalog # FXS-22D

FXS Series - Aluminum Dead-End 2-Pole Tumbler Switch Unit - Factory Sealed - Hub Size 3/4 Inch - 30A

Features

- Eliminates external sealing requirements.
- Lower installation cost.
- NEMA 3 weatherproof.
- Color coded wiring with more wiring space for easier field installation.
- Stainless steel captive screws for cover assembly.
- Lockout accessory available must be factory installed.
- Ground boss for grounding in the splice box.
- Device bodies and covers are copper-free cast aluminum alloy.
- Push button, selector switches and pilot light bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

FXS tumbler switches are suitable for applications where making, breaking, or changing connections in an electrical circuit is required and where conditions of load do not exceed the switch ratings.

Specifications

Nema Rating	3
UL File Number	E53360, E10501
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11712
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	2

Configuration

Back Box Type	FXB

Current

Frequency Rating	50/60 Hz
Amperage Rating	30 A

Dimensions

Height	4.75 in
Width	6.125 in
Length	6.5 in
Gross Weight with Packaging	4.4
Depth	3.15 in
Dimensions	6.5 in x 6.125 in x 4.75 in

General

Color	Gray
UPC	783936195117
Type	Factory Sealed
Series	FXS Series

Operational

Actuator	Lever
Action	DP

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved