



FXS Series 3-Pole Tumbler Switch Cover With Device - Factory Sealed - 15A

By Killark
Catalog # [FXS-8C](#)

FXS Series - Aluminum 3-Pole Tumbler Switch Cover With Device
- Factory Sealed - 15A

Features

- Eliminates external sealing requirements.
- Lower installation cost.
- NEMA 3 weatherproof.
- Color coded wiring with more wiring space for easier field installation.
- Stainless steel captive screws for cover assembly.
- Lockout accessory available must be factory installed.
- Ground boss for grounding in the splice box.
- Device bodies and covers are copper-free cast aluminum alloy.
- Push button, selector switches and pilot light bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

FXS tumbler switches are suitable for applications where making, breaking, or changing connections in an electrical circuit is required and where conditions of load do not exceed the switch ratings.

Specifications

CSA File Number	LR11712
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3
UL File Number	E53360, E10501
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2



Conductor

Number Of Poles	3
-----------------	---

Configuration

Back Box Type	FXB
---------------	-----

Current

Frequency Rating	50/60 Hz
Amperage Rating	15 A

Dimensions

Length	6.5 in
Depth	3.15 in
Height	4.75 in
Width	6.125 in
Gross Weight with Packaging	3.2
Dimensions	6.5 in x 6.125 in x 4.75 in

General

Color	Gray
Series	FXS Series
UPC	783936194899
Type	Factory Sealed

Logistics

Carton Quantity	5
-----------------	---

Operational

Actuator	Lever
Action	3P

Product Assets

[Catalog \[English\]](#)