



FXS Series Ground Fault Interrupter Cover Assembly - Factory Sealed - 20A/120Vac/60Hz - 4-6 Miliamp Trip Setting

By Killark
Catalog # FXS-GFIO3

FXS Series - Aluminum Ground Fault Interrupter Cover Assembly
- Factory Sealed - 20A/120Vac/60Hz - 4-6 Miliamp Trip Setting

Features

- Eliminates external sealing requirements.
- Lower installation cost.
- NEMA 3 weatherproof.
- Color coded wiring with more wiring space for easier field installation.
- Stainless steel captive screws for cover assembly.
- Lockout accessory available must be factory installed.
- Ground boss for grounding in the splice box.
- Device bodies and covers are copper-free cast aluminum alloy.
- Push button, selector switches and pilot light bodies are copper-free aluminum.
- Operating shaft in both push buttons and selector switches are stainless steel.

Application

FXS ground fault interrupters are designed to interrupt a circuit when a ground fault is detected on equipment which may be handled by personnel in hazardous locations.

Specifications

CSA File Number	LR11712
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3
UL File Number	E53360, E10501
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2



Conductor

Number Of Poles	2
-----------------	---

Configuration

Back Box Type	FXB
---------------	-----

Current

Frequency Rating	50/60 Hz
Amperage Rating	20 A

Dimensions

Length	6.75 in
Depth	5-1/8 in
Height	5 in
Width	6.125 in
Gross Weight with Packaging	3.2
Dimensions	6.75 in x 6.125 in x 5 in

General

Color	Gray
Series	FXS-GFI Series
UPC	783936198255
Type	Aluminum Factory Sealed Ground Fault Interrupter Cover Assembly

Logistics

Carton Quantity	1
-----------------	---

Operational

Actuator	Ground Fault Interrupter
Action	Push buttons