



FXSD11 - FXSD Series, AL Dead-End Single Gang 1-Pole, Single Phase Manual Motor Starting Switch Unit, w/ Overload Protection, Hub Size 1/2"

By Killark
Catalog # [FXSD11](#)

FXSD Series - Aluminum Dead-End Single Gang 1-Pole, Single Phase Manual Motor Starting Switch Unit - With Overload Protection - Hub Size 1/2Inch

Features

- Motor running protection when overload heaters are used.
- Factory Sealed so no external seals are required.
- Type 3 (raintight) rated.
- Enclosures are cast copper-free aluminum alloy.
- Operating shaft is stainless steel.
- Multiple gang assemblies available in combination with pilot lights, pushbuttons and switches on request.
- Ground flange joint between bolted cover and box provide required flame path.
- Provisions for padlocking switch in either "ON" or "OFF" position is standard.

Application

Provides manual starting and stopping of small AC or DC motors. Motor running protection when overload heaters are used.

Specifications

Nema Rating	3
UL File Number	E53360 / E12379
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA



- Class II, Divisions 1 & 2, Groups E, F, G
- Class III, Divisions 1 & 2

Current

Frequency Rating	60 Hz
Voltage Rating	230 V

Dimensions

Gross Weight with Packaging	4.4
-----------------------------	-----

General

Product Family	Motor Starters
UPC	783936197296
Type	Aluminum Manual Motor Starting Switch With Overload Protection
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	FXSD Series

Operational

Horsepower - Maximum	1
----------------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)