KILLARK®

GEML-2 - ¾″ GEM Outlet Body L-Type

By Killark
Catalog # GEML-2

¾″ GEM Outlet Body L-Type

Features

- Water shedding cover – suitable for wet locations when mounted in upright position.
- External cover threads on body protecting conductors from damage during pulling.
- No pinching of conductors during cover installation.
- Taper threaded hubs to provide ground continuity.
- Smooth integral hub bushing to protect conductor insulation when pulling.
- Internally threaded cover openings for additional wiring room.
- Covers furnished with boxes.
- Weather-resistant finish.
- Green ground screw standard.

Application

Conduit boxes installed in conduit systems within hazardous areas to: protect conductors in threaded rigid conduit, act as pull and splice boxes, interconnect lengths of conduit, change conduit direction, and provide access to conductors for maintenance and future system changes.

Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA

Configuration

Hub Pattern	L

Dimensions

Hub Size	3/4″
Length	11 in
Weight	0.73 lb.
Height	3.75 in
Width	7 in
Gross Weight with Packaging	0.73
Dimensions	11 in x 7 in x 3.75 in

General

Color	Gray
Series	GE Series
UPC	783936210216
Type	Outlet Body With Cover
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	5

Product Assets

Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved