



G Series - Capillary Seal - Diameter 0.093 In

By Killark
Catalog # [GO-11372-093](#)

G Series - Capillary Seal - Diameter 0.093 In



Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

EU RoHS Indicator	Contact Manufacturer
-------------------	----------------------

Current

Frequency Rating	50/60 Hz
------------------	----------

Dimensions

Gross Weight with Packaging	0.5
-----------------------------	-----

General

UPC	783936220000
Type	Specialty
Series	GO Series

Logistics

Carton Quantity	10
-----------------	----

Operational

Actuator	Capillary Seal
----------	----------------

Product Assets

[Catalog \[English\]](#)