



G Series - G Motor Shaft Operator - Shaft Diameter 1/2 In - Male-Male

By Killark
Catalog # [GO-51](#)

G Series - G Motor Shaft Operator - Shaft Diameter 1/2 In - Male-Male

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

UL File Number	E150827
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2



EU RoHS IndicatorContact Manufacturer

Current

Frequency Rating50/60 Hz

Dimensions

Height	1 in
Width	1 in
Length	7.813 in
Gross Weight with Packaging	0.55
Dimensions	7.813 in x 1 in x 1 in

General

UPC	783936219899
Type	Specialty
Series	GO Series

Operational

Actuator	Motor Shaft Operator
Action	Rotary

Product Assets

[Catalog \[English\]](#)