



G Series - Long SPST Snap Switch Operator - "Off - On"/Blank Nameplate - 10A At 125VAC/5A At 250VAC

By Killark
Catalog # [GO10-31F N34](#)

G Series - Aluminum Long SPST Snap Switch Operator - "Off - On"/Blank Nameplate - 10A At 125VAC/5A At 250VAC

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

UL File Number	E10501
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer



Conductor

Number Of Poles	1
-----------------	---

Current

Frequency Rating	50/60 Hz
Amperage Rating	10 A

Dimensions

Height	1.25 in
Width	2.25 in
Length	6.31 in
Gross Weight with Packaging	0.5
Dimensions	6.31 in x 2.25 in x 1.25 in

General

UPC	783936222271
Type	Specialty
Series	GO Series

Operational

Actuator	Snap Switch
Action	SPST

Product Assets

- [Catalog \[English\]](#)
[Installation Manual \[English\]](#)