



G Series - Long Fifteen-Turn Potentiometer/Rheostat Operator

By Killark
Catalog # [GO114 N34](#)

G Series - Aluminum Long Fifteen-Turn Potentiometer/Rheostat Operator

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

Nema Rating	3, 4, 4X
UL File Number	E150827
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class I, Zones 1 & 2, Groups IIB, IIA



EU RoHS Indicator

- Class II, Divisions 1 & 2, Groups E, F, G
 - Class III, Divisions 1 & 2
- Contact Manufacturer

Dimensions

Height	2 in
Width	2.25 in
Length	6.75 in
Gross Weight with Packaging	0.57
Dimensions	6.75 in x 2.25 in x 2 in

General

UPC	783936220154
Type	Specialty
Series	GO Series

Operational

Actuator	Potentiometer Operator
Action	Rotary

Product Assets

- [Catalog \[English\]](#)
[Installation Manual \[English\]](#)