



G Series - Short Reset Operator With 6 Inch Fiber Extension -"Reset"/Blank Nameplate

By Killark
Catalog # [GO40-KX2C](#)

G Series - Aluminum Short Reset Operator With 6 Inch Fiber Extension -"Reset"/Blank Nameplate

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

UL File Number	E150827
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11714
Hazardous Rating(s)	Class II, Divisions 1 & 2, Groups E, F, G
EU RoHS Indicator	Contact Manufacturer

Conductor



Number Of Poles	1
Current	
Frequency Rating	50/60 Hz
Dimensions	
Height	2 in
Width	2.25 in
Length	6.75 in
Gross Weight with Packaging	0.3
Dimensions	6.75 in x 2.25 in x 2 in
General	
UPC	783936223766
Type	Specialty
Series	GO Series
Operational	
Actuator	Pushbutton
Action	Momentary

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)