



# G Series Long Spring Returned 2-Position Selector Switch Operator - Spring Return To Left - "Off - On"/Blank Nameplate - 1NO/1NC Contact Rating

By Killark  
Catalog # [GO6-3F N34](#)

G Series - Aluminum Long Spring Returned 2-Position Selector Switch Operator - Spring Return To Left - "Off - On"/Blank Nameplate - 1NO/1NC Contact Rating

## Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

## Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

## Specifications

|                          |                                                                                                                                                                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nema Rating              | 3, 4, 4X                                                                                                                                                                                                                                            |
| UL File Number           | E12379                                                                                                                                                                                                                                              |
| Buy America(n) Qualified | Contact Manufacturer                                                                                                                                                                                                                                |
| CSA File Number          | LR11714                                                                                                                                                                                                                                             |
| Hazardous Rating(s)      | <ul style="list-style-type: none"><li>• Class I, Divisions 1 &amp; 2, Groups B, C, D</li><li>• Class I, Zones 1 &amp; 2, Groups IIB, IIA</li><li>• Class II, Divisions 1 &amp; 2, Groups E, F, G</li><li>• Class III, Divisions 1 &amp; 2</li></ul> |
| EU RoHS Indicator        | Contact Manufacturer                                                                                                                                                                                                                                |

## Conductor

|                 |   |
|-----------------|---|
| Number Of Poles | 1 |
|-----------------|---|

## Current

|                  |                                                                                                                                      |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Rating | 50/60 Hz                                                                                                                             |
| Amperage Rating  | 10 A                                                                                                                                 |
| Contact Rating   | <ul style="list-style-type: none"><li>• 60A INRUSH @ 120 VAC</li><li>• 30A INRUSH @ 240 VAC</li><li>• 15A INRUSH @ 480 VAC</li></ul> |



- 12A INRUSH @ 600 VAC
- 0.55A INRUSH @ 125 VDC
- 0.275A INRUSH @ 250 VDC
- 6A BREAKING @ 120 VAC
- 3A BREAKING @ 240 VAC
- 1.5A BREAKING @ 480 VAC
- 1.2A BREAKING @ 600 VAC
- 0.55A BREAKING @ 125 VDC
- 0.275A BREAKING @ 250 VDC
- 10A CARRYING @ 120 VAC
- 10A CARRYING @ 240 VAC
- 10A CARRYING @ 480 VAC
- 10A CARRYING @ 600 VAC
- 2.5A CARRYING @ 125 VDC
- 2.5A CARRYING @ 250 VDC.

## Dimensions

|                             |                               |
|-----------------------------|-------------------------------|
| Height                      | 1.875 in                      |
| Width                       | 2.375 in                      |
| Length                      | 6.75 in                       |
| Gross Weight with Packaging | 0.57                          |
| Dimensions                  | 6.75 in x 2.375 in x 1.875 in |

## General

|        |                 |
|--------|-----------------|
| Color  | Black           |
| UPC    | 783936221991    |
| Type   | Selector Switch |
| Series | GO Series       |

## Operational

|          |                            |
|----------|----------------------------|
| Actuator | 2 Position Selector Switch |
| Action   | Rotary                     |

## Product Assets

[Catalog \[English\]](#)