



G Series -Long 120V Pilot Light Operator - Red Lens With Blank Nameplate

By Killark
Catalog # [GOB3-R23C N34](#)

G Series - Aluminum Long 120V Pilot Light Operator - Red Lens With Blank Nameplate



Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

CSA File Number	LR11714
EU RoHS Indicator	Contact Manufacturer
Nema Rating	3, 4, 4X
UL File Number	E12379
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups B, C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G

- Class III, Divisions 1 & 2

Current

Frequency Rating	50/60 Hz
Amperage Rating	0.025 A
Voltage Rating	250 V

Dimensions

Length	6.31 in
Depth	2-3/4 in
Height	1.25 in
Width	2.25 in
Gross Weight with Packaging	0.5
Dimensions	6.31 in x 2.25 in x 1.25 in

General

Color	Red
Series	GO Series
UPC	783936997193
Type	Indicator

Operational

Actuator	Pilot Light
Operating Cycles	10,000 hrs