



GOB4-C230CN34CN

By Killark

Catalog # [GOB4-C230CN34CN](#)

G Series - Aluminum ATEX Certified Long 120V Illuminated Push Button(Push To Test Pilot Light) Operator - Clear Lens With Blank Nameplate -Without Contacts.



Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

General

Action	Momentary
Actuator	Pilot Light and Momentary Pushbutton
Ambient Temp. Range	UL: -25 to 40 °C, CSA: -50 to 40 °C, IEC: -20 to 40 °C
Application	
Catalog Number	GOB4-C230CN34CN
Color	Clear
	Clair
EU RoHS Indicator	Contact Manufacturer
Operating Cycles	10,000 hrs
Series	GO
Type	
UPC	783936225708

Dimensions

Depth	4
Gross Weight with Packaging	1

Electrical Ratings

Amperage Rating	10 A
Frequency Rating	50/60 Hz
Voltage Rating	250 V

Certifications And Compliance

ATEX File Number	03ATEX 1203 U
CSA File Number	LR11714
Hazardous Rating(s)	Class I, Divisions 1 & 2, Groups B, C, D
	Class I, Zones 1 & 2, Groups IIB, IIA
	Class II, Divisions 1 & 2, Groups E, F, G
	Class III, Divisions 1 & 2
Nema Rating	3, 4, 4X
UL File Number	E12379

Product Assets

[Certifications - GO Series Pilot Lights ATEX Certificate](#)
[Certifications - GO Series Pilotlights Attestation of Conformity](#)
[Certifications - GO Series Pilot Lights UL Certification](#)
[Certifications - GO Series Operators CSA Certificate of Compliance](#)
[Customer Notices - Prop 65 Notice](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-GOB4C230CN34CN-SPEC-EN | REV 6/2024