



GOL4R3CN - G Series, AL ATEX Cert Ext 120V Illuminated Push Button (Push To Test Pilot Light) Op, Red Lens w/ Blank Nameplate, 1 No/1NC Contact Rating

By Killark  
Catalog # GOL4R3CN

G Series - Aluminum ATEX Certified Extended 120V Illuminated Push Button(Push To Test Pilot Light) Operator - Red Lens With Blank Nameplate - 1 No/1NC Contact Rating

Features

- Operators are all aluminum except for certain movable parts which are stainless steel.
- All other parts such as screws are either stainless steel or plated steel.
- Threaded bodies are all 3/4"-14 NPSM thread.
- Control stations can be grouped into a single assembly thus reducing installation time and cost.

Application

G Series custom control panel operators are designed for use in hazardous locations when installed in suitable enclosures such as B7E, EXB, XJB, DB, SWB, and GCS Series boxes and B7, Y7 starter enclosures.

Specifications

|                          |                                                                                                                                                                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ATEX File Number         | 03ATEX 1203 U                                                                                                                                                                                                                                       |
| CSA File Number          | LR11714                                                                                                                                                                                                                                             |
| Nema Rating              | 3, 4, 4X                                                                                                                                                                                                                                            |
| UL File Number           | E12379                                                                                                                                                                                                                                              |
| Buy America(n) Qualified | Contact Manufacturer                                                                                                                                                                                                                                |
| Hazardous Rating(s)      | <ul style="list-style-type: none"><li>• Class I, Divisions 1 &amp; 2, Groups B, C, D</li><li>• Class I, Zones 1 &amp; 2, Groups IIB, IIA</li><li>• Class II, Divisions 1 &amp; 2, Groups E, F, G</li><li>• Class III, Divisions 1 &amp; 2</li></ul> |

Conductor

|                 |   |
|-----------------|---|
| Number Of Poles | 1 |
|-----------------|---|

Current



|                  |                                                                                                                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Rating | 50/60 Hz                                                                                                                                                                                                    |
| Amperage Rating  | 10 A                                                                                                                                                                                                        |
| Voltage Rating   | 250 V                                                                                                                                                                                                       |
| Contact Rating   | <ul style="list-style-type: none"><li>• NEMA A600 - 7200 VA (make), 720 VA (break), 10A cont. @ 600V AC (thermal)</li><li>• NEMA Q300 - 69 VA (make &amp; break), 2.5A cont. @ 250V DC (thermal).</li></ul> |

Dimensions

|                             |                            |
|-----------------------------|----------------------------|
| Length                      | 8.5 in                     |
| Depth                       | 4 in                       |
| Height                      | 3.75 in                    |
| Width                       | 3.75 in                    |
| Gross Weight with Packaging | 1                          |
| Dimensions                  | 8.5 in x 3.75 in x 3.75 in |

General

|                |              |
|----------------|--------------|
| Color          | Red          |
| Product Family | Controls     |
| Series         | GO Series    |
| UPC            | 783936225852 |
| Type           | Indicator    |

Operational

|                  |                                      |
|------------------|--------------------------------------|
| Actuator         | Pilot Light and Momentary Pushbutton |
| Action           | Momentary                            |
| Operating Cycles | 10,000 operations                    |

Product Assets

[Catalog \[English\]](#)