KILLARK®

GRSS-3L - 1″ Aluminum GRSS Outlet Body, 7 Internal Hub Config with Mounting Lugs

By Killark
Catalog # GRSS-3L

1″ Aluminum GRSS Outlet Body, 7 Internal Hub Config with Mounting Lugs

Features

- Internal hubs
- Blank cover included (Cat. No. GRRBC)
- Compact design and multiple hub configurations
- Furnished with internal ground screw
- Cast-in brackets on cover for use with breaker-bar tools
- Finished with 7 internal hubs:Comes with mounting lugs

Application

Conduit boxes installed in conduit systems within hazardous areas to: protect conductors in threaded rigid conduit, act as pull and splice boxes, interconnect lengths of conduit, change conduit direction, and provide access to conductors for maintenance and future system changes.

Specifications

UL File Number	E10514
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11716
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
EU RoHS Indicator	Contact Manufacturer

Dimensions

Hub Size	1″
Gross Weight with Packaging	2.85

General

Color	Gray
UPC	783936073798
Type	Outlet Body With Cover & Mounting Lugs
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Cover Type	Blank
Finish Type	Powder Epoxy Paint
Series	GR Outlet Bodies Series

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved