KILLARK®

LR888 - 3″ LR Hub, Iron Duraloy 8 Conduit Body

By Killark
Catalog # LR888

3″ LR Hub, Iron Duraloy 8 Conduit Body

Features

- Completely interchangeable with competative bodies, gaskets, and covers.
- Flat back design provides greater cubic capacity for easier wire pulling and more room for splicing.
- Raintight when used with gasketed covers.
- Stainless steel screws on stamped and cast covers.
- Smooth integral wire bushings.

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

Specifications

UL File Number	E3397
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).

Configuration

Hub Pattern	LR

Dimensions

Height	5 in
Width	7 in
Hub Size	3″
Length	14 in
Gross Weight with Packaging	14.2
Dimensions	14 in x 7 in x 5 in

General

Color	Gray
Product Family	Fittings
UPC	783936481302
Type	Conduit Body
Material	Iron
Finish Type	Powder Epoxy Paint
Series	Duraloy 8 Series

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved