KILLARK®

MOLBD-6 - 2″ LB Hub, Aluminum Mogul Conduit Body

By Killark
Catalog # MOLBD-6

2″ LB Hub, Aluminum Mogul Conduit Body

Features

- A raised dome cover permits additional wiring room
- Furnished with captive ss screws and gasket
- LBD, C and UB Series available with builtin cable-pulling rollers on sizes 1-1/2" and larger. Add -WR to catalog number. Example MOLBD-5-WR.

Application

Mogul fittings are for use with rigid and IMC raceways. Use where standard conduit bodies do not provide adequate access and wiring area for the pulling of large and heavy conductors. For right angle bends where splices, pulls, and taps are needed in a we

Specifications

Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
EU RoHS Indicator	Contact Manufacturer

Configuration

Hub Pattern	LB

Dimensions

Height	6 in
Width	3 in
Hub Size	2″
Length	15 in
Gross Weight with Packaging	5.9
Dimensions	15 in x 3 in x 6 in

General

Color	Gray
UPC	783936555508
Type	Mogul Conduit Body With Cover & Gasket
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Powder Epoxy Paint
Series	Moguls Series

© 2026 Hubbell Incorporated. All rights reserved