KILLARK®

# MOLBD-6M - 2″ LB Hub, Iron Mogul Conduit Body

By Killark
Catalog # MOLBD-6M

2″ LB Hub, Iron Mogul Conduit Body

## Features

- A raised dome cover permits additional wiring room
- Furnished with captive ss screws and gasket
- LBD, C and UB Series available with builtin cable-pulling rollers on sizes 1-1/2" and larger. Add -WR to catalog number. Example MOLBD-5-WR.

## Application

Mogul fittings are for use with rigid and IMC raceways. Use where standard conduit bodies do not provide adequate access and wiring area for the pulling of large and heavy conductors. For right angle bends where splices, pulls, and taps are needed in a we

## Specifications

| | |
|---|---|
| Hazardous Rating(s) | Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2). |
| EU RoHS Indicator | Contact Manufacturer |

## Configuration

| | |
|---|---|
| Hub Pattern | LB |

## Dimensions

| | |
|---|---|
| Height | 6 in |
| Width | 3 in |
| Hub Size | 2″ |
| Length | 15 in |
| Gross Weight with Packaging | 15.2 |
| Dimensions | 15 in x 3 in x 6 in |

## General

| | |
|---|---|
| Color | Glossy gray |
| UPC | 783936555348 |
| Type | Mogul Conduit Body With Cover & Gasket |
| Material | Iron |
| Finish Type | Powder Epoxy Paint |
| Series | Moguls Series |



© 2026 Hubbell Incorporated. All rights reserved