KILLARK®

OC-3 - 1″ C Hub, Aluminum O Series Conduit Body

By Killark
Catalog # OC-3

1″ C Hub, Aluminum O Series Conduit Body

Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

Specifications

CSA File Number	LR11852
EU RoHS Indicator	Contact Manufacturer
UL File Number	E3397
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).

Configuration

Hub Pattern	C

Dimensions

Hub Size	1″
Length	8 in
Weight	0.5 lb.
Height	2 in
Width	2 in
Gross Weight with Packaging	0.5
Dimensions	8 in x 2 in x 2 in

General

Color	Gray
Series	O Series
UPC	783936450032
Type	Conduit Body
Material	Aluminum, Copper Free (less than 4/10 of 1%)

Logistics

Carton Quantity	5

© 2026 Hubbell Incorporated. All rights reserved