KILLARK®

OLB-0M - 4″ LB Hub, Iron O Series Conduit Body

By Killark
Catalog # OLB-0M

4″ LB Hub, Iron O Series Conduit Body

Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

Specifications

UL File Number	E3397
Buy America(n) Qualified	Contact Manufacturer
CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
EU RoHS Indicator	Contact Manufacturer

Configuration

Hub Pattern	LB

Dimensions

Height	8.5 in
Width	10.75 in
Hub Size	4″
Length	18.875 in
Gross Weight with Packaging	21.72
Dimensions	18.875 in x 10.75 in x 8.5 in

General

Color	Gray
UPC	783936480510
Type	Conduit Body
Material	Iron
Series	O Series

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved