



R-106 - 4" to 2" Reducing Bushing, Aluminum

By Killark
Catalog # [R-106](#)

4" to 2" Reducing Bushing, Aluminum



Features

- Tapered threads (NPT)
- Smooth internal bushing protects conductors
- Threaded for Rigid Conduit or IMC

Application

To reduce the trade size of a taped hole or hub.

Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G

Dimensions

Hub Size	4" to 2"
Length	6.125 in
Height	4.25 in
Width	6 in
Gross Weight with Packaging	1.92
Dimensions	6.125 in x 6 in x 4.25 in

General

Color	Silver
Series	R Series
UPC	783936565347
Type	Reducing Bushing
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Natural

Logistics

Carton Quantity	2
-----------------	---

Product Assets

- [Catalog \[English\]](#)
[Installation Manual \[English\]](#)