KILLARK®

R-63 - 2″ to 1″ Reducing Bushing, Aluminum

By Killark
Catalog # R-63

2″ to 1″ Reducing Bushing, Aluminum

Features

- Tapered threads (NPT)
- Smooth internal bushing protects conductors
- Threaded for Rigid Conduit or IMC

Application

To reduce the trade size of a taped hole or hub.

Specifications

CSA File Number	LR11716
EU RoHS Indicator	Contact Manufacturer
UL File Number	E10514
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups A, B, C, D • Class I, Zones 1 & 2, Groups IIC, IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G

Dimensions

Hub Size	2″ to 1″
Length	2.38 in
Weight	0.3 lb.
Height	0.99 in
Width	2.38 in
Gross Weight with Packaging	0.3
Dimensions	2.38 in x 2.38 in x 0.99 in

General

Color	Silver
Series	R Series
UPC	783936570136
Type	Reducing Bushing
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Natural

Logistics

Carton Quantity	10

Product Assets

Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved