KILLARK®

TB67SA - 2″ TB Hub, Aluminum Duraloy 7 Conduit Body,

By Killark
Catalog # TB67SA

2″ TB Hub, Aluminum Duraloy 7 Conduit Body,

Features

- Enhanced sealing capabilities neoprene sealing gaskets provide a NEMA 3 Seal.
- Suitable for wet locations when used with gaskets.
- High-quality sealing hardware 316 stainless steel cover screws and washers with neoprene gaskets.
- Innovative spring clip design for installation ease and repeat usage.
- For use with threaded rigid conduit steel or aluminum.
- Flat-back design for greater wiring capacity and mounting stability.

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

Specifications

UL File Number	E3397
CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
EU RoHS Indicator	Contact Manufacturer

Configuration

Hub Pattern	TB

Dimensions

Height	3.875 in
Width	6.25 in
Hub Size	2″
Length	9.625 in
Gross Weight with Packaging	1.88
Dimensions	9.625 in x 6.25 in x 3.875 in

General

Color	Gray
UPC	783936080758
Type	Conduit Body
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Finish Type	Powder Epoxy Paint
Series	Duraloy 7 Series

Product Assets

Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved