



UGP Series - 20 Amp 250VAC Interchangeable Blade Style Plug With Quick Wiring - NEMA Configuration 6-20P

By Killark
Catalog # [UGP-20232QW](#)

UGP Series - Aluminum 20 Amp 250VAC Interchangeable Blade
Style Plug With Quick Wiring - NEMA Configuration 6-20P

Features

- Factory sealed chamber in UGR receptacle contains switch's arcing components.
- Spring loaded receptacle cover closes when plug is removed.
- Copper-free aluminum (less than 4/10 of 1%) alloy resists corrosion
- Electrostatically applied and baked powder epoxy/polyester finish
- ACCEPTOR® plugs conform to NEMA configurations, while it's "turn to engage" feature locks in plug and can be used to prevent accidental disengagement of critical equipment.
- Plugs for use with type S/SO/ST/STO heavy duty cord.

Application

Petroleum refineries, chemical plants, wet/damp areas, corrosive environments, petroleum plants, grain elevators/feed mills, flour and feed mills, and indoor or outdoor locations

Specifications

EU RoHS Indicator	Contact Manufacturer
Nema Rating	3, 4, 4X
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups F, G • Class III, Divisions 1 & 2



Conductor

Number Of Wires	3
Wire Size	#10 AWG, #12 AWG, or #14 AWG
Number Of Poles	2

Current

Amperage Rating	20 A
-----------------	------

Dimensions

Length	6.625 in
Height	1.875 in
Width	2.375 in
Gross Weight with Packaging	0.4
Dimensions	6.625 in x 2.375 in x 1.875 in

General

Color	Gray
Series	UGP Series
UPC	783936076676
Type	Straight Blade
Receptacle Type	Delayed Action
Material	Aluminum, Copper Free (less than 4/10 of 1%)

Product Assets

[Installation Manual \[English\]](#)