KILLARK®

# Versamate Series 100A 2 Pole 2 Wire Plug Assembly

By Killark
Catalog # VP10277

100A 2 Pole 2 Wire Plug Assembly

## Features

- Feature an octagonal body style, ensuring a sure grip when connecting or disconnecting.
- Insulators have high mechanical and dielectric strength.
- “Increased Safety” type box terminals with gripper ribs securely clamp around conductors.
- Funneled conductor entry chambers lead all properly stripped conductors into terminals simultaneously.
- Type 4X rating when inserted into VersaMate receptacle and locking ring is tightened.
- Includes suitability for Type P marine cable.

## Application

Suitable for indoor or outdoor use. Applications include the wet, cold, hosedown, hazardous or corrosive areas in such industrial applications as:Pulp & Paper Mills, Electrical Power Plants, Petrochemical Plants, Wastewater Treatment, Marine, Docks, Ports, Construction Sites, Breweries, Refineries, Chemical Plants, Grain Facilities , Textile Manufacturing, Food Processing Facilities

## Specifications

| | |
|---|---|
| Buy America(n) Qualified | Contact Manufacturer |
| EU RoHS Indicator | Contact Manufacturer |

## Conductor

| | |
|---|---|
| Number Of Wires | 2 |

## Current

| | |
|---|---|
| Frequency Rating | 50-400 Hz |
| Amperage Rating | 100 A |
| Voltage Rating | • 600 VAC<br>• 250 VDC |

## Dimensions

| | |
|---|---|
| Height | 4.25 in |
| Width | 4.25 in |
| Grommet Range | 0.88-1.68 |
| Length | 10.87 in |
| Dimensions | 10.87 in x 4.25 in x 4.25 in |

## General

| | |
|---|---|
| Style | Style I |
| UPC | 783936834726 |
| Type | Pin & Sleeve |
| Material | • Body-Copper-free aluminum<br>• Contacts-Brass<br>• Spring tensioner-Patented beryllium copper<br>• External screws-316 stainless steel |
| Finish Type | Baked Powder Epoxy/Polyester Finish |
| Series | VersaMate Series |

## Product Assets

Catalog [English]
Installation Manual [English]



© 2026 Hubbell Incorporated. All rights reserved