



Versamate Series 60A 3P 3W Connector Assembly

By Killark
Catalog # [VPR6355](#)

60A 3W3P Connector Assembly



Features

- Feature an octagonal body style, ensuring a sure grip when connecting or disconnecting.
- Insulators have high mechanical and dielectric strength.
- “Increased Safety” type box terminals with gripper ribs securely clamp around conductors.
- Funneled conductor entry chambers lead all properly stripped conductors into terminals simultaneously.
- Type 4X rating when inserted into VersaMate receptacle and locking ring is tightened.
- Includes suitability for Type P marine cable.

Application

Suitable for indoor or outdoor use. Applications include the wet, cold, hosedown, hazardous or corrosive areas in such industrial applications as:Pulp & Paper Mills, Electrical Power Plants, Petrochemical Plants, Wastewater Treatment, Marine, Docks, Ports, Construction Sites, Breweries, Refineries, Chemical Plants, Grain Facilities , Textile Manufacturing, Food Processing Facilities

Specifications

Buy America(n) Qualified Contact Manufacturer

Conductor

Number Of Wires 3

Current

Frequency Rating 50-400 Hz
Amperage Rating 60 A
Voltage Rating • 600 VAC

- 250 VDC

Dimensions

Height 4.37 in
Width 4.37 in
Grommet Range 0.65-1.50
Length 9.68 in
Dimensions 9.68 in x 4.37 in x 4.37 in

General

Style Style I
Product Family Plugs & Receptacles
UPC 783936834467
Type Pin & Sleeve
Material • Body-Copper-free aluminum
 • Contacts-Brass
 • Spring tensioner-Patented beryllium copper
 • External screws-316 stainless steel

Finish Type Baked Powder Epoxy/Polyester Finish

Series VersaMate Series

Logistics

Carton Quantity 1 EA

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)