KILLARK®

Versamate Series 60A 2 Pole 2 Wire Receptacle - E Type Box - 1-1/2"

By Killark
Catalog # VR621E5

VERSA RECPT STYLE I 60A 2W2P ETYPE 1-1/2

Features

- Patented “Breech-Lock” cap serves as both flip lid and screw cover.
- Patented notch in cap arm holds cap open for easy plug insertion or maintenance.
- Type 4X rating when inserted into VersaMate receptacle and locking ring is tightened.Patented pin design uses slotted spring clip which avoids excessive wear while providing continuous electrical pin to sleeve contact.
- “Increased Safety” type box terminals with gripper ribs securely clamp around conductors.
- Boxes come with a green grounding screw.

Specifications

EU RoHS Indicator	Contact Manufacturer

Conductor

Number Of Poles	2
Number Of Wires	2

Configuration

Back Box Type	DEAD END

Current

Frequency Rating	50-400 Hz
Amperage Rating	60 A
Voltage Rating	• 685 VAC • 250 VDC

Dimensions

Hub Size	1-1/2"

General

Style	Style I
UPC	783936842479
Type	Pin & Sleeve
Material	• Body-Copper-free aluminum • Contacts-Brass • Spring tensioner-Patented beryllium copper • External screws-316 stainless steel
Finish Type	Baked Powder Epoxy/Polyester Finish
Series	VersaMate Series

Product Assets

Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved