KILLARK®

# Versamate Series 60A 2 Pole 3 Wire Receptacle - D Type Box - 1-1/4"

By Killark
Catalog # VR632D4

VERSA REC STYLE II 60A 2W3P DTYPE 1-1/4

## Features

- Patented “Breech-Lock” cap serves as both flip lid and screw cover.
- Patented notch in cap arm holds cap open for easy plug insertion or maintenance.
- Type 4X rating when inserted into VersaMate receptacle and locking ring is tightened.Patented pin design uses slotted spring clip which avoids excessive wear while providing continuous electrical pin to sleeve contact.
- “Increased Safety” type box terminals with gripper ribs securely clamp around conductors.
- Boxes come with a green grounding screw.

## Specifications

| | |
|---|---|
| EU RoHS Indicator | Contact Manufacturer |

## Conductor

| | |
|---|---|
| Number Of Poles | 2 |
| Number Of Wires | 3 |

## Configuration

| | |
|---|---|
| Back Box Type | ANGLED FEED THRU |

## Current

| | |
|---|---|
| Frequency Rating | 50-400 Hz |
| Amperage Rating | 60 A |
| Voltage Rating | • 699 VAC<br>• 250 VDC |

## Dimensions

| | |
|---|---|
| Hub Size | 1-1/4" |

## General

| | |
|---|---|
| Style | Style II |
| UPC | 783936842790 |
| Type | Pin & Sleeve |
| Material | • Body-Copper-free aluminum<br>• Contacts-Brass<br>• Spring tensioner-Patented beryllium copper<br>• External screws-316 stainless steel |
| Finish Type | Baked Powder Epoxy/Polyester Finish |
| Series | VersaMate Series |

## Product Assets

Installation Manual [English]



© 2026 Hubbell Incorporated. All rights reserved