



Versamate Series 60A 2 Pole 3 Wire Receptacle - E Type Box - 1"

By Killark
Catalog # [VR632E3](#)

1" 2W3P STYL2 60A RECEPTACLE TYPE E

Features

- Patented “Breech-Lock” cap serves as both flip lid and screw cover.
- Patented notch in cap arm holds cap open for easy plug insertion or maintenance.
- Type 4X rating when inserted into VersaMate receptacle and locking ring is tightened.Patented pin design uses slotted spring clip which avoids excessive wear while providing continuous electrical pin to sleeve contact.
- “Increased Safety” type box terminals with gripper ribs securely clamp around conductors.
- Boxes come with a green grounding screw.

Specifications

EU RoHS Indicator Contact Manufacturer

Conductor

Number Of Poles 2
Number Of Wires 3

Configuration

Back Box Type DEAD END

Current



Frequency Rating 50-400 Hz
Amperage Rating 60 A
Voltage Rating • 701 VAC
 • 250 VDC

Dimensions

Hub Size 1"

General

Style Style II
UPC 783936842721
Type Pin & Sleeve
Material • Body-Copper-free aluminum
 • Contacts-Brass
 • Spring tensioner-Patented beryllium copper
 • External screws-316 stainless steel

Finish Type Baked Powder Epoxy/Polyester Finish

Series VersaMate Series

Product Assets

[Installation Manual \[English\]](#)