KILLARK®

X38 - 1″ X Hub, Iron Duraloy 8 Conduit Body,

By Killark
Catalog # X38

1″ X Hub, Iron Duraloy 8 Conduit Body,

Features

- Completely interchangeable with competative bodies, gaskets, and covers.
- Flat back design provides greater cubic capacity for easier wire pulling and more room for splicing.
- Raintight when used with gasketed covers.
- Stainless steel screws on stamped and cast covers.
- Smooth integral wire bushings.

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

Specifications

CSA File Number	LR11852
UL File Number	E3397
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).

Configuration

Hub Pattern	X

Dimensions

Hub Size	1″
Length	8 in
Height	3 in
Width	4 in
Gross Weight with Packaging	3.2
Dimensions	8 in x 4 in x 3 in

General

Color	Gray
Product Family	Fittings
Series	Duraloy 8 Series
UPC	783936481470
Type	Conduit Body
Material	Iron
Finish Type	Powder Epoxy Paint

Logistics

Carton Quantity	2

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved