KILLARK®

# X47SA - 1-1/4″ X Hub, Aluminum Duraloy 7 Conduit Body,

By Killark
Catalog # X47SA

1-1/4″ X Hub, Aluminum Duraloy 7 Conduit Body,

## Features

- Enhanced sealing capabilities neoprene sealing gaskets provide a NEMA 3 Seal.
- Suitable for wet locations when used with gaskets.
- High-quality sealing hardware 316 stainless steel cover screws and washers with neoprene gaskets.
- Innovative spring clip design for installation ease and repeat usage.
- For use with threaded rigid conduit steel or aluminum.
- Flat-back design for greater wiring capacity and mounting stability.

## Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

## Specifications

| | |
|---|---|
| UL File Number | E3397 |
| CSA File Number | LR11852 |
| Hazardous Rating(s) | Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2). |
| EU RoHS Indicator | Contact Manufacturer |

## Configuration

| | |
|---|---|
| Hub Pattern | X |

## Dimensions

| | |
|---|---|
| Height | 3.75 in |
| Width | 6 in |
| Hub Size | 1-1/4″ |
| Length | 9.625 in |
| Gross Weight with Packaging | 1.31 |
| Dimensions | 9.625 in x 6 in x 3.75 in |

## General

| | |
|---|---|
| Color | Gray |
| UPC | 783936080611 |
| Type | Conduit Body |
| Material | Aluminum, Copper Free (less than 4/10 of 1%) |
| Finish Type | Powder Epoxy Paint |
| Series | Duraloy 7 Series |

## Product Assets

Installation Manual [English]



© 2026 Hubbell Incorporated. All rights reserved