



XAL Series - Feed-Thru Fire Alarm Station With Pull-Ring Activation - Hub Size 3/4 Inch Npt - 1NO/1NC Contact Rating

By Killark
Catalog # [XAL-53](#)

XAL Series - Aluminum Feed-Thru Fire Alarm Station With Pull-Ring Activation - Hub Size 3/4 Inch Npt - 1NO/1NC Contact Rating

Features

- Enclosure is made of copper free aluminum alloy
- Conduit openings are 3/4" NPT feed through.
- Red, textured powder epoxy paint finish is standard on box and cover to provide high visibility for alarm station.
- Bilingual nameplates included per CSA requirement.
- Internal ground screw is standard.
- The alarm station is activated by lifting the front cover and pulling down ring. This quick easy to use two-step process prevents unintentional operation.

Application

Hazardous areas due to the presence of flammable gases or vapors, combustibile dusts, or easily ignitable fibers or flyings. Installation at petroleum refineries, chemical and petrochemical plants, storage areas, and other processing facilities where hazardous substances are handled or stored. Areas where emergency control of fire alarm or signal circuits is required.

Specifications

CSA File Number	LR31085
EU RoHS Indicator	Contact Manufacturer
UL File Number	E50498
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2

Conductor

Number Of Poles	1
-----------------	---

Configuration



Back Box Type	SWB
Current	
Frequency Rating	50/60 Hz
Amperage Rating	10 A
Contact Rating	• 7200 VA (make), 720 VA (break), 10A cont. @ 600V AC • 2.5A cont. @ 600V DC.
Dimensions	
Length	7.5 in
Depth	4-1/2 in
Weight	2.67 lb.
Height	4 in
Width	6 in
Gross Weight with Packaging	2.67
Dimensions	7.5 in x 6 in x 4 in
General	
Color	Red
Series	XAL Series
UPC	783936880389
Type	Aluminum Fire Alarm Station With Pull-Ring Activation
Logistics	
Carton Quantity	1
Operational	
Actuator	Lift Cover, Pull ring
Action	SP
Product Assets	
	Installation Manual [English]